



## FINAL PROJECT CONCEPT STATEMENT

Bridge over Burlington Northern Railroad  
Union Pacific Railroad and Taft Street,  
on IA 376, 0.1 mile south of County Road D12

Woodbury County  
BRF-376-1(6)--38-97  
PIN: 10-97-376-020  
Maint. No. 9799.0R376  
FHWA No. 53070

Highway Division  
Office of Design

Kevin K. Patel, P.E.  
515-239-1540

August 22, 2011

### I. STUDY AREA

#### A. Project Description

This project involves the IA 376 northbound bridge replacement (Maint. No. 9799.0R376) over the Burlington Northern Railroad, Union Pacific Railroad and Taft Street, 0.1 mile south of County Road D12.

#### B. Need for Project

The bridge is functionally obsolete due to the deck geometry. The bridge width is 28' which is substandard. The bridge was designed for live loads below current standards. The current overlay is near the end of its useful life and the bottom of the deck has several hollow areas and spalls with exposed steel and leaching transverse cracks. The steel girders have several fatigue cracks in 3 girders of the 4 girder cross section and both exterior beams have already been strengthened; therefore this bridge should be replaced.



C. Present Facility

The existing structure is a 514' x 28' steel beam bridge constructed in 1956 and overlaid in 1984.

IA 376 in the project area is 24' wide PCC pavement with 10' wide partial paved shoulders and 3:1 foreslopes, constructed in 1957. HMA resurfacing was accomplished in 2007.

D. Traffic Estimates

The 2015 and 2035 average daily traffic estimates are 8,400 ADT with 10% trucks and 13,100 ADT with 11% trucks, respectively.

E. Sufficiency Ratings

IA 376 is classified as an "area development" route and is a maintenance service level "B" road with a sufficiency rating of 83. The federal bridge sufficiency rating is 47.

F. Access Control

Access rights will not be acquired for this project.

G. Crash History

During the five-year study period from January 1, 2006 through December 31, 2010, there were three crashes involving the bridge including, one possible unknown personal injury crash, and two property damage only crashes.

## II. PROJECT CONCEPT

A. Feasible Alternative-Replace with a Concrete Beam Bridge

Replace the existing 507' x 28' steel beam bridge with a 563' x 40' pretensioned prestressed concrete beam bridge, placed at a 52 degree right ahead skew. The typical cross section adjacent to the bridge will consist of a 24 ft. roadway (26 ft. pavement) with 6 ft. inside and 10 ft. outside, partial paved 4 ft. shoulders and 6:1/3.5:1 foreslopes. The overall cross section is two 24 ft. roadways and a 66 ft. median. The bridge will be built on the existing horizontal alignment. The vertical alignment will be raised in order to meet the minimum vertical clearance over the existing railroad below the bridge. This will require approximately 1,000 ft of new roadway

reconstruction. (See attached plan and profile sheets for the adjustments to the vertical alignment.) It should be noted that the preferred standard for the grade and the K value for the crest vertical curve are not met. However, they do meet the acceptable standards. Construct new bridge approaches. Replace the existing guardrail with new guardrail and pave the shoulders 20 ft. beyond the ends of the guardrail. Class 10 will be necessary to flatten the existing foreslopes and to construct the new guardrail blisters. Place macadam stone for slope protection under the bridges. Construct bridge end drains on each end of the bridge.

Apply erosion control and rural seeding and fertilizing to all disturbed areas.

It appears that no right of way will be required for this project.

Traffic will be maintained by one lane of traffic in each direction on the southbound lanes via the use of median crossovers. Prior to the placement of the crossover south of the bridge the existing median crossover should be removed.

<u>Item</u>	<u>Estimated Cost</u>
New Bridge	\$ 2,077,000
Removal Existing Bridge	160,000
Mobilization @ 10%	223,700
M&C @ 15%	<u>369,100</u>
<b>Bridge Total</b>	<b>\$ 2,829,800</b>

New Pavement	\$129,000
Granular Subbase	16,700
Paved Shoulder	18,000
Granular Shoulder	3,900
Bridge Approaches	48,900
Pavement Removal	20,300
Class 10 Roadway and Borrow	151,800
Excavation Class 13 Waste	12,100
Guardrail (Removal and Install New)	15,300
Paved Shoulders for Guardrail	9,200
Class 10 for Guardrail Blisters	3,700
Bridge End Drains	10,900
Longitudinal Subdrains and Outlets	9,500
Milled Rumble Strips	1,100
Clearing and Grubbing	4,200
Seeding and Fertilizing	1,200
Wetland Mitigation	50,000
Removal of Existing Crossover	33,000
New Median Crossovers	225,200
Traffic Control@5%	38,200



Mobilization@ 5%	38,200
M&C @ 30%	<u>252,100</u>
<b>Roadway Total</b>	<b>\$ 1,092,500</b>
<b>Project Total</b>	<b>\$3,922,300</b>

B. Detour Analysis

Traffic will be maintained by the use of median crossovers. (See attached sheet 2 of the plan sheets attached.) Both crossovers are within mainline horizontal curves, therefore; the geometrics for the crossovers will need to accommodate the mainline superelevation. The speed limit will need to be lowered to 45 MPH during construction.

The northbound exit loop to Taft Street will be closed to traffic during construction.

C. Recommendations

It is recommended that the present structure be replaced, as described above.

D. Construction Sequence

It is anticipated that all work on this project will be awarded to one prime contractor. The Office of Bridges and Structures will coordinate the plan preparation with assistance from the Office of Design.

E. Special Considerations

The design criteria has been established and approved by the Office of Design Director. The preferred values in Chapter 1C-1 of the IDOT Design Manual were not met but in all cases the acceptable values were met or exceeded.

A steel beam bridge was considered but rejected due to increase in cost, possible construction issues over two live tracks and steel availability.

No bike path or sidewalk will be required as part of this project.

It appears Right of Way will not be required for this project.

The Office of Location and Environment has completed their review and have the following recommendations:

1. Federal and state laws require that impacts to wetlands and streams be avoided

and minimized. Project design should focus on the least environmentally damaging, practicable alternative.

Project specific recommendations include the following:

1. Based on the information provided in the Draft Concept and discussions at the DO field exam, we have determined that a Section 404 Permit will NOT be required for this work, provided that the wetland area located adjacent to northbound IA 376 is avoided.

If the project concept changes, additional ROW becomes necessary, or extra work is identified during construction, further review by this office may be required.

The Office of Location and Environment Cultural Resource Section commented that this bridge was recently found eligible for nomination to the National Register of Historic Places as it meets the 95<sup>th</sup> percentile (over 400 feet) requirement for overall length of a Type 302 steel stringer bridge. As replacement of this bridge will constitute an adverse effect to a historic property, the DOT will be required to mitigate for the loss of this historic property.

A phase I archaeological investigation of any new easement or borrow areas may also be required.


#### F. Program Status

Site data has been developed by the Office of Design. This project is listed in the 2012-2016 Iowa Transportation Improvement Program, with \$3,312,000 programmed for replacement/repair in FY 2015. Costs for this project will be eligible for bridge replacement funds. A schedule of events will be developed following approval of the Project Concept.

KKP: jmb

# WOODBURY COUNTY


## SIOUX CITY



STA 209 + 36.3  
FHWA 53070  
MAINT. NO. 9799.0R376  
DESIGN 555



IN SIOUX CITY  
OVER R.R. & TAFT STREET,  
0.1 MILE SOUTH OF COUNTY ROAD D-12  
(NBL)]  
BRF-376-1(6)—38-97  
PIN: 10-97-376-020

WOODBURY COUNTY  
 SIOUX CITY TOWNSHIP  
 T89N R47W  
 SEC. 12



190	195	200	205	210	215				
ROAD DESIGN • CADD • PRODUCED		STATE OF IOWA	FHWA REGION 7	FISCAL YEAR	WOODBURY COUNTY	PROJECT NUMBER	BRF-376-1(6)--38-97	SHEET NUMBER	1





ROAD DESIGN • CADD • PRODUCED	STATE OF IOWA	FHWA REGION 7	FISCAL YEAR	WOODBURY COUNTY	PROJECT NUMBER	BRF-376-1(6)--38-97	SHEET NUMBER	2
-------------------------------	---------------	---------------	-------------	-----------------	----------------	---------------------	--------------	---

**WOODBURY CO.**  
**BRIDGE REPLACEMENT - PPCB**  
**BRF-376-1(6)--38-97**

LETTING DATE  
**DEC. 16, 2014**


**Iowa Department of Transportation**  
**Highway Division**

PLANS OF PROPOSED IMPROVEMENT ON THE  
**PRIMARY ROAD SYSTEM**  
**WOODBURY COUNTY**  
**BRIDGE REPLACEMENT - PPCB**  
 IN SIOUX CITY OVER R.R. AND TAFT STREET  
 0.1 MILES SOUTH OF CO. RD. D-12 (NBL)

SCALES: As Noted


Refer to the Proposal Form for list of applicable specifications.

NO MILEAGE SUMMARY



REVISIONS

	TOTAL
PROJECT IDENTIFICATION NUMBER	
10-97-376-020	
PROJECT NUMBER	
BRF-376-1(6)--38-97	
R.O.W. PROJECT NUMBER	
STPN-376-1(8)--2J-97	



**PROJECT LOCATION**

Borrow = 43,000 CY  
(Includes 30% Shrink)

For Project Location Map  
Refer to Sheet A.3

DESIGN DATA URBAN			
2015 AADT	8,400	V.P.D.	
2035 AADT	13,000	V.P.D.	
2035 DHV	--	V.P.H.	
TRUCKS	11	%	
Total Design ESALs	--		

INDEX OF SEALS		
SHEET NO.	NAME	TYPE
A.1	X	Primary Signature Block
	X	

PROJECT SCHEDULE	
EVENT	DATE
D3	11/01/12
S2	02/01/13
B1	02/01/13
D5	03/01/13
S4	03/15/13

PRELIMINARY PLANS


Subject to change by final design.

D3 PLAN – Date: Nov. 1, 2012






T-89N




**REPLACE NORTHBOUND BRIDGE  
MAINT. NO. 9799.OR376**

R-47W

# Location Map





LOCATION		DIMENSIONS				
ROAD IDENTIFICATION	STATION TO STATION	(L) Feet	(R) Feet	(X) Inches	(BW) Feet	(MW) Feet
IA 376	196+00.00 - 206+45.86	28	32	16	16	66
IA 376	212+19.37 - 213+31.10	28	32	16	16	66

Normal section shown may be modified appropriately in areas of superelevated curves or other locations specifically designated by the Engineer.


① Refer to project plan and cross sections for specific location of foreslope change.

See Plan & Profile sheets and cross sections for additional details of ditches and backslopes.

**Combination Shoulder**

Shoulder Jointing:  
Longitudinal joint: B

STATION TO STATION		(P) Feet	(G) Feet
196+00.00	204+44.44	4	2
212+68.92	213+31.10	4	Varies



Section shown in the direction of traffic.

Mainline Jointing:  
Transverse joints: CD at 20' spacing  
Longitudinal joint: L-2

4DP_ 10-19-10			
Direction of Travel	BEGIN STATION	END STATION	(MW) Feet
NB	196+00.00	205+64.39	66

**Combination Shoulder**

Shoulder Jointing:  
Longitudinal joint: B

STATION TO STATION		(P) Feet	(G) Feet
196+00.00	205+10.18	4	4
213+10.83	213+31.10	4	Varies

See Tab 100-24 for pavement quantities.  
See Tab 112-9 for shoulder quantities.

**IA 376 RECONSTRUCTION (NB LANES ONLY)**



DATUM INFORMATION

THE DATUM PLANE FOR THIS SURVEY IS RELATIVE TO N.A.V.D. 88 DATUM. BENCHES WERE RAN FROM IADOT BM NO. ... TO NO. ... FOR A CHECK THEN A CLOSED LOOP WAS RAN FROM NO. ... TO NO. ....

ALL CONTROL POINT COORDINATES SHOWN ARE LOCAL PROJECT PLANE (GROUND) COORDINATES.  
 CONVERSION EQUATION GRID TO GROUND: GROUND COORD = (STATE PLANE - HOLD POINT) 1/GRID FACTOR + HOLD POINT  
 CONVERSION EQUATION GROUND TO GRID: GRID COORD = (GROUND - HOLD POINT) GRID FACTOR + HOLD POINT

HOLD POINT = G021      NORTH      EAST      GRID FACTOR      1/GRID FACTOR  
 580322.54      2455353.37      0.999936506      1.000063498

BENCH MARKS

IOWA BENCHMARKS:				ELEVATION
No. 312	Sta. 177+05.18	24.02 RT	SET IRON P IN -----	1113.796
No. 313	Sta. 187+26.17	47.29 RT	FND 1/2 REBAR -----	1114.554
No. 314	Sta. 205+83.31	42.58 LT	FND 1/2 REBAR -----	1135.385
No. 315	Sta. 223+89.28	34.59 LT	FND 1/2 REBAR -----	1130.743
No. 316	Sta. 211+74.92	43.59 LT	FND 1/2 REBAR -----	1140.025
No. 317	Sta. 241+67.79	23.96 RT	SET IRON P IN -----	1122.514
No. 500	Sta. 176+05.06	32.52 RT	CUT X ON TOP BOLT OF FIRE HYDRANT -----	1114.503
No. 501	Sta. 186+46.07	46.53 RT	CUT X ON N BOLT OF FIRE HYDRANT -----	1114.341
No. 502	Sta. 205+64.52	71.46 LT	CUT SQUARE SE HANDRAIL OF SB BRIDGE -----	1142.188
No. 503	Sta. 211+75.19	18.43 LT	FND IHC BUTTON NW WHEELGUARD NB BRIDGE -----	1144.435
No. 504	Sta. 224+46.01	34.02 RT	FND IHC BUTTON NE HANDRAIL NB BRIDGE -----	1132.281
No. 505	Sta. 211+02.63	71.16 LT	FND CUT SQUARE -----	1146.007
No. 506	Sta. 239+99.42	44.60 LT	FND DOT BUTTON INLET HDWL RCB -----	1119.286

DETAILS OF REFERENCE INFORMATION

All References are Plumb Distances  
 unless otherwise noted.

### SURVEY SYMBOLS

- ENU edge of unpaved entrance&parking
- x- FW fence wire
- ← FLD Flowline of Ditch
- TOE toe of slope
- TB top of bank
- EP edge of paved roads
- C center of roadway
- OHE Overhead electric line
- PP power pole
- GW GW Guy Wire
- Default.Point Default Point Feature
- TP TPD telephone pedestal
- St.S. --- STA storm sewer 1st co.
- CMP corrugated metal pipes
- MB MB Mailbox
- SIGN SI sign
- RET retaining walls
- FWD wood fence
- ⊕ MHE Electrical Manhole
- T1 --- TLA buried telephone line 1st co.
- ⊕ CPT Control Point Temporary
- CC control check
- CS concrete slab
- GR Ground Field Survey
- PIP pipes(cast iron,steel,tile,etc)
- ⊕ MHSN Sanitary Manhole
- ⊕ CPS Control Point Set
- ⊕ CPF Control Point Found
- ⊕ TDC tree deciduous
- TLN tree line
- RCP reinforced conc.pipe
- ▲ SCR section corner
- ROW right of way rails
- HDG hedge
- LC LC lot corner
- SHG granular shoulder
- REF reference tie points
- BD Bridge Deck
- BCL bridge centerline
- EG edge of gravel road
- ⊕ SHR shrub
- SH shoulder
- CON concrete or a/c slab
- MIS miscellaneous
- SHP paved shoulder

### UTILITY LEGEND

Where public utility fixtures are shown as existing on the plans or encountered within the construction area, it shall be the responsibility of the contractor to notify the owners of those utilities prior to the beginning of any construction. The Contractor shall afford access to these facilities for necessary modification of services. Underground facilities, structures and utilities have been plotted from available surveys and records, and therefore their locations must be considered approximate only. It is possible there may be others, the existence of which presently not known or shown. It is the Contractor's responsibility to determine their existence and exact location and to avoid damage thereto. No claims for additional compensation will be allowed to the Contractor for any interference or delay caused by such work.

The Contractor is required to utilize the utility One-Call service at (800) 292-8989 at least 48 hours prior to excavating anywhere on the project.

The following utility companies are known to have facilities on the project:

CITY OF SIOUX CITY  
 Timothy J. Higgins  
 712-279-6164  
 thiggins@sioux-city.org

MIDAMERICAN ENERGY  
 Barb Parks  
 712-233-4866  
 BTParks@midamerican.com

MCI  
 Janette Harris  
 972-729-6650  
 janette.l.harris@verizonbusiness.com

MAGELLAN MIDSTREAM PARTNERS  
 Tim Kassen  
 918-574-7351  
 tim.kassen@magellanlp.com



- San. ---
- St.S. ---
- W ---
- E1 ---
- G ---

### PLAN VIEW COLOR LEGEND OF PLAN AND PROFILE SHEETS

LINEWORK	Design Color No.	
Green	(2)	Existing Topographic Features and Labels
Blue	(1)	Proposed Alignment, Stationing, Tic Marks, and Alignment Annotation
Magenta	(5)	Existing Utilities
SHADING		
Design Color No.		
Yellow	(4)	Highlight for Critical Notes or Features
Red	(3)	Delineates Restricted Areas
Lavender	(9)	Temporary Pavement Shading
Gray, Light	(48)	Proposed Pavement Shading
Gray, Med	(80)	Proposed Granular Shading
Gray, Dark	(112)	Proposed Grade and Pave Shading
Brown, Light	(236)	Grading Shading
Tan	(8)	Proposed Sidewalk Shading
Blue, Light	(230)	Proposed Sidewalk Landing Shading
Pink	(11)	Proposed Sidewalk Ramp Shading

### PROFILE VIEW COLOR LEGEND OF PLAN AND PROFILE SHEETS



LINEWORK	Design Color No.	
Green	(2)	Existing Ground Line Profile
Blue	(1)	Proposed Profile and Annotation
Magenta	(5)	Existing Utilities
Blue, Light	(230)	Proposed Ditch Grades, Left
Black	(0)	Proposed Ditch Grades, Median
Rust	(14)	Proposed Ditch Grades, Right





## PLAN AND PROFILE LEGEND AND SYMBOL INFORMATION SHEET



(COVERS SHEET SERIES D, E, F, & K)

**IOWA 1-CALL# 1-800-292-8989**





185	190	195	200
C		ENGLISH	IOWA DOT
DESIGN TEAM		FOTH	
WOODBURY COUNTY		PROJECT NUMBER	BRF-376-1(6)--38-97
SHEET NUMBER		D.2	










Curve Data

$\Delta$	$15^{\circ} 41' 41.20''$ (RT)
T	136.72
L	271.73
R	992.00
E	9.38

Curve Data

$\Delta$	$9^{\circ} 03' 59.11''$ (LT)
T	79.92
L	159.50
R	1,008.00
E	3.16



**STAGING NOTES**

108-26A  
08-01-08

**TRAFFIC CONTROL PLAN**

108-23A  
08-01-08

Traffic on IA 376 will be maintained as two-lane, two-way traffic on the SB lanes via NB lane median crossovers. The existing exit loop from NB IA 376 to Floyd Blvd/Taft St will be closed for the duration of the project. Access to Floyd Blvd/Taft St will be detoured via Outer Drive.


Traffic control shall be in accordance with Standard Road Plan TC-61.

**TABULATION OF SPECIAL EVENTS**

102-15  
08-01-08

Event	Location	Date

- NOTES TO FINAL DESIGNER:  
 1. TL-5 BRIDGE RAILING PROPOSED.  
 2. CONSTANT 2% CROSS SLOPE FOR FULL BRIDGE LENGTH.  
 3. PIER TYPE - FRAME.  
 4. BEAM TYPE - BTB.




PROPOSED PROFILE GRADE ON N.B. IA376



TRAFFIC ESTIMATE

2015 AADT	8400	V.P.D.
2035 AADT	13,100	V.P.D.
2035 DHV		V.P.H.
TRUCKS	11	%


LONGITUDINAL SECTION ALONG CL N.B. IA376




UTILITIES LEGEND:  
TO BE DETERMINED



TYPICAL APPROACH SECTION



TYPICAL BRIDGE CROSS SECTION




SITUATION PLAN

LOCATION

N.B IA376 OVER  
 BNSF RR, CN RR & TAFT ST.  
 T-89N R-47W  
 SECTION 12  
 SIOUX CITY TOWNSHIP  
 WOODBURY COUNTY  
 BRIDGE MAINT. NO. 9799.0R376  
 LATITUDE 42.546309°  
 LONGITUDE -96.350328°

PRELIMINARY  
 DESIGN FOR 52° SKEW (R.A.)  
**563'-0 X 40'-0 PRETENSIONED  
 PRESTRESSED CONCRETE BEAM BRIDGE**  
 76'-0 END SPANS (3) 137'-0 INTERIOR SPANS  
**SITUATION PLAN**  
 STATION: 209+32.50 JAN. 2013  
**WOODBURY COUNTY**  
 IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION  
 DESIGN SHEET NO. \_\_\_ OF \_\_\_ FILE NO. ##### DESIGN NO. ###






LONGITUDINAL SECTION ALONG CL N.B. IA376

**CURVE DATA**

PI STA. 216+00.95  
 $\Delta = 26^\circ 30' 03.31''$  (RT)  
 $D = 4^\circ 59' 58.67''$   
 $T = 269.86$   
 $L = 530.06$   
 $E = 31.34$   
 $R = 1146.00$   
 $e = 6.00\%$   
 $I = 250.00$   
 $x = 77.00$

**SPIRAL DATA**


SCS PI STA. 216+12.67  
 $\Delta = 39^\circ 00' 00.00''$  (RT)  
 $\theta_s = 6^\circ 14' 58.34''$   
 $L_s = 250.00$   
 $T_s = 531.57$   
 $E_s = 72.14$   
 $P = 2.27$   
 $K = 124.95$   
 $X_c = 249.70$   
 $Y_c = 9.08$   
 $LT = 166.77$   
 $ST = 83.43$   
 $LC = 249.87$   
 $TS STA. 210+81.10$   
 $SC STA. 213+31.10$



SITUATION PLAN


**MINIMUM VERTICAL CLEARANCE**

OVERHEAD STATION = 210+15.01, OFFSET 20.08' RT.  
 OVERHEAD ELEVATION = 1145.20  
 DEPTH OF SUPERSTRUCTURE = 5.38'  
 UNDERPASS STATION = NA, OFFSET 25.00' LT.  
 UNDERPASS ELEVATION = 1116.32'  
 MINIMUM VERTICAL CLEARANCE = 23.50'




PRELIMINARY  
 DESIGN FOR 52° SKEW (R.A.)  
**563'-0 X 40'-0 PRETENSIONED  
 PRESTRESSED CONCRETE BEAM BRIDGE**  
 76'-0 END SPANS (3) 137'-0 INTERIOR SPANS  
**SITUATION PLAN**  
 STATION: 209+32.50 JAN. 2013  
**WOODBURY COUNTY**  
 IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION  
 DESIGN SHEET NO. \_\_\_ OF \_\_\_ FILE NO. ##### DESIGN NO. ###


Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




# Preliminary IA 376 NB





# Preliminary IA 376 NB



Preliminary  
IA 376 NB





Preliminary  
IA 376 NB







Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB



Preliminary  
IA 376 NB




Preliminary  
IA 376 NB







Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB



Preliminary  
IA 376 NB




Preliminary  
IA 376 NB









Preliminary  
IA 376 NB



Preliminary  
IA 376 NB





Preliminary  
IA 376 NB





110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180

Preliminary  
IA 376 NB




110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180

Preliminary  
IA 376 NB



EX.  
R/W

Preliminary  
IA 376 NB



110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180

Preliminary  
IA 376 NB






110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180


Preliminary  
IA 376 NB



110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180


Preliminary  
IA 376 NB






Preliminary  
IA 376 NB


Preliminary  
IA 376 NB




Preliminary  
IA 376 NB




Preliminary  
IA 376 NB



Preliminary  
IA 376 NB




Preliminary  
IA 376 NB





Preliminary  
IA 376 NB



Preliminary  
IA 376 NB

213+50.00

213+31.10  
1142.46

