GRADING

IM-035-3(194)87--13-77

LETTING DATE

POLK Co.

INDEX OF SHEETS

No.	DESCRIPTION
A Sheets	**Title Sheets**
A.1	Title Sheet
A.2	Location Map Sheet
A.3 - 6	Project Key Map Sheets
B Sheets	**Typical Cross Sections and Details**
B.1 - 5	Roadway Typical Sections and Details
B.6	Detour Typical Sections and Details
B.7	Chichaqua Valley Trail Typical Section
B.8	Special Ditch Typical Section
D Sheets	**Mainline Plan and Profile Sheets**
* D.1	Plan & Profile Legend & Symbol Information Sheet
* D.2 - 10	I-35 Northbound
* D.11 - 14	I-235 Northbound
* D.15	I-80 Mainline-Survey
* D.16	I-80 Mainline
E Sheets	**Side Road Plan and Profile Sheets**
* E.1	Chichaqua Valley Trail
* E.2	NE 54th Avenue
* E.3	NE 29th Street
* E.4	NE Broadway Avenue
* E.5	Special Ditches
F Sheets	**Detour or Temporary Pavement Sheets**
* F.1	DET_3_14 I-35 NB
G Sheets	**Survey Sheets**
G.1 - 2	Survey Control Points, Reference Ties & Bench Marks
G.3 - 6	Horizontal Control Alignment Geometry
G.7 - 11	Mainline andRamp Geometrics
J Sheets	**Traffic Control and Staging Sheets**
* J.1	Traffic Control & Staging Notes
* J.2	Traffic Control & Staging Legend & Symbol Info. Sheet
* J.3	Staging Overview
* J.4 - 21	Staging and Traffic Control Sheets
K Sheets	**Interchange Sheets**
* K.1 - 2	Ramp A Plan & Profile Sheets
* K.3 - 4	Ramp B Plan & Profile Sheets
* K.5 - 9	Ramp G Plan & Profile Sheets
K.10 - 15	Interchange Drainage & Site Grading
M Sheets	**Storm Sewer Sheets**
M.1	Storm Sewer Tabulations
M.2	Storm Sewer Legend & Symbol Information Sheet
M.3 - 12	Storm Sewer Plan and Profile Sheets "ML or SR Name"
N Sheets	**Traffic Signal Sheets**
N.1 - 14	Signing Locations and Detail Sheets
R Sheets	**Erosion Control Sheets**
RC.1 - 7	Sediment Control Quantities Tabulations
RR.1 - 18	Erosion Control Plan Sheets
U Sheets	**500 Series, Mod.Stds. and Detail Sheets**
U.1 - 41	Special Details
V Sheets	**Bridge and Culvert Situation Plans**
V.2 - 17	Bridge Situation Plans
V.18 - 19	Ramp B Retaining Wall Details
V.20	Ramp B Retaining Wall Plan & Profile
W Sheets	**Mainline Cross Sections**
W.1	Cross Sections Legend & Symbol Information Sheet
W.2 - 85	Mainline Cross Sections

H Sheets

IOWA DOT

Highway Division

PLANS OF PROPOSED IMPROVEMENT ON THE

INTERSTATE ROAD SYSTEM

POLK COUNTY

GRADING

I-35/80/235

I-35/80/235 Interchange Northeast of Des Moines (Stage 3A)

SCALES: As Noted

Refer to the Proposal Form for list of applicable specifications.

Value Engineering Saves. Refer to Article 1105.14 of the Specifications.

IOWA ONE CALL
1-800-292-8989
www.iowaonecall.com
811 Know what's below. Call before you dig.


REVISIONS

TOTAL

PROJECT IDENTIFICATION NUMBER
10-77-035-010-03
PROJECT NUMBER
IM-035-3(194)87--13-77
R.O.W. PROJECT NUMBER

X Sheets	**Side Road Cross Sections**
X.1 - 15	Side Road Cross Sections
Y Sheets	**Ramp Cross Sections**
Y.1 - 65	Ramp Cross Sections
	* Color Plan Sheets

For Project Location Map
Refer to Sheet A.2



INTERSTATE 235 DESIGN DATA URBAN		
2012 AADT	63,000	V.P.D.
2050 AADT	105,600	V.P.D.
2050 DHV	11,000	V.P.H.
TRUCKS	9	%
Total Design ESALs	--	

INTERSTATE 35 DESIGN DATA URBAN		
2012 AADT	75,200	V.P.D.
2050 AADT	125,800	V.P.D.
2050 DHV	13,000	V.P.H.
TRUCKS	14	%
Total Design ESALs	--	

INTERSTATE 80 DESIGN DATA URBAN		
2012 AADT	84,100	V.P.D.
2050 AADT	133,900	V.P.D.
2050 DHV	13,900	V.P.H.
TRUCKS	19	%
Total Design ESALs	--	

ROADWAY DESIGN

LICENSED PROFESSIONAL ENGINEER
CHRISTOPHER M. MALMBERG
17598
IOWA

I hereby certify that this engineering document was prepared by me or under my direct personal supervision and that I am a duly licensed Professional Engineer under the laws of the State of Iowa.

Signature Date
Christopher M. Malmberg
Printed or Typed Name

My license renewal date is December 31, 2022

Pages or sheets covered by this seal: A.1-A.6, B.1-B.8, C.1-C.4, D.1-D.16, E.1-E.5, F.1, G.1-G.11, J.1-J.15, K.1-K.15, U.1-U.13, W.1-W.88, X.1-X.15, Y.1-Y.53

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER A.1

10:18:02 AM 10/18/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194A01.sht

R-24W

R-23W

T-80N

T-79N

MARGO FRANKEL WOODS STATE PARK

DELAWARE AVENUE

Corporate Woods Drive

NE BERWICK DR

BERWICK

NORWOOD-VILLE

NE 62 AVE

NE 60 AVE

NE 58 AVE

NE 57 PL

NE 54 AVE

NE 54 PL

NE 46 AVE

NE 46 ST

NE 29 ST

NE 22 ST

NE 14 ST

NE 3 ST

NW 52 PL

NW 51 PL

NW 50 PL

NE BROADWAY AVE

E 38 ST

CAPI HEIG

Sta. 8465+42.83
Begin NB I-35 Construction

Sta. 2114+60.00
End NB I-35 Widening

Sta. 38488+93.31
Begin Ramp A Construction

Sta. 38511+66.22
End Ramp A Construction

Sta. 38637+77.87
End Ramp G Construction

Detour Construction

Detour Construction

Sta. 32574+22.46
Begin Ramp B Construction

Sta. 32593+05.82
End Ramp B Construction

Sta. 38557+03.00
Begin Ramp G Construction
End ML 235 Widening

Sta. 2015+96.21
Begin ML 235 Widening

FHWA # 609865 EB
609815 WB

FHWA # 41740

FHWA # 41690

FHWA # 41950 EB
41960 WB

FHWA # 43071 EB
43081 WB


FHWA # 609860 EB
609810 WB

FHWA # 43051 EB
43061 WB


LOCATION MAP SCALE
0 0.5 1 1.5
Miles

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER A.2

8:40:10 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194A01.sht



MAINLINE
NORTHBOUND I-35




MAINLINE I-235


Project Key Maps

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER A.3

8:40:11 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194A01.sht



SURVEY I-80




WESTBOUND I-80
TO NORTHBOUND I-35
RAMP A

MAINLINE I-80


Project Key Maps

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER A.4


8:40:12 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194A01.sht



WESTBOUND I-80
TO SOUTHBOUND I-235
RAMP G



EASTBOUND I-80
TO SOUTHBOUND I-235
RAMP B




CHICHAQUA VALLEY
TRAIL


Project Key Maps

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER A.5


8:40:13 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194A01.sht




NE 29TH STREET




SPECIAL DITCH
NE 54TH AVENUE



SPECIAL DITCH
RAMP G



NE 54TH AVENUE



NE BROADWAY AVE.


Project Key Maps

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER A.6

8:40:15 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194A01.sht

10 Lane Foreslope Grading w/Auxiliary Lanes

LOCATION			DIMENSIONS		
ROAD IDENTIFICATION	STATION TO STATION		(AL) Feet	(R) Feet	(BW) Feet
ML080	5137+77.87	5143+38.72	51.9-24.0	116.1-88.1	6.1
ML080	5143+38.72	5147+28.08	24.0-12.0	88.1-81.8	6.1-0
ML080	5147+28.08	5150+58.17	12.0	81.8	0



10 LANE GRADING

LOCATION			DIMENSIONS		
ROAD IDENTIFICATION	STATION TO STATION		(L) Feet	(X) Inches	(MW) Feet
ML080	5137+77.87	5150+58.17	37.75	30	30

See Tab 100-24 or 100-25 for pavement quantities.


See Tab 112-9 for shoulder quantities.

Grading

MAINLINE I-80 (WESTBOUND)

12-Lane Foreslope Grading

LOCATION			(R1)	(R2)	(X)	(BW)
ROAD IDENTIFICATION	STATION TO STATION		Feet	Feet	Inches	Feet
ML235	2109+31.25	2114+60.00	49	69.8	30	2.2



6-Lane Foreslope Grading w/ Auxiliary Lanes

LOCATION			(R1)	(R2)	(X)	(BW)	(AL)
ROAD IDENTIFICATION	STATION TO STATION		Feet	Feet	Inches	Feet	
ML235	2099+16.25	2109+31.25	49.1-49	94.0-69.8	30	2.2	

See Tab 100-24 or 100-25 for pavement quantities.

See Tab 112-9 for shoulder quantities.

See Tab 100-24 or 100-25 for pavement quantities.

See Tab 112-9 for shoulder quantities.

(1) Refer to project plan and cross sections for specific location of foreslope change.

Section view is in direction of traffic.

Normal sections shown may be appropriately modified for areas specifically designated by the Engineer such as intersections or superelevated curves.

Grading
ML 235 SOUTHBOUND, ML 235 NORTHBOUND (Future)


LOCATION				DIMENSIONS					
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet	(AL) Feet
NEMM	ML035N	8465+42.83	8470+36.1	57.0	45.0	30	0.0	0.0	12
NEMM	ML035N	8470+36.1	8474+22.46	57.0	45.0-69.9	30	0.0	0.0	12-40

LOCATION				DIMENSIONS					
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet	(AL) Feet
NEMM	ML035N	8474+22.46	8478+33.22	57.0	33.0	30	0.0	0.0	0.0
NEMM	ML035N	8504+90.22	8515+96.11	57.0	33.0	30	0.0	0.0	0.0

LOCATION				DIMENSIONS					
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet	(AL) Feet
NEMM	ML035N	8515+96.11	8520+16.11	57.0	82.4-57.0	30	0.0	0.0	49.1-24

LOCATION				DIMENSIONS					
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet	(AL) Feet
NEMM	ML035N	8520+16.11	8526+75.00	57.0	57.0	30	0.0	-	12
NEMM	ML035N	8526+75.00	8529+75.00	57.0	57.0-45.0	30	0.0	0.0	12-0

LOCATION				DIMENSIONS				
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet
NEMM	ML035N	8529+75.00	8532+37.46	57.0	45.0	30	0.0	-



See Tab 100-24 or 100-25 for pavement quantities.


See Tab 112-9 for shoulder quantities.

Grading
ML035N


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER B.3

8:41:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194B01.sht

LOCATION				DIMENSIONS				
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet
NEMM	235A	38488+93.31	38511+66.22	28.1	49.0	30	0.0	4.2
NEMM	235G	38557+03.00	38557+30.04	28.1	49.0	30	0.0	0.0



LOCATION				DIMENSIONS					
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet	(AL) Feet
NEMM	235G	38557+30.04	38557+53.16	28.1	49.0	30	0.0	0.0	0.0
NEMM	235G	38557+53.16	38559+09.54	33.8-36.8	49.0	30	0.0	0.0	0-3
NEMM	235G	38560+69.54	38567+30.44	36.6-49.8	49.0	30	0.0	0.0	6,76-20
NEMM	235G	38567+30.44	38569+60.04	49.8-69.1	49.0	30	0.0	0.0	20-39
NEMM	235G	38611+66.22	38618+16.50	85.0-52.4	49.0	30	0.0	0.0	52-19,5
NEMM	235G	38618+16.50	38621+16.13	52.4-45.0	49.0	30	0.0	0.0	19,5-12
NEMM	235G	38621+16.13	38637+77.87	45.0	49.0	30	0.0	0.0	12




See Tab 100-24 or 100-25 for pavement quantities.

See Tab 112-9 for shoulder quantities.


Grading
RAMP 235A,
RAMP 235G

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER B.4


LOCATION				DIMENSIONS				
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet
NEMM	235B	32574+22.46	32579+41.71	40.0	26.0	30	2.2	2.2
NEMM	235B	32587+55.00	32590+34.72	40.0	26.0	30	2.2	2.2
NEMM	235B	32592+48.72	32593+05.82	40.0	26.0	30	2.2	2.2



LOCATION				DIMENSIONS				
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet
NEMM	235B	32579+41.71	32581+41.71	40.0	29.8-43.7	30	2.2	2.2-0
NEMM	235B	32581+41.71	32582+09.38	40.0	43.7	30	2.2	0.0
NEMM	235B	32582+09.38	32582+21.88	40.0	43.7-42.2	30	2.2	0.0
NEMM	235B	32582+21.88	32582+75.00	40.0	42.2	30	2.2	0.0
NEMM	235B	32585+75.00	32587+55.00	40.0	41-29.8	30	2.2	0-2.2



LOCATION				DIMENSIONS				
INTERCHANGE	RAMP	STATION TO STATION		(L) Feet	(R) Feet	(X) Inches	(BW_L) Feet	(BW_R) Feet
NEMM	235B	32582+75.00	32585+75.00	41.8	21.8	30	2.2	-




Section view is in direction of traffic.

Normal sections shown may be appropriately modified for areas specifically designated by the Engineer such as intersections or superelevated curves.

See Tab 100-24 or 100-25 for pavement quantities.

See Tab 112-9 for shoulder quantities.


Grading
RAMP 235B



Section shown in the direction of traffic.

STATION TO STATION		(P1) Feet	(A) Feet	(B) Feet	(P2) Feet
10+07.86	13+41.56	0.0	0.0-12.0	12.0	12.0
13+41.56	16+85.36	0.0-23.9	12.0	12.0	12.0
16+85.36	18+45.89	12.0	12.0	12.0	12.0


EB I-35/80 TO NB I-35
DETOUR PAVEMENT
DET_3_10
(Future)



Section shown in the direction of traffic.

STATION TO STATION		(P1) Feet	(A) Feet	(P2) Feet
1157+53.27	1156+73.17	0	0	12.0
1156+73.17	30+40.77	0.0	0.0-16.0	12.0
30+40.77	25+60.57	0.0-23.9	16.0	12.0
25+60.57	20+25.00	8.0	16.0	12.0


WB I-80 TO NB I-35
DETOUR PAVEMENT
DET_3_20



Section shown in the direction of traffic.

ROAD IDENTIFICATION	STATION TO STATION		(A) Feet
SUR080	1064+80.91	1068+43.04	11.6-6.0
SUR080	1068+43.04	1069+08.09	6.0


EB I-35/80
DETOUR PAVEMENT
DET_3_12
(Future)



Section shown in the direction of traffic.

ROAD IDENTIFICATION	STATION TO STATION		(A) Feet
ML035N	8532+38.63	8539+69.18	24.28-2

NORTHBOUND I-35
DET_3_22




Section shown in the direction of traffic.

ROAD IDENTIFICATION	STATION TO STATION		(P) Feet
ML035N	8465+42.83	8466+13.39	12.0

NB 1-35
DETOUR PAVEMENT
DET_3_14

Earth Shoulder

BEGIN STATION	END STATION	(G) Feet
13+50.00	13+70.79	2 (MIN)
17+25.59	20+98.08	2 (MIN)



*Maximum 2%

Earth Shoulder

BEGIN STATION	END STATION	(G) Feet
13+50.00	13+70.79	2 (MIN)
17+25.59	20+98.08	2 (MIN)


Trail Jointing:
Transverse joints: C at 10' spacing.

ROAD IDENTIFICATION	BEGIN STATION	END STATION
CHICHAQUA VALLEY TRAIL	13+50.00	13+70.79
CHICHAQUA VALLEY TRAIL	17+25.59	21+18.01

See Tab 100-24 or 100-25 for pavement quantities.

See Tab 112-9 for shoulder quantities.

CHICHAQUA VALLEY TRAIL



ROAD IDENTIFICATION	BEGIN STATION	END STATION
RAMP G SPECIAL DITCH	4100+00.00	4102+33.19
54th AVE SPECIAL DITCH	4200+00.00	4203+28.85

SPECIAL DITCHES

SURVEY SYMBOLS

- PPA Power Pole Co. 1
- PRA Power Riser Co. 1
- UB Utility Box
- TSG Traffic Signal
- TSL Traffic Signal and Luminare
- TCB Traffic Signal Box
- LUM Luminaire
- TP TPD Telephone Pedestal
- MH Utility Access (Manhole)
- IN Storm Sewer Intake
- INB Storm Sewer Beehive Intake
- WV Water Valve
- FHYD Fire Hydrant
- SIGN SI Sign
- SIGN SL Speed Limit Sign
- BB Billboard
- MM MM Mile Marker Post
- ROW Right of Way Rail
- TEV Evergeen Tree
- SHR Shrub
- TDC Tree Deciduous
- SWAMP
- Flg FLG Flagpole
- BCL Bridge Centerline
- BD Bridge Deck
- BLS Bridge Low Steel
- UE Utility Elevation
- PRO Profile Shot
- BRG Bridge
- PLG Location of General Photo
- PIP Pipe Culvert
- SOP Size of Pipe or Culvert
- DU Centerline Draw or Stream (Up)
- D Centerline Draw or Stream (Down)
- DIK Centerline of Dike or Dam
- GDL Guard Rail Steel
- GPR Guard Post (4 or More Posts)
- GDC Guard Rail Cable
- RIP Rip-Rap
- TLN Tree Line
- Tile TIL Tile Line
- FCL Chain Link and Security Fence
- FW Wire Fence
- RET Retaining Walls

- EP Edge of Paved Roads (ML or SR)
- SNP Unpaved Shoulder
- CU Back of Curb
- GU Gutter In Front of Curb
- ENT Centerline BL of Entrance
- ENP Edge Paved Entrance & Park Lot
- ENU Edge Unpaved Entrance & Parking
- SWK Sidewalk
- CON Concrete or A/C Slab
- E1 ELA Underground Electric Line Co. 1
- E2 ELA Underground Electric Line Co. 2
- E3 ELA Underground Electric Line Co. 3
- T1 ELA Underground Telephone Line Co. 1
- FO FOA Underground Fiber Optic Co. 1
- FO2 FOB Underground Fiber Optic Co. 2
- FO3 FOB Underground Fiber Optic Co. 3
- FO4 FOB Underground Fiber Optic Co. 4
- G GLA Underground Gas Line Co. 1
- W WLA Underground Water Line Co. 1
- St.S. STA Storm Sewer Line Co. 1
- St.S.2 STA Storm Sewer Line Co. 2

UTILITY LEGEND

This is a POINT 25 Project and is subject to the provisions of IAC 761-115.25.

Mid American Energy - Power and Gas
Michael Younts
E1 / G — 10510 Douglas Avenue
Urbandale, Iowa 50322
515-252-6565 - myounts@midamerican.com

Iowa D. O. T. - Lighting and Fiber Optic
E2 — Tony Taylor
800 Lincoln Way
FO3 — Ames, Iowa 50010
515-239-1902 - Tony.Taylor@dot.iowa.gov
Olsson Associates - Gregory T. Seib
601 P Street
Lincoln, Nebraska 68508
402-458-5037
gseib@olssonassociates.com

Polk County - Lighting and Traffic Signals
Kurt Bailey
E3 — 5885 NE 14th Street
Des Moines, Iowa 50313
515-286-3705
Kurt.Bailey@polkcountyiowa.gov

Century Link - Telephone and Fiber Optics
Dustin Withers
T1 — 2103 East University Avenue
Des Moines, Iowa 50317
FO — 515-263-7202
Dustin.Withers@centurylink.com

Windstream - Fiber Optics
Jim Wiand
FO2 — 115 South 2nd Avenue West
Newton, Iowa 50208
641-787-2270
jim.wiand@windstream.com

Iowa Communications Network (ICN) - Fiber Optics
Larry Klawitter
FO3 — Grimes State Office Building
400 East 14th Street
Des Moines, Iowa 50319
515-229-2046
larry.klawitter@iowa.gov

Iowa Network Services (INS) - Fiber Optics
Jeff Klocko
FO4 — 7760 Office Plaza Drive South
West Des Moines, Iowa 50266
515-830-0445
Jeff@netins.com

Des Moines Water Works - Water
Matt Smith
W — 2201 George Flagg Parkway
Des Moines, Iowa 50321
515-283-8781
msmith@dmww.com

St.S. — IDOT or Private

Polk County - Storm Sewer
Kurt Bailey
St.S.2 — 5885 NE 14th Street
Des Moines, Iowa 50313
515-286-3705
Kurt.Bailey@polkcountyiowa.gov

PLAN VIEW COLOR LEGEND OF PLAN AND PROFILE SHEETS

LINEWORK	Design Color No.	
Green	(2)	Existing Topographic Features and Labels
Blue	(1)	Proposed Alignment, Stationing, Tic Marks, and Alignment Annotation
Magenta	(5)	Existing Utilities
SHADING	**Design Color No.**	
Yellow	(4)	Highlight for Critical Notes or Features
Red	(3)	Delineates Restricted Areas
Lavender	(9)	Temporary Pavement Shading
Gray, Light	(48)	Proposed Pavement Shading
Gray, Med	(80)	Proposed Granular Shading
Gray, Dark	(112)	Proposed Grade and Pave Shading "In conjunction with a paving project"
Brown, Light	(236)	Proposed Future Pavement Shading
Tan	(8)	Proposed Sidewalk Shading
Blue, Light	(230)	Proposed Sidewalk Landing Shading
Pink	(11)	Proposed Sidewalk Ramp Shading

PROFILE VIEW COLOR LEGEND OF PLAN AND PROFILE SHEETS

LINEWORK	Design Color No.	
Green	(2)	Existing Ground Line Profile
Blue	(1)	Proposed Profile and Annotation
Magenta	(5)	Existing Utilities
Blue, Light	(230)	Proposed Ditch Grades, Left
Black	(0)	Proposed Ditch Grades, Median
Rust	(14)	Proposed Ditch Grades, Right

- Reference Point / Station — Survey Line
- Section Corner
- Ground Line Intercept
- Saw Cut
- Guardrail
- Trench Drain
- HighTension Cable Guardrail
- Sheet Pile
- Pavement Removal
- Clearing & Grubbing Area

RIGHT-OF-WAY LEGEND

- Proposed Right-of-Way
- Existing Right of Way
- Existing and Proposed Right-of-Way
- Easement and Existing Right-of-Way
- Easement (Temporary)
- Easement
- C/A Access Control
- Property Line

PLAN AND PROFILE LEGEND AND SYMBOL INFORMATION SHEET

(COVERS SHEET SERIES D, E, F, & K)

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.1

11:19:27 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194lgd.sht

Sta. 1066+75
42" X 226 Conc Pipe
D.A. = 52 Ac - R
(Plug & Abandon)

SAYLOR TWP.
T-79-N R-24W
SEC. 13

Sta. 8470+71.58
Install 66" x 150' DR-601
Skew = 15° Lt. Ahd.
F.L. = Lt. 922.24
Rt. 921.45

Sta. 1075+95.35
54" X 45" Conc Pipe
W/ 54" Conc Pipe Extension
D.A. = 89 Ac - R-H (U.A.C.)

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 8466+33.34
Install 54" x 330' DR-611
Skew = 0° Lt. Ahd.
F.L. = Lt. 922.03
Rt. 913.08
Other. 913.72

FUTURE WB I-80
WESTBOUND I-80
SIGN BRIDGE
SUR080 D
FUTURE EB I-80
EASTBOUND I-80
SIGN BRIDGE
DETOUR PAVING
(SEE SHEET F.1)
PT Sta 8466+93.08
NB I-35 (ML035N)
PC Sta 8464+19.42
8465
Sta. 8465+42.83 (NB I-35)
Begin Grading
Sta. 8469+16.10
Begin Widening
PT Sta 8469+64.19
8470
PC Sta 8473+48.85
8475
Remove
(By Others)
Curve Data
Δ = 46° 54' 31.73" (LT)
T = 577.04
L = 1,088.89
R = 1,330.00
E = 119.79
e = 6.0%
L = 240
x = 80
DS = 60mph
Curve Data
Δ = 13° 34' 14.76" (RT)
T = 273.66
L = 544.77
R = 2,300.00
E = 16.22
e = 5.2%
L = 208
x = 80
DS = 60mph
POT Sta. 8473+98.99 NB I-35 =
POT Sta. 2040+08.19 NE 22ND ST.
Sta. 8478+36.72 (NB I-35)
Stop Grading
PT Sta 8479+25.90
EB I-80 to SB I-235 RAMP B (I235B)
NE 22nd Street (By Others)

SAYLOR TWP.
T-79-N R-24W
SEC. 13

0 FEET 50

DELAWARE TWP.
T-79-N R-23W
SEC. 18

MAINLINE
NORTHBOUND I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.2

11:19:40 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

985 980 975 970 965 960 955 950 945 940 935 930 925 920 915 910 905 900

934.61

STA. 8465+42.83
BEGIN CONSTRUCTION
ELEV. 934.61

VPI +75.000
Elv 930.50
K = 148
Len 700.00 ft
DS = 60mph

NE 22ND ST. BRIDGE
(By Others)

EXISTING EB to SB
RAMP B
(To Be Removed)

PROPOSED PGL

+4.000%

-0.740%

-1.08% Lt. Ditch Grade

+3.83% Rt. Ditch Grade

+1.93% Rt. Ditch Grade

+50 Lt.
931.50

-0.51%
Lt. DG

+02.51 Lt.
931.24

+22 Rt.
935.03

+65 Rt.
921.36

+43 Rt.
916.97

-4.30% Rt.
Ditch Grade

+34 Rt.
913.05

+0.53%
Lt. DG

+05.43 Lt.
922.54

+56.80 Lt.
922.81

MAINLINE
NORTHBOUND I-35

Lt: See Sheet F.1 | Ditch Grade | No Ditch


Rt: See Sheet F.1 | Ditch Grade | Vari. - See Cross Section

934.57 934.38 934.20 934.01 933.83 933.64 933.46 933.27 933.09 932.92 932.80 932.72 932.69 932.69 932.74 932.83 932.96 933.14 933.35 933.61 933.91 934.26 934.64 935.07 935.54 936.06 936.61 937.21 937.85 938.53 939.26 940.03 940.84 941.69 942.58 943.52 944.50 945.50 946.50 947.50 948.50 949.50 950.50 951.50 952.50 953.50 954.50 955.50 956.50 957.50 958.50 959.50 960.50 961.50 962.50 963.50 964.50 965.50

8464 8465 8466 8467 8468 8469 8470 8471 8472 8473 8474 8475 8476 8477 8478

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.3

11:19:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht


SIGN
EB
SIGN
SIGN
SIGN
FUTURE WB I-80
WB I-80 to SB I-235
SB I-35 to EB I-80
FUTURE EB I-80
EASTBOUND I-80
Equation:
Sta. 8493+11.75 NB I-35 =
Sta. 2062+45.23 I-235
PT Sta 8484+37.74
PC Sta 8491+99.33
NB I-35 (ML035N)
8480
8485
8490
SIGN
SIGN
SIGN

VPI +25.000
Elv 1,024.50
K = 262
Len 2,100.00 ft
DS = 60mph

+4.000%

EXISTING SB to EB
RAMP F

EXISTING WB to SB
RAMP G

EXISTING I-235

FUTURE EB I-80

EXISTING EB I-80

Bridge

Bridge

Bridge

Bridge

MAINLINE
NORTHBOUND I-35

966.50	967.50	968.50	969.50	970.50	971.50	972.50	973.50	974.50	975.50	976.50	977.50	978.50	979.50	980.50	981.50	982.50	983.49	984.45	985.39	986.31	987.20	988.07	988.91	989.74	990.53	991.31	992.06	992.78	993.49	994.16	994.82	995.45	996.06	996.64	997.20	997.74	998.25	998.74	999.20	999.64	1,000.06	1,000.45	1,000.82	1,001.16	1,001.49	1,001.78	1,002.06	1,002.31	1,002.53	1,002.74	1,002.91	1,003.07	1,003.20	1,003.31	1,003.39	1,003.45	1,003.49	1,003.50	1,003.49
8479				8480				8481				8482				8483				8484				8485				8486				8487				8488				8489				8490				8491				8492				8493			

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.5

11:20:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

Sta. 2065+90
42" X 212' Conc. Pipe
D.A. = 3 Ac - Median
(U.A.C)

Sta. 2067+05,
63' Lt
12" X 83' C.M.P.
(U.A.C)

Sta. 2067+05,
63' Rt
12" X 84' C.M.P.
(U.A.C)

FUTURE SB I-35 to EB I-80

WESTBOUND I-80

SOUTHBOUND I-235

NORTHBOUND I-235

FUTURE SB I-235

FUTURE NB I-235

SIGN

2065

2070

8495

8500

8505

WB I-80 to SB I-235

FUTURE WB I-80

NB I-35 (ML035N)

Sta. 8508+00.00 (NB I-35)
Resume Grading

PT Sta 8505+89.13

Sta. 8504+86.73 (NB I-35)
Resume Grading

Sta. 8505+50.00 (NB I-35)
Stop Grading

WB I-80 to NB I-35
RAMP A (235A)

FUTURE WB I-80 to SB I-235

REMOVE 116' C.M.P.
INSTALL 40° ELBOW AND
INSTALL 12" X 124' C.M.P.
DR-622

Sta. 2062+83,
63' Rt.
12" X 116' C.M.P.

PI Sta 8499+65.23

SIGN BRIDGE GO

Curve Data
Δ = 59° 52' 18.89" (LT)
T = 765.89
L = 1,389.80
R = 1,330.00
E = 204.76
e = 6.0%
L = 240
x = 80
DS = 60mph

E2

FO3

EB

0 50
FEET

MAINLINE
NORTHBOUND I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.6

11:20:17 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

PROPOSED PGL

-4.000%

EXISTING EB I-80
to NB I-35
(To Be Removed)

EXISTING WB I-80

FUTURE WB I-80

+85 Rt.
952.54

+85 Lt.
952.23

-0.50% Lt. Ditch Grade

-1.36% Rt. Ditch Grade

MAINLINE
NORTHBOUND I-35

Bridge

Ditch Grade

Lt

Rt

8494	8495	8496	8497	8498	8499	8500	8501	8502	8503	8504	8505	8506	8507	8508
1,003.49	1,003.45	1,003.39	1,003.31	1,003.20	1,003.07	1,002.91	1,002.74	1,002.53	1,002.31	1,002.06	1,001.78	1,001.49	1,001.16	1,000.82	1,000.45	1,000.06	999.64	999.20	998.74	998.25	997.74	997.20	996.64	996.06	995.45	994.82	994.16	993.49	992.78	992.06	991.31	990.53	989.74	988.91	988.07	987.20	986.31	985.39	984.45	983.49	982.50	981.50	980.50	979.50	978.50	977.50	976.50	975.50	974.50	973.50	972.50	971.50	970.50	969.50	968.50	967.50	966.50	965.52	964.58

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.7

11:20:26 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 2083+12.47
24" X 165'
Conc Pipe
D.A. = 0.6 Ac - R
(U.A.C.)

Sta. 2084+98.30
24" X 159'
Conc Pipe
D.A. = 24 Ac - R
(U.A.C.)

DELAWARE TWP.
T-79-N R-23W
SEC. 17

SOUTHBOUND I-235

NORTHBOUND I-235

FUTURE SB I-235 to EB I-80

FUTURE SB I-235 to WB I-80

FUTURE SB I-235

FUTURE NB I-235

SIGN BRIDGE

SIGN

NB I-35 (ML035N)

WB I-80 to NB I-35
RAMP A (235A)

8510

8515

8520

F03

EB

NE 54TH STREET

APPROX. STA.

POT Sta. 8417+05.64 NB I-35 =
POT Sta. 2237+18.96 NE 54TH AVE.

Note:
Underground fiber was relocated during construction of the NE 54th Avenue bridge and is not as shown on this plan.
Update of fiber location will be required.

Sta. 8512+64.00
Install 24" x 254' DR-601
Skew = 22° Lt. Ahd.
F.L. = Lt. 943.20
Rt. 939.19

DELAWARE TWP.
T-79-N R-23W
SEC. 18

0 50
FEET

Sta. 8518+00.00
Install 52" x 32" x 114' DR-601
Skew = 0° Lt. Ahd.
F.L. = Lt. 952.07
Rt. 949.50

DELAWARE TWP.
T-79-N R-23W
SEC. 17

MAINLINE
NORTHBOUND I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.8

11:20:34 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

1015 1010 1005 1000 995 990 985 980 975 970 965 960 955 950 945 940 935 930

Removed By Others

VPI +00.000
Elv 953.50
K = 144
Len 650.00 ft
DS = 60mph

-4.000%
+0.512%
+0.512%

+00 Lt.
950.16

-2.60% Lt. Ditch Grade

-1.36% Rt.
Ditch Grade

+70 Rt.
945.94

+00 Lt.
944.96

-0.80% Lt. Ditch Grade

+00 Lt.
943.36

+1.87% Lt.
Ditch Grade

+00 Lt.
945.23

+3.10% Lt. Ditch Grade

+10 Lt.
954.84

+1.50% Rt.
Ditch Grade

+96 Rt.
949.90

-3.08% Lt.
Ditch Grade

+00 Lt.
952.07

-1.96% Rt.
Ditch Grade

+00 Rt.
951.46

+1.00% Lt.
Ditch Grade

+00 Rt.
949.50

+00 Lt.
953.07

+0.69% Rt. Ditch Grade

	D.G.	Ditch Grade	Ditch Grade	Ditch Grade	Ditch Grade	Ditch Grade	5.0 Ft Ditch
Lt							
Rt	Ditch Grade	Vari. - See Cross Section		Ditch Grade	Ditch Grade	Ditch Grade	

	962.84	962.04	961.28	960.56	959.89	959.25	958.67	958.12	957.62	957.16	956.75	956.38	956.05	955.77	955.53	955.33	955.17	955.06	955.00	954.97	954.99	955.06	955.16	955.29	955.42	955.55	955.67	955.80	955.93	956.06	956.19	956.31	956.44	956.57	956.70	956.83	956.95	957.08	957.21	957.34	957.47	957.59	957.72	957.85	957.98	958.11	958.23	958.36	958.49	958.62	958.75	958.87	959.00	959.13	959.26	959.39	959.51	959.64	959.77	959.89
	8509				8510					8511				8512				8513				8514				8515				8516				8517				8518				8519				8520				8521				8522				8523			

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.9

DELAWARE TWP.
T-79-N R-23W
SEC. 17

SOUTHBOUND I-235

NORTHBOUND I-235

FUTURE SB I-235 to EB I-80

BRIDGE 88.4

SIGN BRIDGE

REFER TO F SHEETS FOR DETAILS

FUTURE SB I-235

FUTURE NB I-235

SIGN

MM

F03

NB I-35 (ML035N)

8525

8530

8535

PC Sta 8531+09.25

PI Sta 8536+86.32

Curve Data
Δ = 5° 30' 22.71" (LT)
T = 577.06
L = 1,153.24
R = 12,000.00
E = 13.87

Sta. 8532+37.46 (NB I-35) =
Sta. 2099+18.69, 83.20' RT (I-235)
End Grading

DELAWARE TWP.
T-79-N R-23W
SEC. 17

0 FEET 50

MAINLINE
NORTHBOUND I-35

VPI +25.000
Elv 961.82
K = 299
Len 800.00 ft
DS = 60mph

+0.512%

-2.160%

950.75

STA. 8532+37.46
END CONSTRUCTION
ELEV. 950.75

+0.69% Rt. Ditch Grade

+40 Rt.
954.62

PROPOSED PGL

+55 Rt.
952.45

-2.00% Rt. Ditch Grade

+37 Rt.
944.80

EXIST. GROUND

975 970 965 960 955 950 945 940

Lt

Rt

5.0 Ft Ditch

Vari. - See Cross Sections

Ditch Grade

5.0 Ft Ditch

Ditch Grade

959.98 960.06 960.12 960.15 960.16 960.16 960.13 960.08 960.01 959.92 959.80 959.67 959.52 959.34 959.15 958.93 958.69 958.44 958.16 957.86 957.54 957.19 956.83 956.45 956.04 955.62 955.17 954.71 954.22 953.71 953.18 952.64 952.10 951.56 951.02

8524 8525 8526 8527 8528 8529 8530 8531 8532 8533

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.10

11:20:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

Sta. 2020+27
24" X 89' Conc. Pipe

Extend Existing 24" RCP
w/24" x 32' Lt. DR-621

Sta. 2024+29
30" X 215' Conc Pipe
D.A. = 10 Ac - R

Extend Existing 30" RCP
w/30" x 46' Lt. DR-621

DELAWARE TWP.
T-79-N R-23W
SEC. 19

Sta. 2015+96.21 (I-235)
Begin Widening

WB I-80 to SB I-235
RAMP G (235G)

EXISTING BRIDGE

FUTURE SB I-235

SOUTHBOUND I-235

ML I-235 (ML235)

EXISTING BRIDGE

2015

FUTURE NB I-235

(U.A.C.)

2020

NORTHBOUND I-235

2025

Sta. 2028+42.95 (I-235)
End Widening

DELAWARE TWP.
T-79-N R-23W
SEC. 19

0 FEET 50

MAINLINE I-235

960
955
950
945
940
935
930
925
Lt
Rt

+00 Lt.
928.20

+1.40% Lt. Ditch Grade

+50 Lt.
931.70

-0.20% Lt. Ditch Grade

+50 Lt.
930.90

+1.30% Lt. Ditch Grade

+00 Lt.
932.85

-0.20% Lt. Ditch Grade


+00 Lt.
932.45


Ditch Grade | Ditch Grade | Ditch Grade | Ditch Grade | D.G. | No Ditch

2017 2018 2019 2020 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.11

11:21:01 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht





FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.12	REVISED

11:21:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

Sta. 2102+34
24" X 84' Conc. Pipe
(U.A.C)

DELAWARE TWP.
T-79-N R-23W
SEC. 7

SIGN BRIDGE

FUTURE SB I-235 to EB I-80

REFER TO F SHEETS
FOR DETAILS

NORTHBOUND I-235

SOUTHBOUND I-235

2100 BRIDGE

2105

Sta. 2109+31.40 (NB I-235) =
Sta. 2109+31.19, 13.00' RT (I-235)

Sta. 2109+31.19 (I-235)
Begin Widening

FUTURE SB I-235

I-235 (ML235)

I-235 (ML235NB)

FUTURE NB I-235

2110 BRIDGE

(U.A.C.)

(U.A.C.)

I-35 NB (ML035N)

I-35 NB (ML035N)

MM

SIGN


F03

F03

DELAWARE TWP.
T-79-N R-23W
SEC. 7

0 FEET 50

MAINLINE I-235



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.13

11:21:18 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

Sta. 2112+52
24" x 90' Conc. Pipe
(U.A.C)

Sta. 165+43
24" X 109' Conc. Pipe
(U.A.C)

DELAWARE TWP.
T-79-N R-23W
SEC. 7

Sta. 2109+31.40 (NB I-235) =
Sta. 2109+31.19, 13.00' RT (I-235)

Sta. 2109+31.19 (I-235)
Begin Widening

Sta. 2114+60.00 (I-235)
End Widening

N BRIDGE

PT Sta 2109+34.40

FUTURE SB I-235

I-235 (ML235)

I-235 (ML235NB)

FUTURE NB I-235

I-35 NB (ML035N)

(U.A.C.)

SOUTHBOUND I-235/35

(U.A.C.)

NORTHBOUND I-235/35

SIGN BRIDGE

2110

2115

2120

F03

Sta. 2114+91
64" X 586' Steel Pipe
W/6' X 6' RCB Exts
D.A. = 111 Ac - R
(U.A.C)

Extend Existing 24" RCP
w/24" x 24' DR-621
Sta. 2107+00
24" X 121' Conc. Pipe

DELAWARE TWP.
T-79-N R-23W
SEC. 7

0 FEET 50

MAINLINE I-235

955
950
945
940
935
930
925
920

+00 Rt.
931.33

1.88% Rt. Ditch Grade

+50 Rt.
924.75

5.58% Rt. Ditch Grade

+00 Rt.
910.80

U.A.C.

Lt

Rt

Ditch Grade

Ditch Grade

U.A.C.

2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.14

11:21:27 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

SAYLOR TWP.
T-79-N R-24W
SEC. 13

Sta. 1066+75
42" X 226 Conc Pipe
D.A. = 52 Ac - R
(Plug & Abandon)

PC Sta 1058+28.34

PI Sta 1064+18.99

PT Sta 1071+34.02

1060

1065

1070

SIGN BRIDGE

FUTURE WB I-80

FUTURE EB I-80

I-80/35 (SUR080)

WESTBOUND I-80

EASTBOUND I-80

NB I-35 (ML035N)

SIGN

DETOUR PAVING
(SEE SHEET F.1)

Curve Data
Δ = 6° 57' 38.61" (LT)
T = 653.65
Lc = 1,305.68
R = 10,747.47
E = 19.86

0 FEET 50

Sta. 1057+00
24" X 95' Conc Pipe

SAYLOR TWP.
T-79-N R-24W
SEC. 13

MAINLINE I-80
SURVEY

+00 Lt.
929.02

-4.30% Lt. Ditch Grade

+4.10% Lt. Ditch Grade

+00 Lt.
927.29

+67 Lt.
921.84

Ditch Grade

950
945
940
935
930
925
920
915

Lt
Rt

950.95 950.35 949.74 949.12 948.51 947.89 947.28 946.66 946.05 945.43 944.82 944.20 943.59 942.97 942.36 941.74 941.13 940.51 939.90 939.28 938.67 938.05 937.44 936.82 936.21 935.59

1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.15

11:21:36 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

Sta. 1138+99
18" X 146' Conc Pipe
Remove 73' Existing 24" RCP
STA 5139+01.45, 63.23 LT
AREA INLET SW-562
w/24" x 180' Lt. DR-621

DELAWARE TWP.
T-79-N R-23W
SEC. 17

Sta. 1142+98
18" X 150'
Conc Pipe
Remove 96' Existing 24" RCP
STA 5143+01.19, 44.67 LT
AREA INLET SW-562
w/24" x 176' Lt. DR-621

Sta. 1146+99
18" X 132'
Conc Pipe
Remove 80' Existing 24" RCP
STA 5146+99.18, 42.63 LT
AREA INLET SW-562
w/24" x 144' Lt. DR-621

STA 5148+12.94, 38.20 LT
AREA INLET SW-562
w/24" x 144' Lt. DR-621

Sta. 5151+00
Extend Existing 24" F
w/24" x 48' Lt. DR-62

Sta. 5137+77.87, 90.97' LT (ML080) =
Begin Grading

Sta. 5150+58.17, 69.00' LT (ML080) =
End Construction

FUTURE WB I-80

SIGNAL BRIDGE

I-80 (ML080)

(U.A.C.)

WESTBOUND I-80

EASTBOUND I-80

FUTURE EB I-80

SIGN

5140

5145

5150

DELAWARE TWP.
T-79-N R-23W
SEC. 17

0 FEET 50

MAINLINE
WESTBOUND I-80

STA. 5137+77.67
BEGIN I-80 CONSTRUCTION
ELEV 919.24

PROPOSED PGL

+78 Lt.
888.16

-3.00% Lt. Ditch Grade

-3.00% Lt. Ditch Grade

+00 Lt.
875.50

-1.80% Lt.
Ditch Grade

-3.000%

VPI +75.000
Elv 883.32
K = 1250
Len 250.00 ft

STA. 515+58.17
END CONSTRUCTION
ELEV 881.00

+58 Lt.
860.05

Ditch Grade

Ditch Grade

915 910 905 900 895 890 885 880

880 875 870 865 860

5136 5137 5138 5139 5140 5141 5142 5143 5144 5145 5145 5145 5145 5145 5145 5145

918.57 917.07 915.57 914.07 912.57 911.07 909.57 908.07 906.57 905.07 903.57 902.07 900.57 899.07 897.57 896.07 894.57 893.07 891.57 890.07 888.57 887.07 885.58 884.11 882.66 881.23

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER D.16

11:21:45 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194D02.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

DELAWARE TWP.
T-79-N R-23W
SEC. 18

DELAWARE TWP.
T-79-N R-23W
SEC. 17

DELAWARE TWP.
T-79-N R-23W
SEC. 17

CHICHAQUA VALLEY TRAIL

(U.A.C.)

APPROX. SEC. LINE

NE 29TH STREET

Sta. 13+98.43 CV TRAIL
Begin Construction

Equation:
Sta. 17+52.13 CV TRAIL
=Sta. 3862+81.86 RAMP G

Sta. 21+18.01 CV TRAIL
End Construction

Curve Data
C1 Δ = 22° 56' 27.65" (RT)
T = 10.15
L = 20.02
R = 50.00
E = 1.02

Curve Data
C2 Δ = 22° 56' 27.65" (LT)
T = 10.15
L = 20.02
R = 50.00
E = 1.02

Curve Data
C3 Δ = 11° 40' 45.25" (LT)
T = 10.23
L = 20.38
R = 100.00
E = 0.52

Curve Data
C4 Δ = 11° 40' 45.25" (RT)
T = 10.23
L = 20.38
R = 100.00
E = 0.52

Curve Data
C5 Δ = 84° 27' 36.42" (RT)
T = 90.77
L = 147.41
R = 100.00
E = 35.05

Curve Data
C6 Δ = 60° 39' 51.21" (LT)
T = 29.26
L = 52.94
R = 50.00
E = 7.93

PC Sta 13+85.12
PI Sta 13+95.26
PT Sta 14+05.14
PC Sta 14+30.20
PI Sta 14+40.35
PT Sta 14+50.22
PI Sta 15+24.79
PI Sta 15+34.87
PRC Sta 16+06.44
PC Sta 16+06.06
PI Sta 16+96.28
PT Sta 17+26.82
PI Sta 17+96.67
PC Sta 18+03.57
PI Sta 18+24.34
PT Sta 19+50.98
PC Sta 20+52.14
PI Sta 20+81.39
PT Sta 21+05.08

FUTURE WB I-80
FUTURE EB I-80
EASTBOUND I-80
WESTBOUND I-80
WB I-80 to SB I-235 RAMP G (235G)

Trail Grading Matchline

Driveway Grading

Sta. 20+85.00
Install 44" x 27" x 26' DR-601
Skew 30° Rt. Ahd.
F.L. = Lt. 895.15'
Rt. 893.89'

0 FEET 50

PROPOSED RAMP G BRIDGE

STA. 13+98.43
BEGIN CONSTRUCTION
MATCH EXISTING
ELEV 906.74

VPI +48.434
Elv 906.24
K = 22
Len 100.00 ft

-1.000%
+3.639%

VPI +53.304
Elv 910.06
K = 32
Len 100.00 ft

+0.500%

VPI +75.214
Elv 911.17
K = 20
Len 100.00 ft

-4.628%

VPI +25.004
Elv 899.61
K = 28
Len 100.00 ft

-1.000%

STA. 21+18.01
END CONSTRUCTION
MATCH EXISTING
ELEV 898.68

930 925 920 915 910 905 900 895

Lt
Rt

906.73 906.84 908.12 909.60 910.29 910.54 910.79 910.89 909.86 907.71 905.39 903.08 900.88 899.47 898.86

10 11 12 13 14 15 16 17 18 19 20 21 22

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER E.1

11:42:30 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194E01.sht

DELAWARE TWP.
T-79N R-23W
SEC. 7

Sta. 79+11.39
24" X 62.0 C.M.P.
D.A. = 1.5 Ac - R
(U.A.C)

DELAWARE TWP.
T-79N R-23W
SEC. 7

8520

NB I-35 (ML035N)

FO3

FO3

2240

2245

2250

FUTURE ROW LINE

PI Sta 2248+02.40

NE 54th Avenue (By Others)

SIGN

Note:
For Plan & Profile for Special Ditch
NE 54th Avenue, see Sheet E.5

DELAWARE TWP.
T-79N R-23W
SEC. 18

DELAWARE TWP.
T-79N R-23W
SEC. 18

0 FEET 50

NE 54TH AVENUE

975
970
965
960
955
950
945
940
Lt
Rt

EXISTING GROUND LINE AT
NE 54TH AVE. BASE LINE

+90 Lt.
949.50

-0.50% Lt. Ditch Grade

+33 Lt.
945.78

Ditch Grade

2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER E.2

11:42:35 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194E01.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 38805+75.07
24" x 26' CMP
(Remove)

Equation:
Sta. 38806+23.10 SR 29TH ST.=
Sta. 38632+22.58 RAMP G

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 38807+75.00 (SR29TH)
Begin Construction
Sta. 38808+00.00 (SR29TH)
End Construction

+20 Prop.
Type "M" Dike
Elev. 905.50

EASTBOUND I-80
WESTBOUND I-80
FUTURE WB I-80
CLOSE
CLOSE
APPROX. SEC. LINE
APPROX. SEC. LINE
POT Sta 38800+00.00
POT Sta 38808+85.14
38800
38805
Interim Trail
Trail
Grading
Matchline
Driveway Grading
DITCH
DITCH

DELAWARE TWP.
T-79-N R-23W
SEC. 17

0 50
FEET

DELAWARE TWP.
T-79-N R-23W
SEC. 17

SIDE ROAD
NE 29th STREET

38808+30.00
+30 Prop. Type "C" Ent.
-4.0%
-5.500%
-2.24%
-6.2%
910.12
909.82
-1.200%
+25 Lt.
908.98
-4.00% Lt.
Ditch Grade
+87 Lt.
902.50
+25 Lt.
904.61
5.56% Lt.
Ditch Grade
Ditch Grade
D.G.
910.12
909.82

930
925
920
915
910
905
900
895
Lt
Rt

38800 38801 38802 38803 38804 38805 38806 38807 38808 38809

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER E.3

11:42:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194E01.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

DELAWARE TWP.
T-79-N R-23W
SEC. 18

DELAWARE TWP.
T-79-N R-23W
SEC. 19

DELAWARE TWP.
T-79-N R-23W
SEC. 19

WB I-80 to SB I-235
RAMP G (235G)

SOUTHBOUND I-235

NORTHBOUND I-235

ML I-235 (ML235)

Equation:
Sta. 1180+16.12 NE BROADWAY AVE
=Sta. 38559+88.29 RAMP G

POT Sta 1175+00.22

POT Sta 1188+00.22

1185

38560

(Close)

(Close)

6 HP

APPROX. SEC. LINE

(U.A.C.)

APPROX. SEC. LINE

(U.A.C.)

APPROX.

NE BROADWAY AVE. (SRBRWY)

SIGN

0 FEET 50

SIDE ROAD
NE BROADWAY AVE

PROPOSED RAMP G BRIDGE


EXIST. GROUND

960
955
950
945
940
935
930
925

1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER E.4

11:42:44 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194E01.sht




0 FEET 50


SPECIAL DITCH
NE 54th AVE



0 FEET 50


SPECIAL DITCH
RAMP G





FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER E.5

11:42:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194E01.sht



This Sheet
For Information Only

INTERSTATE 80/35
NORTHEAST MIX MASTER
DET_3_14 STAGE 1 (197)

		Iowa DOT\HDR	POLK	IM-035-3(194)87--13-77	F.1	

8:45:58 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194F01.sht

Survey Information

County: Polk
PIN: 10-77-035-010-03
Project Number: IM-035-3(194)87--13-77
Location: I-35/80/235 Interchange NE Of Des Moines(Stage 3A)
Type of Work: Grading
Project Directory: 7703501010
This Index covers SAP's 0742.2, 0742.3 and 0742.4

General Information

Measurement units for this survey are US survey feet. This survey is for phase 3 of the NE Mixmaster ramp reconstruction. This survey uses the same coordinate system as the Delaware Ave. IM-035-4(161)87--13-77 and 54th. Ave. IM-035-4(160)87--13-77 Surveys. Phase 3 surveying was accomplished by an IDOT design survey crew and 2 consulting firms. IDOT surveyed project control, mainline alignments, culvert surveys, utility survey, photo control survey and selected ground features. R.E.Y. Consultants surveyed mainline pavement and interchange ramps using mobile LiDAR. Snyder and Associates surveyed railroads. Aerial survey will also be used to create a project surface and to add other topographic features.

IDOT Design Party Personnel

John Dewey- Party Chief
Robert Mingus- Party Chief
Myron Fox- Assistant Party Chief

IDOT Date(s) of Survey

Begin Date 04/2014
End Date 09/2014

R.E.Y Engineers, Inc.
Contract No. 801AH; WO7

Date(s) of R.E.Y. Survey
June-July 2014

Snyder and Associates
Contract No. 433AF; WO 5

Date(s) of R.E.Y. Survey
Oct. 2014

Project Control Information

GPS Control from previous surveys were used as follows:
GPS PROJECT : Sap 323 & 324 STP-69-4(65)--2c-77 (2000 Survey)
STATE PLANE COORDINATE ZONE 1402 (IOWA SOUTH LAMBERT)
STATE PLANE COORDINATES HELD AT POINT G030
AVERAGE PROJECT LATITUDE = 41 40 12.05576
RESULTING RADIUS = 6363663.482 (METERS)
MEAN PROJECT ELEVATION = 285.000 (METERS)
SEA LEVEL FACTOR = 0.999955216
AVERAGE PROJECT SCALE FACTOR = 0.999982250
COMBINED FACTOR (GRID) = 0.999937467
1 / GRID = 1.000062537
VERTICAL DATUM = NAVD 88 <> HORIZONTAL DATUM = NAD 83 (1996)

GPS Control point G024 coordinates from previous surveys were used and the following points were re-observed and adjusted: G013, G025, G026 and G027. G010, G011, G029 and G030 were searched for but not found. It is presumed reconstruction has obliterated those points. Point G128 from an I-235 survey was re- observed and adjusted. Points G128 and G026 are FENO monuments. All other points are 5/8" Rebar. Two FENO monuments were added. These are points 100 and 101.
It is intended that the control included in the re-observation will be the primary control used for future survey work. The FENO monuments designated as 26,100,101 and 128 to the north, south, east and west of the interchange are constructed to hold horizontal and vertical position reasonably well. The other rebar can be used but should be verified first relative to the FENO monuments. It is anticipated additional temporary marks in the interchange will be needed at various stages as the project progresses. Those temporary marks will be established as needed relative to this control.

Alignment Information

Mainline Alignment (I-80)

The I 80 alignment is relative to the control in the metric as-built plans IM-35-3(116)85--13-77 computed from a 1994 metric I 80 survey alignment. Metric alignment points were scaled and translated to this survey coordinate system. No rotation was required. Sta 2000+00.00 was assigned to the PC of the metric I 80 curve west of the Delaware Ave. Bridge. Stationing was run ahead without station equation to the end of the alignment at the mixmaster interchange central intersection point.

This Mainline survey relates to the mainline plan stationing as follows:

CP Sta. 1024+84.88, 97.35' Lt this survey (English)
=CP Sta. 312+34.97, 29.67m Lt Project # IM-35-3(116)85—13-77 (Metric)

POT Sta. 1075+46.01, 0.04' Lt this survey (English)
=POT Sta. 327+77.59, 0.010m Lt Project # IM-35-3(116)85—13-77 (Metric)

POT Sta. 1181+51.81 this survey (English)
=POT Sta. 1181+53.0 Project # IM-80-5(145)137--13-77 (English)

Mainline Alignment (I-35)

From 2001/2002 I-35 Realignment, Project # IM-35-4(101)—13-77
The mainline alignment for this survey is a retrace of Project # IM-35-4(101)—13-77. The mainline alignment was created in centerline of median. Stationing was obtained at PI Sta. 2001+60.36 and carried ahead to PI Sta. 3100+53.44 without equation. The following PI points were used to create this CL alignment.

PI 2001+60.36 Project # IM-35-4(101)88—13-77 (not found or set)
PI 3100+53.44 Project # IM-35-4(101)88—13-77 (not found or set)

This Mainline survey relates to the mainline plan stationing as follows:


PI Sta. 2001+60.36 this survey
=PI Sta. 2001+60.36 Project # IM-35-4(101)88—13-77

PI Sta. 2100+53.74 this survey
=PI Sta. 3100+53.44 Project # IM-35-4(101)88—13-77

Project Control -FENO monuments are also Bench Marks

Name	Ground Northing (USft)	Ground Easting (USft)	Elevation (USft)	Description
13	604251.756	1612997.613	933.158	rebar, 6" deep, in the SE quad. of intersection NE 14th (US 69) & NE 54th Ave., 13' south of ROW rail; 62' south of NE 54th Ave.;
25	604260.796	1621907.741	939.609	rebar, 6" deep, in the south sideditch, @ the west edge of field entrance south, and adj. to inlet of CMP under NE 54th Ave.; 22' west of field entr.; 10' from inlet CMP; 5' from edge AC slab.
26	604283.735	1624489.54	886.7	Feno. Monument, w/cap stamped "026", 6" deep, in the north ROW/shoulder of NE 54th Ave., 9' north of edge AC slab; 128' from P.I. of NE 54th Ave. with of RR crossing.
27	604243.29	1627372.639	838.959	rebar, 6" deep, in the south edge of shoulder, on the west side of a field entrance; 31' west of approx. center gravel field south; 13' south of edge AC slab of NE 54th Ave.; 40' north of center large CMP under entrance.
100	601242.316	1613129.094	904.541	Feno. Monument
101	612281.879	1619265.525	932.935	Feno. Monument
128	594971.978	1619970.2	933.868	Feno. Monument between top backslope and ROW fence in east ROW

Project Control Point Location Map



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER G.2	REVISED

11:53:01 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht

ALIGNMENT COORDINATES

101-16
10-20-09

Name	Location	Point on Tangent			Begin Spiral			Begin Curve			Simple Curve PI or Master PI of SCS			End Curve			End Spiral		
		Station	Coordinates		Station	Coordinates		Station	Coordinates		Station	Coordinates		Station	Coordinates		Station	Coordinates	
			Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)
	I-80																		
90		5128+03.54	602,662.82	1,623,353.19															
91		5188+97.59	603,831.81	1,629,334.07															
92		5208+07.61	604,179.78	1,631,212.12															
93		5240+69.50	604,805.49	1,634,413.44															
	I-80 ML SURVEY																		
8011		975+28.38	600,997.23	1,608,212.44															
SUR080-1								998+08.83	600,998.02	1,610,492.89	1004+20.94	600,998.23	1,611,105.00	1010+32.54	601,041.98	1,611,715.55			
8012		1024+84.88	601,145.79	1,613,164.17															
8013		1055+07.15	601,361.80	1,616,178.71															
SUR080-2								1058+28.34	601,384.75	1,616,499.08	1064+81.98	601,431.47	1,617,151.06	1071+34.02	601,556.86	1,617,792.56			
8014		1240+69.40	604,805.49	1,634,413.44															
	I-35 NORTHBOUND																		
ML035N-1								8464+19.42	601,337.20	1,617,100.02	8466+93.08	601,357.77	1,617,372.91	8469+64.19	601,313.73	1,617,643.01			
ML035N-2								8473+48.85	601,251.83	1,618,022.66	8479+25.90	601,158.98	1,618,592.19	8484+37.74	601,511.45	1,619,049.07			
ML035N-3								8491+99.33	601,976.65	1,619,652.07	8499+65.23	602,444.47	1,620,258.48	8505+89.13	603,203.78	1,620,158.24			
ML035N-4								8531+09.25	605,702.22	1,619,828.39	8536+86.32	606,274.32	1,619,752.86	8542+62.49	606,836.53	1,619,622.78			
	I-235																		
23510		1949+59.42	590,888.03	1,619,611.10															
ML235-1								1973+48.82	593,260.91	1,619,891.57	1976+35.85	593,545.95	1,619,925.27	1979+20.97	593,832.02	1,619,901.74			
ML235-2								1999+18.25	595,822.57	1,619,738.02	2001+63.13	596,066.63	1,619,717.95	2004+07.71	596,311.51	1,619,718.77			
ML235-3								2091+68.42	605,072.17	1,619,748.25	2100+53.74	605,957.48	1,619,751.23	2109+31.19	606,820.01	1,619,551.67			
ML235-4								2120+36.80	607,897.17	1,619,302.45	2133+30.72	609,157.79	1,619,010.79	2145+94.73	610,438.20	1,619,197.30			
ML235-5								2175+76.86	613,389.19	1,619,627.15	2181+89.48	613,995.41	1,619,715.45	2187+99.48	614,607.95	1,619,706.02			
23511		2221+71.45	617,979.53	1,619,654.15															
	I-235 NORTHBOUND (NORTH END I-235)																		
309100		2090+59.42	604,963.12	1,619,762.88															
ML235NB-1								2091+68.09	605,071.79	1,619,763.13	2096+10.48	605,514.19	1,619,764.17	2100+51.90	605,953.75	1,619,714.23			
ML235NB-2								2100+51.90	605,953.75	1,619,714.23	2104+93.64	606,392.67	1,619,664.37	2109+34.40	606,822.94	1,619,564.34			
	I-235 SOUTHBOUND (NORTH END I-235)																		
309200		2090+59.42	604,963.22	1,619,732.88															
ML235SB-1								2091+68.07	605,071.88	1,619,733.37	2096+08.60	605,512.40	1,619,735.34	2100+48.16	605,950.22	1,619,686.57			
ML235SB-2								2100+48.16	605,950.22	1,619,686.57	2104+88.55	606,387.91	1,619,637.82	2109+27.97	606,817.08	1,619,539.01			
	RAMP A																		
235A-1								38484+75.18	604,621.62	1,619,995.26	38486+84.50	604,414.10	1,620,022.66	38488+93.31	604,211.33	1,620,074.59			
235A-2								38490+63.31	604,046.65	1,620,116.77	38495+12.65	603,611.36	1,620,228.26	38499+29.96	603,332.87	1,620,580.89			
235A-3								38502+68.51	603,123.05	1,620,846.58	38507+35.22	602,833.80	1,621,212.84	38511+66.22	602,836.84	1,621,679.54			
	RAMP B																		
303220		32574+22.46	601,202.23	1,618,091.36															
235B-1								32576+53.97	601,149.86	1,618,316.87	32579+68.33	601,078.75	1,618,623.08	32582+63.12	600,845.23	1,618,833.52			
235B-2								32585+22.66	600,652.43	1,619,007.27	32590+41.99	600,266.64	1,619,354.94	32595+34.44	599,755.47	1,619,446.66			
	RAMP G																		
235G-1								38552+54.84	598,296.98	1,619,652.83	38555+37.05	598,579.19	1,619,653.78	38558+18.03	598,857.90	1,619,609.50			
235G-2								38576+34.09	600,651.46	1,619,324.57	38584+47.75	601,455.05	1,619,196.91	38590+94.52	601,934.59	1,619,854.24			
235G-3								38600+76.01	602,513.05	1,620,647.15	38604+68.41	602,744.31	1,620,964.16	38608+39.16	602,766.46	1,621,355.93			
235G-4								38630+76.49	602,892.74	1,623,589.70	38634+27.39	602,912.55	1,623,940.05	38637+77.87	602,962.58	1,624,287.37			

ALIGNMENT COORDINATES

101-16
10-20-09

Name	Location	Point on Tangent			Begin Spiral			Begin Curve			Simple Curve PI or Master PI of SCS			End Curve			End Spiral		
		Station	Coordinates		Station	Coordinates		Station	Coordinates		Station	Coordinates		Station	Coordinates		Station	Coordinates	
			Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)		Y (Northing)	X (Easting)
	CHICHAQUA VALLEY TRAIL																		
TRAIL1		13+68.43	602,526.64	1,623,779.87															
TRAIL2								13+85.12	602,543.32	1,623,779.87	13+95.26	602,553.47	1,623,779.87	14+05.14	602,562.81	1,623,783.82			
TRAIL3								14+30.20	602,585.90	1,623,793.58	14+40.35	602,595.24	1,623,797.54	14+50.22	602,605.39	1,623,797.53			
TRAIL4		15+24.79	602,679.95	1,623,797.52															
TRAIL5		15+34.87	602,689.95	1,623,798.76															
TRAIL6								16+86.06	602,841.14	1,623,798.73	16+96.28	602,851.37	1,623,798.72	17+06.44	602,861.39	1,623,796.65			
TRAIL7								17+06.44	602,861.39	1,623,796.65	17+16.67	602,871.40	1,623,794.58	17+26.82	602,881.63	1,623,794.58			
TRAIL8								18+03.57	602,958.37	1,623,794.56	18+94.34	603,049.14	1,623,794.54	19+50.98	603,057.93	1,623,884.88			
TRAIL9								20+52.14	603,067.72	1,623,985.56	20+81.39	603,070.55	1,624,014.68	21+05.08	603,097.32	1,624,026.48			
TRAIL10		22+18.00	603,200.65	1,624,072.02															
	NE 29TH ST																		
308100		38800+00.00	602,279.20	1,623,735.62															
308101		38808+85.14	603,164.34	1,623,735.41															
	NE 54TH AVE																		
221917		2219+15.91	604,336.66	1,618,209.25															
221918		2248+02.40	604,295.07	1,621,095.43															
	SPECIAL DICTH NE 54TH																		
841800		4200+00.00	604,347.10	1,620,826.76															
841801		4203+28.85	604,668.65	1,620,895.68															
	SPECIAL DICTH RAMP G																		
V1100		4100+00.00	602,716.01	1,621,970.08															
V1101		4102+33.19	602,575.84	1,622,156.43															

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER G.4

11:53:02 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht

SPIRAL OR CIRCULAR CURVE DATA

101-17
04-19-11


Name	Location	Δ_{scs}	Horizontal Alignment Data												Remarks
			Spiral Data								Curve Data				
			θs	Ls	Ts	Es	Xc	Yc	L.T.	S.T.	Δ_c	T	L	R	E	
	I-80 ML SURVEY															
SUR080-1											4° 04′ 43.41″ LT	612.11′	1,223.71′	17,190.00′	10.89′	
SUR080-2											6° 57′ 38.61″ LT	653.65′	1,305.68′	10,747.47′	19.86′	
	I-35 NORTHBOUND															
ML035N-1											13° 34′ 14.76″ RT	273.66′	544.77′	2,300.00′	16.22′	
ML035N-2											46° 54′ 31.73″ LT	577.04′	1,088.89′	1,330.00′	119.79′	
ML035N-3											59° 52′ 18.89″ LT	765.89′	1,389.80′	1,330.00′	204.76′	
ML035N-4											5° 30′ 22.71″ LT	577.06′	1,153.24′	12,000.00′	13.87′	
	I-235															
ML235-1											11° 26′ 34.74″ LT	287.03′	572.15′	2,864.79′	14.34′	
ML235-2											4° 53′ 40.67″ RT	244.88′	489.46′	5,729.58′	5.23′	
ML235-3											13° 13′ 11.22″ LT	885.31′	1,762.76′	7,639.98′	51.12′	
ML235-4											21° 18′ 52.28″ RT	1,293.92′	2,557.93′	6,875.99′	120.69′	
ML235-5											9° 10′ 08.25″ LT	612.62′	1,222.62′	7,639.98′	24.52′	
	I-235 NORTHBOUND															
	(NORTHERLY END I-235)															
ML235NB-1											6° 36′ 56.13″ LT	442.39′	883.81′	7,654.39′	12.77′	
ML235NB-2											6° 36′ 24.10″ LT	441.74′	882.51′	7,653.45′	12.74′	
	I-235 SOUTHBOUND															
	(NORTHERLY END I-235)															
ML235SB-1											6° 36′ 45.46″ LT	440.53′	880.08′	7,625.57′	12.71′	
ML235SB-2											6° 36′ 35.18″ LT	440.39′	879.81′	7,626.51′	12.70′	
	RAMP A															
235A-1											6° 50′ 41.78″ LT	209.32′	418.13′	3,500.00′	6.25′	
235A-2											37° 20′ 05.39″ LT	449.34′	866.65′	1,330.00′	73.85′	
235A-3											38° 40′ 21.70″ LT	466.71′	897.70′	1,330.00′	79.51′	
	RAMP B															
235B-1											34° 54′ 05.36″ RT	314.35′	609.15′	1,000.00′	48.25′	
235B-2											31° 51′ 07.08″ RT	519.33′	1,011.78′	1,820.00′	72.65′	
	RAMP G															
235G-1											9° 13′ 10.55″ LT	282.21′	563.19′	3,500.00′	11.36′	
235G-2											62° 54′ 53.64″ RT	813.67′	1,460.44′	1,330.00′	229.15′	
235G-3											32° 52′ 34.42″ RT	392.40′	763.15′	1,330.00′	56.68′	
235G-4											4° 57′ 40.47″ LT	350.91′	701.38′	8,100.00′	7.60′	
	CHICHAQUA VALLEY TRAIL															
TRAIL2											22° 56′ 27.65″ RT	10.15′	20.02′	50.00′	1.02′	
TRAIL3											22° 56′ 27.65″ LT	10.15′	20.02′	50.00′	1.02′	
TRAIL6											11° 40′ 45.25″ LT	10.23′	20.38′	100.00′	0.52′	
TRAIL7											11° 40′ 45.25″ RT	10.23′	20.38′	100.00′	0.52′	
TRAIL8											84° 27′ 36.42″ RT	90.77′	147.41′	100.00′	35.05′	
TRAIL9											60° 39′ 51.21″ LT	29.26′	52.94′	50.00′	7.93′	

SUPERELEVATION DATA

See PV-300 Series

Road Identification	Circular Curve or Spiral Curve Name	Radius	Superelevation Data			Standard Road Plan	Section A-A	Section B-B	Section C-C	Section D-D	Section E-E	Section F-F	Case A	Case B	Case C	Case S	Case T	Case U	Remarks
			e	L	x														
		FT	%	FT	FT														
ML035N	ML035-1	2300	5.2	208	80	PV-303	[1]		8464+19.42	8464+81.82						8464+33.82	8464+33.82		
							8470+29.79		8469+64.19	8469+01.79						8469+49.79	8469+49.79		
ML035N	ML035N-2	1330	6.0	240	80	PV-303	8472+60.85		8473+48.85	8474+20.85						8473+40.85	8473+40.85		
							8485+25.74		8484+37.74	8483+65.74						8484+45.74	8484+45.74		
ML035N	ML035N-3	1330	6.0	240	80	PV-303	8490+63.33		8491+99.33	8492+23.33						8491+43.33	8491+43.33		Refer to Modified PV-303 CASE B
ML035N	ML035N-3	1330	6.0	240	80	PV-303													
							8508+85.13	8508+05.13	8505+89.13	8505+65.13						8506+45.13	8506+45.13		Refer to Modified PV-303 CASE A
ML035N	ML035N-4	12000	NC	N/A	N/A														No Superelevation
																			No Superelevation
235A	235A-2	1330	5.4	194	72	PV-303	[2]		38490+63.31	38491+21.51						38490+71.21	38490+71.21		
							38499+93.76		38499+29.96	38498+71.76						38499+22.06	38499+22.06		
235A	235A-3	1330	5.4	194	72	PV-303	38502+04.71		38502+68.51	38503+26.71						38502+76.41	38502+76.41		
							[3]		38511+66.22	38511+08.02						38511+58.32	38511+58.32		
235B	235B-1	1000	6.0	216	72	PV-303	32575+74.77		32576+53.97	32577+18.77						32576+46.77	32576+46.77		
							32583+42.32		32582+63.12	32581+98.32						32582+70.32	32582+70.32		
235B	235B-2	1820	4.6	166	72	PV-303	32584+78.46		32585+22.66	32585+72.46						32585+50.81	32585+50.81		
							[4]		32595+34.44	32594+84.64						32595+06.29	32595+06.29		
235G	235G-1	3500	3.0	108	72	PV-303	[5]		38552+54.84	[5]									
							38558+21.63		38558+18.03	38557+85.63									
235G	235G-2	1330	5.4	194	72	PV-303	38574+26.29	38574+98.29	38576+34.09	38576+92.29						38576+41.99	38576+41.99		
235G	235G-2	1330	5.4	194	72	PV-303													
							38591+58.32		38590+94.52	38590+36.32						38590+86.62	38590+86.62		
235G	235G-3	1330	5.4	194	72	PV-303	38600+12.21		38600+76.01	38601+34.21						38600+83.91	38600+83.91		
235G	235G-3	1330	5.4	194	72	PV-303													
							38610+46.96	38609+74.96	38608+39.16	38607+80.96						38608+31.26	38608+31.26		
235G	235G-4	8100	NC	N/A	N/A														No Superelevation

NOTE:
[1] Sta. 8465+42.83 5.2%. Refer to K Sheets.
[2] Sta. 38490+71.23 4.0%. Refer to K Sheets.
[3] Sta. 38511+66.22 3.78%. Refer to Ramp A Exit Detail in the U Sheets.
[4] Refer to Ramp B Entrance Detail in the U Sheets.
[5] Refer to Ramp G Entrance Detail in the U Sheets.



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER G.7

11:53:03 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht

MAINLINE I-235

MAINLINE NB I-35

MAINLINE NB I-35

RAMP G

MAINLINE NB I-35

WB I-80 to SB I-235 RAMP G

WB I-80 to NB I-35 RAMP A

PC Sta 8491+99.33

PI Sta 8499+65.23

PT Sta 8505+89.13

PI Sta 38495+12.65

PT Sta 38590+94.52

PI Sta 38486+84.50

PC Sta 38490+63.31

PT Sta 38488+93.31

PC Sta 38484+75.18

PC Sta 38600+76.01

PI Sta 38604+68.41

PT Sta 38499+29.96

PC Sta 38502+68.51

PI Sta 38507+35.22

PT Sta 38608+39.16

PT Sta 38511+66.22

PC Sta 2090+59.42

PC Sta 2091+68.09

PC Sta 2091+68.42

PI Sta 2096+10.48

PC Sta 8531+09.25

PC Sta 2100+51.90

PI Sta 2100+53.74

PI Sta 8536+86.32

PI Sta 2104+93.64

PT Sta 2109+34.40

PT Sta 2109+31.19


PT Sta 8542+62.49

0 200 FEET

MAINLINE AND RAMP GEOMETRICS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER G.8


11:53:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht



MAINLINE AND RAMP GEOMETRICS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER G.9


11:53:05 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht



SIDE ROAD GEOMETRICS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER G.10

11:53:06 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht



SIDE ROAD GEOMETRICS

FILE NO.	ENGLISH	DESIGN TEAM	COUNTY	PROJECT NUMBER	SHEET NUMBER G.11

11:53:07 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194G01.sht

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /CARMAN
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 7/24/2019
Color Legend:

- Property Lines
- Temporary Easement
- Permanent Acquisition

NE¼ SW FRL¼ SEC. 7-79-23

KREG ENTERPRISES, INC.
18A

LEGACY III, LLC.
18

2112+05
℄278'±Ex.R/W

2110+25
℄225'

2109+33±P
℄215'

2104+30
℄175'

2101+60
℄195'

8540

8535

0 50
FEET

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.1

10:59:48 AM 7/25/2019 untitled pw:\\ntPwInt1.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /CARMAN
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 7/24/2019
Color Legend:
- Property Lines
- Temporary Easement
- Permanent Acquisition

N

LEGACY III, LLC.

18

STATE OF IOWA

SE¼ SW FRL¼
SEC. 7-79-23

2097+75
℄205'

2097+23±Ex.R/W
℄200'

2085+00
℄390'

FUTURE ROW/CA LINE

NB I-35 (ML035N)

0 FEET 50

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.2

4:20:52 PM 7/24/2019 untitled pw:\\ntPwInt1.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /GROAT
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 03-01-18
Color Legend:

- Property Lines
- Temporary Easement
- Permanent Acquisition

CHA SR54TH_P & SEC. LINE

DELAWARE TWP. T-79-N R-23W SEC. 18

STATE OF IOWA

2085+00 ℄390′

2083+15 ℄400′

2077+45 ℄635′

2075+75 ℄795′

NE¼ NW¼ SEC. 18-79-23

0 50 FEET

NB I-35 (ML035N)

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.3

3:54:41 PM 3/29/2018 untitled pw:\\projectwise.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /GROAT
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 03-01-18
Color Legend:

- Property Lines
- Temporary Easement
- Permanent Acquisition

N

2072+70
℄1185'

STATE OF IOWA

2070+72±P
℄1690'

0 FEET 50

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.4

3:54:25 PM 3/29/2018 untitled pw:\\projectwise.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /GROAT
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 01/22/2020
Color Legend:

- Property Lines
- Temporary Easement
- Permanent Acquisition

N

RICH EYCHANER

1119+60
℄481'±Ex.R/W

1119+80
℄480'

TEMPORARY EASEMENT TO SHAPE, REMOVE FENCE & SEPTIC

19A
COMMERCE CENTER, LLC

1132+06±Ex.R/W
℄397'(R)

1130+20
℄435'

1126+30
℄395'

1129+95
℄320'

19
BYRON J. & CAROLYN A. STRAIN

1133+29
℄400

1133+
℄330'

CHA SUR080

1131+20±P
℄200'

23
IOWA NATURAL HERITAGE FOUNDATION

1131+48±P
℄215'


1132+11±Ex.R/W
℄243.59'

H.5

0 FEET 50

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.5

9:03:55 AM 5/19/2020 jlarso1 pw:\\\ntPwInt1.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row




Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /GROAT
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 03/04/2020
Color Legend:
- **Property Lines**
- **Temporary Easement**
- **Permanent Acquisition**

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IMN-035-4(194)87--0E-77	SHEET NUMBER H.6

9:09:31 AM 5/19/2020 jlarso1 pw:\\ntPwInt1.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.7	

8:49:18 AM 7/25/2019 untitled pw:\\ntPwInt1.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /GROAT
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 09-14-18
Color Legend:

- Property Lines
- Temporary Easement
- Permanent Acquisition

N 40°

RD. 1/2" RE-ROD W/ YEL. CAP 7844

(16) JTB INVESTMENTS, L.L.C. 1/2 INT. &
NORWALK READY MIXED, INC. 1/2 INT.

(5) WHALEY WASTE SYSTEMS, INC.

(1R) UNION PACIFIC RAILROAD

2042+75±P
℄530'

2041+42±P
℄485'

2037+09±P
℄395'

2036+50
℄395'

2036+30
℄375'

2033+55
℄340'

2031+73±Ex.R/W
℄305'

(Close)

(Close)

(U.A.C.)

DELAWARE TOWNSHIP
ESTABLISHED 1849

0 FEET 50

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.8	

10:33:05 AM 9/14/2018 untitled pw:\\projectwise.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

Right of Way Design Information

THIS SHEET INCLUDED FOR INFORMATION ONLY

ROW Team: LARSON /GROAT
ROW #: IMN-035-3(201)87--0E-77
Plan Date: 03-01-18
Color Legend:
- Property Lines
- Temporary Easement
- Permanent Acquisition

1185

NE BROADWAY AVE. (SRBWY)

UCS HOLDINGS, L.L.C.

DES MOINES BAPTIST CHU

DELAWARE TWP.
T-79-N R-23W
SEC. 19

(Close)

(Close)

(U.A.C.)

3±Ex.R/W

2030+73±Ex.R/W
℄235'

2027+70
℄225'

2017+97±P
℄155'

17

TLC
PROPERTIES

DELAWARE TWP.
T-79-N R-23W
SEC. 19

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER H.9	

3:55:44 PM 3/29/2018 untitled pw:\\projectwise.dot.int.lan:PWMain\Documents\Projects\7703501010\ROW\NE Mixmaster_Section 3\Section 3.row

108-23A
08-01-08

TRAFFIC CONTROL PLAN

1. Traffic will be maintained on I-35, I-235, and I-80 at all times as provided on the following staging sheets, except as provided for in the following notes.

   A. Temporary nighttime full road closure of I-35, I-235, and I-80 will be permitted as follows.

      - Short duration of up to 20 minutes to complete overhead work and to set new bridge beams. The Contractor shall submit the traffic control plan 2 weeks in advance to the Engineer for approval.
      - Extended durations of over 20 minutes to remove existing bridge or place bridge beams. I-35, I-235, and I-80 traffic will be detoured to local roads per Off Site Detours. The Contractor shall submit the traffic control plan 2 weeks in advance for the Engineer's approval.

2. Install PCMS on interstates per Off-Site Detour plans for extended duration temporary nighttime full road closure. Coordinate messages with Engineer.

3. Coordinate with Engineer during temporary nighttime road closures to display sign messages on permanent DMS on I-235 NB, NB I-35/EB I-80, I-35 SB, and I-80 EB.

4. Contractor shall fully remove all detour signing nightly.

5. Contractor is responsible for installation, maintenance, and removal of all detour signing.

108-26A
08-01-08

STAGING NOTES

STAGING NOTES

Stage 3A-1

Traffic:
-Maintain Traffic on existing roadways.
-Maintain traffic with lane closures during off-peak hours for shoulder strengthening and milling/filling rumble strip activities
-Temporary closures for erecting overhead sign truss

Construction:
-Construct footings and erect overhead sign truss at Sta. 1030+87.01 on EB I-80/35
-Construct median footing at Sta. 1057+45.46 on EB I-80/35 for overhead sign truss
-Construct I-80/35 EB shoulder strengthening/widening in median west of NE 22nd St
-Remove existing Dynamic Message Sign at Sta. 2019+52.31 on WB I-235 and footings
-Construct median footing for overhead dynamic message sign at Sta. 2019+98.21 on WB I-235

Stage 3A-2

Traffic:
-Maintain Traffic on existing roadways.
-Maintain traffic via detour widening and lane shifts
-Reduce I-35 NB to 3 lanes just north of NE 54th Ave.
-I-80/35 EB, I-80 WB, I-235 SB, and I-35NB traffic in chute design at tie-ins
-Temporary short term closures of I-80 EB and WB, I-35 NB, SB to EB ramp, EB to NB ramp and WB to SB ramp for setting beams
-Temporary closures of NE 29th St. for setting beams
-Temporary closures of Chichaqua Valley Trail for tying in trail pavement and setting beams
-Temporary closures of NE Broadway Ave. for setting beams
-Place Portable Changeable Message Sign on WB I-235 to temporarily replace existing DMS that is being removed
-Temporary closures for erecting overhead sign truss and DMS truss

Construction:
-Construct I-35 NB ramp and flyover bridge with gaps at EB to SB ramp and WB to NB ramp
-Construct I-35 NB interim exit Taper and interim shoulder
-Construct outside footing at Sta. 1057+45.46 on EB I-80/35 for overhead sign truss and erect structure
-Grade and pave relocated temporary, interim and portions of ultimate Chichaqua Valley Trail
-Construct Ramp G Bridge over NE 29th St and relocated Chichaqua Valley Trail
-Construct footing and erect cantilevered sign truss at Sta. 1170+31.40 on WB I-80
-Construct footing and erect cantilevered sign truss at Sta. 1201+62.99 on WB I-80
-Construct retaining wall along Ramp B
-Construct Ramp B bridge over UPRR
-Construct Ramp G bridge over Broadway Ave
-Grade and pave Ramp G partial, Ramp A and Ramp B
-Construct Ramp G interim exit Taper
-Construct outside footing at Sta. 2019+98.21 on WB I-235 for overhead dynamic message sign and erect structure

Stage 3B

Traffic:
-Maintain traffic on existing and new roadway
-No chute design
-Open Ramp G partial, Ramp A and Ramp B to traffic
-Permanently close existing EB to SB ramp and WB to NB ramp to traffic

Construction:
-Complete Gap on I-35 NB bridge and grade and pave gap
-Remove existing EB to SB and WB to NB ramps

Stage 3C-Complete

Traffic:
-Open I-35 NB to traffic
-Permanently close existing I-35 NB left exit ramp to traffic
-Temporary short term closures of I-80 WB for ramp bridge demo

Construction:
-Remove existing I-35 NB left exit ramp pavement and bridge

CROSS SECTION VIEW COLOR LEGEND OF TRAFFIC CONTROL AND STAGING SHEETS

SHADING	Design Color No.	
Green, Light	(225)	Existing Pavement Shading
Gray, Light	(48)	Previously Constructed Pavement Shading
Gray, Med	(80)	Previously Constructed Granular Surface Shading
Blue, Light	(230)	Proposed Pavement Shading
Lavender	(9)	Temporary Pavement Shading
Brown, Med	(237)	Future Proposed Pavement Shading

CROSS SECTION VIEW PATTERN AND SYMBOL LEGEND OF TRAFFIC CONTROL AND STAGING SHEETS

	Pavement Removal		Proposed Granular Shoulder
	Proposed Granular Subbase		Temporary Shoulder
	Proposed Special Backfill		Existing Shoulder Strengthening
	Temporary Barrier Rail		Permanent Barrier Rail
			Channelizing Device

PLAN VIEW COLOR LEGEND OF TRAFFIC CONTROL AND STAGING SHEETS

LINEWORK	Design Color No.	
Green	(2)	Existing Topographic Features and Labels
Magenta	(5)	Pavement Marking Call Outs
Blue	(1)	Proposed Alignment, Stationing, Tic Marks, and Alignment Annotation
Yellow	(4)	Pavement Markings, Yellow
Off White	(254)	Pavement Markings, White
Violet	(15)	Temporary barrier rail, Unpinned
Flush Orange	(228)	Temporary barrier rail, Pinned
SHADING	**Design Color No.**	
Green, Light	(225)	Existing Pavement Shading
Gray, Light	(48)	Previously Constructed Pavement Shading
Gray, Med	(80)	Proposed Granular Surface Shading
Gray, Med	(80)	Previously Constructed Granular Surface Shading
Blue, Light	(230)	Proposed Pavement Shading
Lavender	(9)	Temporary Pavement Shading
Brown, Light	(236)	Proposed Grading Limits Shading
Pink, Dark	(13)	Proposed MSE or CIP Wall Shading
Red	(3)	Proposed Bridge Shading and Sign Trusses
Black w/Gray, Light Fill	(0,48)	Previously Constructed Structure

PLAN VIEW PATTERN AND SYMBOL LEGEND OF TRAFFIC CONTROL AND STAGING SHEETS

●	Channelizing Device		Crash Cushion (Temp or Perm)
✕	Drum		Traffic Signal
◘	Temporary Lane Separator		Flagger
◆	Tubular Marker		Temporary Floodlighting
♦	Channelizer Marker		Traffic Sign
△	Concrete Barrier Marker		Type III Barricade
☇	Delineator		Type A Warning Light
	Temporary Barrier Rail		Direction of Traffic
	Pavement Removal		Safety Closure
	Sand Barrel Layout	1	Lane Identification

NOTE: Device spacing according to Standard Road Plans unless specifically dimensioned.

TRAFFIC CONTROL AND STAGING LEGEND AND SYMBOL INFORMATION SHEET


(COVERS SHEET SERIES J)

J.13
J.12
J.11
J.14
J.15
J.16
J.17
J.18
J.6
J.7
J.8
J.9
J.10


NO SCALE
NORTHEAST MIX MASTER
GRADING STAGE 1
SHEET LAYOUT
OVERVIEW

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.3	

8:46:43 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht




PHASING TYPICALS
MAINLINE I-80 (ML080)
STA. 5150+00




PHASING TYPICALS
MAINLINE I-80 (SUR080)
STA. 1062+00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	J.4

8:46:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht



PHASING TYPICALS
MAINLINE I-235 (ML235)
STA. 2099+50



PHASING TYPICALS
MAINLINE I-235 (ML235)
STA. 2027+00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	J.5

8:47:08 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

F03

F03

F03

Billboard

1045

1050

1055

SUR080

SIGN BRIDGE

SIGN

MM

16'

12'

I-35 SB/ I-80 WB

S.S.

SIGN BRIDGE

12'
12'
12'

LGT

I-35 NB/ I-80 EB

12'
12'
12'
12'

SIGN

SIGN

SIGN

SIGN BRIDGE

RRB

ROAD WORK AHEAD


W20-1
48" x 48"
STA. 1046+00

0 50
FEET

INTERSTATE 80/35
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.6

8:47:17 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht



INTERSTATE 80/35
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.7

8:47:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

STA. 8478+36.72
STOP ML035N GRADING

STA. 8477+34.07, 209.88' LT
BEGIN TBR

STA. 32583+48.58, 60.40' LT
END TBR

EB I-80 to SB I-235 RAMP B (235B)

ML035N

235B

STA. 32574+22.46
BEGIN RAMP B GRADING

8480

8475

32575

32580

32585

38580

16'

12'

0 50
FEET

INTERSTATE 35/RAMP B
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.8

8:47:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

I-235 EB

I-235 WB

2045

2040

2035

16'

12'

ML235

ROAD WORK AHEAD

W20-1
48" x 48"
STA. 2045+00

STA. 38569+60.04
STOP RAMP G GRADING

235G

38575

32590

38570

38565

32595

235B

EB I-80 to SB I-235 RAMP B (235B)

STA. 32590+33.22
STOP RAMP B GRADING

STA. 32593+05.82
END RAMP B GRADING

STA. 32592+50.22
RESUME RAMP B GRADING

32589

0 FEET 50

RAMP B/RAMP G
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.9

8:48:00 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

STA. 2027+00.00
PHASING TYPICAL

ML235

I-235 EB

I-235 WB

2030

2025

2020

38560

38555

235G

END
ROAD WORK

G20-2A
48" x 24"

STA. 2023+00

STA. 8557+03.00
BEGIN RAMP G GRADING

STA. 38559+07.52
STOP RAMP G GRADING

STA. 38560+69.57
RESUME RAMP G GRADING

STA. 2019+98.21 (ML235)
DMS TRUSS

APPROX. SEC. LINE

Open Storage

SIGN

Billboard

0 50
FEET

RAMP G
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.10

8:48:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

I-235 WB
I-235 EB
ML235
2070
2075
2080
2085
ROAD WORK AHEAD
W20-1
48" x 48"
STA. 2075+00
STA. 8507+48.88, 88.98' LT
END TBR (1' CLEAR SPACE)
STA. 8508+25.58, 114.15' LT
END TBR
STA. 8504+86.72
RESUME ML035N GRADING
GRADE BERM ONLY
ML035N
8505
8510
8515
STA. 8505+50.00
STOP RAMP G GRADING
STA. 8508+00.00
RESUME ML035N GRADING
STA. 8505+92.46, 95.58' RT
BEGIN TBR
STA. 8505+02.23, 190.39' RT
BEGIN TBR (1' CLEAR SPACE)
16'
WB I-80 to NB I-35 RAMP A (235A)
38490
38495
38500
235A
STA. 38488+93.31
BEGIN RAMP A GRADING
APPROX. SECT.
SIGN
SIGN BRIDGE
FO3
0 50
FEET

INTERSTATE 35/RAMP A NORTHEAST MIX MASTER TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	J.11

8:48:17 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

Pond

Billboard

SIGN BRIDGE

I-35 SB

I-35 NB

ML235

St.S.

2090

2095

2100

12'

F03

STA. 2090+00.00, 74.55' RT
BEGIN TBR

MW

SIGN

8520

8525

8530

ML035N

235A

38485

STA. 8524+50.00
END CONSTRUCTION

STA. 2099+50.00
PHASING TYPICAL

0 50
FEET

INTERSTATE 35/RAMP A
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.12

8:48:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

Billboard

SIGN BRIDGE

Rip Rap

Rip Rap

SIGN BRIDGE

12'
12'
12'
12'

12'
12'
12'

St.S.

St.S.

St.S.

St.S.

ML235

I-35 SB

I-35 NB

2105

2110

2115

8535

8540

MM

SIGN

F03

F03

ML035N

STA. 2109+31.19, 77.00' RT
END TBR

END
ROAD WORK

G20-2A
48" x 24"
2110+00

0 FEET 50

INTERSTATE 35/RAMP A
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.13

8:48:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

STA. 38511+66.22
END RAMP A GRADING

235A

WB I-80 to NB I-35 RAMP A (235A)

38500

38505

38510

38610

235G

STA. 38611+66.22
RESUME RAMP G GRADING

38605

51989

F03

E2

EB

SIGN

16'

12'

110

UB

SIGN BRIDGE

0 FEET 50

RAMP A/Ramp G
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.14

8:48:40 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

38615

38620

38625

235G

FO3

FO3

1125

1120

1115

SUR080

SIGN

I-80 WB

I-80 EB

12'
12'
12'

0 FEET 50

RAMP G
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.15

8:48:48 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

SEC. LINE

STA. 21+18.00, 0.00' RT
TIE TO EXISTING TRAIL

STA. 38637+77.87
END RAMP G GRADING

STA. 5137+77.87
BEGIN ML080 GRADING

STA. 38807+00.00, 17.00' RT
END TBR

STA. 38631+20.84
STOP RAMP G GRADING

STA. 38633+32.87
RESUME RAMP G GRADING

STA. 5135+10.02, 39.25' LT
BEGIN TBR

SIGNAL BRIDGE

SIGNAL BRIDGE

I-80 WB

I-80 EB

ML080

GAP GRADING OVER EXISTING
TRAIL UNTIL PROPOSED TRAIL
IS CONSTRUCTED AND PEDESTRIAN
TRAFFIC IS MOVED ONTO NEW TRAIL

STA. 13+98.43, 0.00' RT
TIE TO EXISTING TRAIL

STA. 38802+87.20, 23.00' RT
BEGIN TBR

20

38630

38635

38805

5130

5135

5140

12'
12'
12'

FO3

TP

235G

SIGN

0 50
FEET

INTERSTATE 80/RAMP G
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.16

8:48:56 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

STA. 5150+58.17
END ML080 GRADING

STA. 5152+00.00, 36.25' LT
END TBR

F03

I-80 WB

12'
12'
12'

I-80 EB

12'
12'
12'

5145

5150

5155

SIGN

ML080

STA. 5150+00.00
PHASING TYPICAL

0 50
FEET

INTERSTATE 80
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.17

8:49:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

ROAD WORK AHEAD

W20-1
48" x 48"
STA. 5168+00

STA. 5170+31.36 (ML080)
CANTILEVER SIGN

12'
12'
12'

I-80 WB

I-80 EB

12'
12'
12'

SIGN

5160
5165
5170
5175


ML080

0 FEET 50

INTERSTATE 80
NORTHEAST MIX MASTER
TRAFFIC CONTROL GRADING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.18

8:49:14 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht



NO SCALE

STAGE 1
ACCESS ROUTES

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.19

8:49:22 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht


Access Route Ingress
Access Route Egress
Existing Route From Previous Stage
Temporary Barrier Rail Location
Safety Fence Location

NO SCALE

STAGE 1
ACCESS ROUTES

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.20

8:49:41 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht



NO SCALE

STAGE 1
ACCESS ROUTES

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER J.21

8:49:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194J03.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 38501+70.00
Install 30" x 90' DR-601 .
F.L. = Lt. 934.75
Rt. 938.08

Sta. 38488+93.31 (RAMP A) =
Sta. 8515+98.97, 48.95' RT (NB I-35)
Begin Ramp Construction

NE 54TH AVENUE
(By Others)

PT Sta 38488+93.31

PC Sta 38490+63.31

PT Sta 38499+29.96

38490

38495

38500

FUTURE WB I-80 to NB I-35

WB I-80 to NB I-35
RAMP A (235A)

NB I-35 (ML035N)

Curve Data
Δ = 37° 20' 05.39" (LT)
T = 449.34
L = 866.65
R = 1,330.00
E = 73.85
e = 5.4%
L = 194
x = 72
DS = 50mph

PI Sta 38495+12.65

DELAWARE TWP.
T-79-N R-23W
SEC. 18

0 50
FEET

WESTBOUND I-80 to NORTHBOUND I-35 RAMP A

STA. 38488+93.31
BEGIN CONSTRUCTION
ELEV 954.04

954.04

VPI +75.000
Elv 953.39
K = 95
Len 250.00 ft
DS = 50mph

EXIST. GROUND

-0.360%

-3.000%

VPI +75.000
Elv 944.39
K = 100
Len 350.00 ft
DS = 50mph

+0.500%

VPI +75.000
Elv 945.89
K = 200
Len 200.00 ft
DS = 50mph

-0.500%

PROPOSED PGL

-0.500%

VPI +75.000
Elv 943.39
K = 152
Len 250.00 ft
DS = 50mph

+1.147%

+93 Lt.
949.90

-2.66% Lt. Ditch Grade

+30 Rt.
942.28

-0.50% Rt. Ditch Grade

+00 Lt.
939.10

-0.50% Lt. Ditch Grade

+70 Rt.
938.08

+4.00% Rt.
Ditch Grade

+0.50% Rt.
Ditch Grade

+50 Rt.
941.28

965 960 955 950 945 940 935 930

Lt: Ditch Grade | Ditch Grade

Rt: Vari. - See Cross Section | Ditch Grade | Ditch Grade | Ditch Grade

954.02 953.93 953.84 953.71 953.52 953.27 952.95 952.56 952.11 951.59 951.00 950.35 949.64 948.92 948.26 947.67 947.14 946.67 946.26 945.92 945.64 945.42 945.26 945.17 945.14 945.17 945.26 945.39 945.50 945.57 945.62 945.64 945.62 945.57 945.50 945.39 945.26 945.14 945.01 944.89 944.76 944.64 944.51 944.39 944.26 944.14 944.01 943.91 943.84 943.82 943.84 943.90 944.00 944.14 944.33 944.55 944.82 945.11 945.39

38489 38490 38491 38492 38493 38494 38495 38496 38497 38498 38499 38500 38501 38502 38503

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.1

12:08:09 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 38511+66.22 (RAMP A) =
Sta. 38611+66.22, 52.00' LT (RAMP G)
End Ramp Construction

PI Sta 38511+66.22

38505

38510

FUTURE WB I-80 to NB I-35

WB I-80 to NB I-35
RAMP A (235A)

PI Sta 38507+35.22

Curve Data
Δ = 38° 40' 21.70" (LT)
T = 466.71
L = 897.70
R = 1,330.00
E = 79.51
e = 5.4%
L = 194
x = 72
DS = 50mph

FUTURE WB I-80 to SB I-235

WB I-80 to SB I-35
RAMP G (235G)

NOTE: Refer to sheet E.5
for Special Ditch

(U.A.C.)

FUTURE WB I-80

WESTBOUND I-80

AF03

0 50
FEET

DELAWARE TWP.
T-79-N R-23W
SEC. 18

WESTBOUND I-80 to NORTHBOUND I-35 RAMP A

VPI +75.000
Elv 950.27
K = 180
Len 700.00 ft
DS = 50mph

PROPOSED PGL

+1.147%

-2.740%

EXIST. GROUND

939.55

STA. 38511+66.22
END CONSTRUCTION
ELEV 939.55

+0.50% Rt. Ditch Grade

+50 Rt.
944.28

-4.39% Rt. Ditch Grade

+66 Rt.
930.41

-0.50% Lt. Ditch Grade

+20 Lt.
930.50

-4.00% Lt. Ditch Grade

+66 Lt.
924.65

960 955 950 945 940 935 930 925

Lt Ditch Grade Ditch Grade

Rt Ditch Grade Ditch Grade

945.68 945.97 946.25 946.52 946.76 946.96 947.12 947.26 947.35 947.41 947.44 947.43 947.39 947.31 947.20 947.05 946.87 946.65 946.40 946.12 945.80 945.44 945.05 944.63 944.17 943.67 943.14 942.58 941.98 941.35 940.68 940.00

38504 38505 38506 38507 38508 38509 38510 38511

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.2

12:08:15 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

FUTURE EB I-80

Sta. 32574+82.00, 28.5' Lt.
Area Intake SW-562
w/24" x 90' DR-601

Sta. 32584+11.43, 223.6' LT
Install 30" x 106' DR-601
(Trenchless)
Skew = 0° Ahd.
F.L. = Lt. 947.25
Rt. 947.80
(See Sheets V.17)

(U.A.C.)

FUTURE WB I-80
to SB I-235

PI Sta 32579+68.33

32580

EB I-80 to SB I-235 RAMP B (235B)

32585

PC Sta 32585+22.66

Sta. 32587+55.00, 8.00' RT
End Ramp Taper

Sta. 8473+98.99 (ML035N)
Sta. 2040+08.19 (NE 22nd St)

NB I-35 (ML035N)

POT Sta 32574+22.46

32575

PC Sta 32576+53.97

PT Sta 32582+63.12

PROPOSED RETAINING WALL

Sta. 32585+75.00, 20.00' RT
Begin Ramp Taper

15:1 Taper

Curve Data
Δ = 34° 54' 05.36" (RT)
T = 314.35
L = 609.15
R = 1,000.00
E = 48.25
e = 6.0%
L = 216
x = 72
DS = 50mph

Sta. 3258X+XX, 20.00' Rt.
Area Intake SW-507
w/24" x 80' DR-601

Sta. 3256+58, 145' Lt
30" X 110' Conc Pipe
D.A. = 8 Ac - Median
Proposed Ramp B
Sta. 32584+89, 143' Lt
(Remove in (197))

SAYLOR TWP.
T-79-N R-24W
SEC. 13

Sta. 32574+22.46 (RAMP B) =
Sta. 8474+22.46, 40.00' RT (NB I-35)
Begin Construction

0 50
FEET

DELAWARE TWP.
T-79-N R-23W
SEC. 18

EASTBOUND I-80 to SOUTHBOUND I-235 RAMP B

VPI +75.000
Elv 954.18
K = 90
Len 300.00 ft

VPI +00.000
Elv 958.81
K = 177
Len 150.00 ft

VPI +00.000
Elv 958.11
K = 150
Len 150.00 ft

STA. 32574+22.46
BEGIN CONSTRUCTION
ELEV 948.31

948.31
+3.850%
+0.500%
+0.500%
-0.348%

+50 Lt.
948.80
-5.50% Lt. Ditch Grade
EXIST. GROUND
+00 Lt.
953.27
+4.28% Lt. Ditch Grade
+45 Lt.
938.07
+0.20% Rt. Ditch Grade
+50 Rt.
944.70
+4.25% Rt. Ditch Grade
+22 Rt.
935.03
+00 Lt.
953.00
-2.34% Lt. Ditch Grade
+75 Rt.
945.95
+50 Lt.
949.25
+4.12% Lt. Ditch Grade
-0.20%
+75 Rt.
950.10
-2.55% Rt. Ditch Grade
+25 Rt.
950.00
-1.92% Lt. Ditch Grade
+50 Lt.
954.50

970 965 960 955 950 945 940 935

Lt: Vari. - See Cross Sections | Ditch Grade | 5.0' Ditch | Ditch Grade
Rt: Ditch Grade | Wall | Ditch Grade

948.41 949.34 950.19 950.98 951.70 952.35 952.93 953.44 953.87 954.24 954.54 954.77 954.93 955.06 955.18 955.31 955.43 955.56 955.68 955.81 955.93 956.06 956.18 956.31 956.43 956.56 956.68 956.81 956.93 957.06 957.18 957.31 957.43 957.56 957.68 957.81 957.93 958.06 958.18 958.31 958.43 958.54 958.61 958.65 958.65 958.62 958.55 958.46 958.37 958.31 958.28 958.30 958.36 958.46 958.60 958.76


32575 32576 32577 32578 32579 32580 32581 32582 32583 32584 32585 32586 32587 32588

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.3


12:08:22 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

Sta. 32589+00.00
Install 30" x 124' DR-601
Skew = 0° Ahd.
F.L. = Lt. 949.70
Rt. 943.00

DELAWARE TWP.
T-79-N R-23W
SEC. 18



EASTBOUND I-80
to SOUTHBOUND I-235
RAMP B



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.4

12:08:28 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

Sta. 2020+27
24" X 89' Conc. Pipe

DELAWARE TWP.
T-79-N R-23W
SEC. 19

Sta. 38557+03.00 (RAMP G) =
Sta. 2028+39.88, 101.28' LT (I-235)
Begin Ramp Construction

Curve Data
Δ = 9° 13' 10.55" (LT)
T = 282.21
L = 563.19
R = 3,500.00
E = 11.36
e = 3.0%
L = 108
x = 72
DS = 50mph

PC Sta 38552+54.84

PI Sta 38555+37.05

PT Sta 38558+18.03

Sta. 38561+38.24, 16.00' LT
Begin Cable Guardrail

Sta. 38559+03.17, 16.00' LT
End Cable Guardrail

Equation:
Sta. 38559+88.29 RAMP G =
Sta. 1180+16.12 SB BROADWAY

38555

38560

NE BROADWAY AVE (SR6WV)

WB I-80 to SB I-235
RAMP G (235G)

SOUTHBOUND I-235

NORTHBOUND I-235

FUTURE SB I-235

FUTURE NB I-235

Sta. 38561+38.24, 24.00' RT
Begin Taper

DELAWARE TWP.
T-79-N R-23W
SEC. 19

Sta. 2024+29
30" X 215' Conc Pipe
D.A. = 10 Ac - R

0 50
FEET

DELAWARE TWP.
T-79-N R-23W
SEC. 18

WESTBOUND I-80
to SOUTHBOUND I-235
RAMP G

STA. 38557+03.00
BEGIN CONSTRUCTION
ELEV 959.07

959.07

VPI +00.000
Elv 962.04
K = 175
Len 350.00 ft
DS = 50mph

VPI +25.000
Elv 958.79
K = 151
Len 250.00 ft
DS = 50mph

+1.000%

-1.000%

PROPOSED PGL

-2.62% Rt. Ditch Grade

+00 Rt.
957.67

+70 Lt.
932.46

+40 Lt.
933.00

+0.20% Lt. Ditch Grade

No Ditch | Bridge | Ditch Grade

Vari. - See Cross Section | Bridge

Lt	959.29	959.54	959.79	960.04	960.29	960.52	960.72	960.88	961.00	961.09	961.15	961.16	961.15	961.09	961.00	960.88	960.72	960.52	960.29	960.04	959.81	959.62	959.48	959.37	959.31	959.29	Lt
Rt																											Rt

38552 38553 38554 38555 38556 38557 38558 38559 38560 38561 38562 38563

965 960 955 950 945 940 935 930

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.5

12:08:34 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

Sta. 2035+56
36" X 294'
Conc Pipe
D.A. = 16 Ac - R

Extend Existing 36" RCP
w/36" x 174' DR-626

Sta. 38566+00.00
Install 24" x 190' DR-601
Skew = 0° Ahd.
F.L. = Lt. 936.93
Rt. 944.58

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Open Storage

UPRR

SIGN

Gate

EB I-80 to SB I-235 RAMP B (235B)

Open Storage

Note: For Gore Detail,
Refer to sheet U.5

38565

38570

38575

WB I-80 to SB I-235
RAMP G (235G)

FUTURE WB I-80 to SB I-235

EB EB EB

PC Sta 38576+34.09

Sta. 38567+50.04 (Ramp G)

Sta. 38569+60.04 (Ramp G) =
Sta. 32593+09.10, 38.82' LT (Ramp B)
End Ramp G Construction

SOUTHBOUND I-235

St.S St.S St.S.

NORTHBOUND I-235

SIGN BRIDGE

MOIS

SIGN

FUTURE SB I-235

FUTURE NB I-235

St.S. St.S. St.S.

SIGN

0 FEET 50

DELAWARE TWP.
T-79-N R-23W
SEC. 18

WESTBOUND I-80
to SOUTHBOUND I-235
RAMP G

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.6

12:08:41 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

STA. 38569+60.04
STOP CONSTRUCTION
ELEV 962.96

FUTURE PGL

+0.656%

+0.656%

+4.000%

VPI +50.000
Elv 966.17
K = 150
Len 500.00 ft
DS = 50mph

+00 Rt.
955.50

-2.62% Rt. Ditch Grade

+00 Rt.
944.58

+0.25% Rt. Ditch Grade

+00 Rt.
945.33

+10.17% Rt.
Ditch Grade

+1.50% Lt. Ditch Grade

-0.50% Lt. Ditch Grade

+15 Lt.
937.12

+50 Lt.
935.45

WESTBOUND I-80
to SOUTHBOUND I-235
RAMP G

Lt Ditch Grade Ditch Grade

Rt Ditch Grade Ditch Grade Ditch Grade

959.30 959.36 959.47 959.61 959.77 959.94 960.10 960.27 960.43 960.59 960.76 960.92 961.09 961.25 961.41 961.58 961.74 961.91 962.07 962.23 962.40 962.56 962.73 962.89 963.05 963.22 963.38 963.55 963.71 963.87 964.04 964.20 964.37 964.53 964.71 964.94 965.21 965.52 965.87 966.27 966.70 967.18 967.70 968.26 968.86 969.51 970.19 970.92 971.69 972.50 973.36 974.25 975.19 976.17 977.17 978.17 979.17 980.17 981.16 982.13

38564 38565 38566 38567 38568 38569 38570 38571 38572 38573 38574 38575 38576 38577 38578

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.7

12:08:46 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 38613+57.50
Install 73" x 45" x 284' RCP DR-601
Skew = 47° Rt. Ahd.
F.L. = Lt. 922.50
Rt. 922.24

38619+50 Prop. Type "M" Dike
Elev. =927.00

Note: For Gore Detail,
Refer to sheet U.4

WB I-80 to NB I-35
RAMP A (235A)

38610

38615

38620

WB I-80 to SB I-235
RAMP G (235G)

FUTURE WB I-80 to SB I-235

PT Sta 38608+39.16

Sta. 38611+66.22 (Ramp G) =
Sta. 38511+66.22, 51.93' RT (Ramp A)
Begin Ramp G Construction

Sta. 38615+86.22
Begin Widening

Note: For Special Ditch,
Refer to sheet E.5

0 FEET 50

DELAWARE TWP.
T-79-N R-23W
SEC. 18

WESTBOUND I-80 to SOUTHBOUND I-235 RAMP G

FUTURE PGL

STA. 38611+66.22
RESUME CONSTRUCTION
ELEV 941.11

EXIST. GROUND

VPI +75.000
Elv 927.17
K = 267
Len 1200.00 ft
DS = 50mph

4.000%

+0.500%

+66 Rt.
930.41

-3.00% Rt. Ditch Grade

-4.00% Lt.
Ditch Grade

+66 Lt.
924.65

+20 Lt.
922.50

+0.20% Lt. Ditch Grade

+40 Rt.
922.20

+0.60% Rt. Ditch Grade

+75 Lt.
923.41

+15 Rt.
924.45

+50 Lt.
924.12

-0.50% Lt. Ditch Grade

950 945 940 935 930 925 920 915

Lt: Ditch Grade | Vari. - See Cross Sections | Ditch Grade

Rt: Ditch Grade | No Ditch | See Westbound I-80 Left Ditch

951.17 950.18 949.22 948.28 947.36 946.46 945.59 944.74 943.92 943.12 942.34 941.59 940.86 940.15 939.47 938.81 938.17 937.56 936.97 936.40 935.86 935.34 934.84 934.37 933.92 933.49 933.09 932.71 932.36 932.03 931.72 931.43 931.17 930.93 930.72 930.53 930.36 930.21 930.09 929.99 929.92 929.87 929.84 929.84 929.86 929.90 929.97 930.06 930.17 930.29 930.42 930.54 930.67 930.79 930.92 931.04 931.17 931.29 931.42 931.54

38609 38610 38611 38612 38613 38614 38615 38616 38617 38618 38619 38620 38621 38622 38623

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.8

12:08:52 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

Sta. 38625+80.00
Install 24" x 124' DR-601
Skew = 0° Ahd.
F.L. = Lt. 921.09
Rt. 923.73

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 1130+74
18" X 131' Conc Pipe
Remove 72' & Extend 18" RCP
w/ 18" x 50' Lt.

Equation:
Sta. 38632+22.58 RAMP G =
Sta. 38806+23.10 NE 29TH ST.

DELAWARE TWP.
T-79-N R-23W
SEC. 17

Sta. 38637+77.87 (RAMP G) =
Sta. 5137+77.87, 115.00' LT (I-80)
End Construction

19
BYRON J. & CAROLYN A. STRAIN

38625
38630
38635

NE 29TH STREET

CHICHAQUA VALLEY TRAIL

Equation:
Sta. 38632+81.86 RAMP G =
Sta. 17+52.13 CV TRAIL

Curve Data
Δ = 4° 57' 40.47" (LT)
T = 350.91
L = 701.38
R = 8,100.00
E = 7.60
e = NC
DS = 50mph

PT Sta 38637+77.87

PC Sta 38630+76.49

Tp

WB I-80 to SB I-235,
RAMP G (235G)

FUTURE WB I-80 to SB I-235

PC Sta 38634+27.39

SIGNAL BRIDGE
WESTBOUND I-80
SIGNAL BRIDGE
EASTBOUND I-80
I-80 (ML080)
FUTURE EB I-80
FUTURE WB I-80

F03

Sta. 1125+49
24" X 123'
Conc Pipe
(U.A.C.)

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 1128+24
18" X 127'
Conc Pipe
(U.A.C.)

0 FEET 50

DELAWARE TWP.
T-79-N R-23W
SEC. 17

Sta. 1135+07
24" X 131'
Conc Pipe

**WESTBOUND I-80
to SOUTHBOUND I-235
RAMP G**

VPI +75.000
Elv 935.67
K = 97
Len 350.00 ft
DS = 50mph

38635+30 Lt.
893.89

-2.31% Lt. Ditch Grade

38637+78 Lt.
888.16

+0.500%

-3.099%

EXIST. GROUND

-0.50% Lt. Ditch Grade

+50 Lt.
919.12

-4.12% Lt. Ditch Grade

+90 Lt.
909.24

-2.850%

VPI +00.000
Elv 925.60
K = 1206
Len 300.00 ft
DS = 50mph

917.68

STA. 38637+77.87
END CONSTRUCTION
ELEV 917.68

940 935 930 925 920 915 910 905

890 885

Lt Ditch Grade | Ditch Grade | Bridge | Vari. - See Cross Section | Ditch Grade


Rt See Westbound I-80 Left Ditch | Vari. - See Cross Section | Bridge | Vari. - See Cross Section

931.67 931.79 931.92 932.04 932.17 932.29 932.42 932.54 932.67 932.79 932.92 933.04 933.17 933.29 933.42 933.54 933.67 933.79 933.92 934.04 934.17 934.29 934.42 934.54 934.67 934.79 934.89 934.92 934.88 934.78 934.62 934.39 934.10 933.74 933.32 932.83 932.28 931.67 930.99 930.25 929.48 928.71 927.95 927.19 926.44 925.69 924.95 924.22 923.48 922.76 922.04 921.32 920.61 919.90 919.19 918.47 917.76

38624 38625 38626 38627 38628 38629 38630 38631 38632 38633 38634 38635 38636 38637 38638

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.9


12:08:57 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht



INTERCHANGE GRADING
I-35 NB & RAMP B

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.10

12:09:03 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht



INTERCHANGE GRADING RAMP B & G


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.11

12:09:10 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

INTERCHANGE GRADING I-35 NB

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.12


12:09:16 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht



INTERCHANGE GRADING
I-35 NB & RAMP A

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.13


12:09:22 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht



INTERCHANGE
GRADING
RAMP A & G

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.14

12:09:28 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht



INTERCHANGE GRADING RAMP G

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER K.15

1:56:24 PM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194K01.sht

STORM SEWER

(1) Diameter or equivalent diameter
* Bid Item
** For SW-545

INTAKES AND UTILITY ACCESSES

No.	Location Station and Offset	*Type or Standard Road Plan	Form Grade Elev.	Bottom Well Elev.	Extension Length** FT	Notes
	Existing Structures (For Information Only)					
26	5135+06.95, 18.984 Rt.	RA-47	926.63	922.34		UAC
30	5139+00.00, 18.50 Rt	SW-547	915.25	911.18		UAC
30A	5139+00.39, 43.71 Lt	DR-122	908.78			Elbow
32	5142+99.50, 18.71 Rt	SW-547	903.13	899.04		UAC
32A	5143+01.00, 43.7 Lt	DR-122	896.64			Elbow
34	5147+00.00, 18.60 Rt	SW-547	891.33	887.16		UAC
34A	5146+99.21, 44.15 Lt.	DR-122	884.76			Elbow
36	5151+00.00, 19.00 ft	SW-547	879.13	875.22		UAC
36A	5151+00.24, 43.85 Lt.	DR-122	872.81			Elbow
	Proposed Structures					
27	5135+25.00, 0.0 Lt	SW-547	926.8	920.8		Future Stg 5
27A	5135+25.14, 94.50 Lt	SW-562	924.5	917.31		
27B	5135+38.24, 158.59 Lt	DR-122	918			Elbow
27C	5135+53.14, 235.68 Lt	DR 122	894			Elbow
29A	5137+29.29, 83.00 Lt	SW-562				
29B	5137+24.18, 140.00 Lt	DR-122	914			Elbow
29C	5134+24.18, 220.00 Lt	DR-122	889.69			Elbow
30AA	5139+00.14, 25.0 Lt	SW-511	915.8	909.5		Temp. Inlet
30B	5139+03.48, 130.63 Lt	DR 122	886.27			Elbow
32AA	5143+01.50, 25.0 Lt	DR-122	903.71	897.4		Elbow
32B	5143+03.82, 134.63 Lt	DR 122	876.35			Elbow
34AA	5146+99.32, 25.17 Lt.	SW511	891.78	885.49		Temp. Inlet
34B	5146+98.81, 116.91 Lt	DR-122	868.93			Elbow
36B	5151+00.67, 100.04 LT	DR-122	860.78			Elbow

PIPES

Design Length, Slope, and Flowlines are calculated from inside wall to inside wall along CL of pipe. An additional 2 ft length is added to each side of the Design Length to account for estimated length to center of structures.

Line Number	Intake/ Utility Access No. From	To	Class 'D'	(1) Pipe Size IN	Bid* Length FT	Design Length FT	Slope %	Connected Pipe Joint (DR-121) Type	Flow Lines Inlet Elevation	Outlet Elevation	Other Elevation	Pipe Profile Sheet No.	Notes
	Existing Pipes (For Information Only)												
P-26A	e26	26A	2000	24		64.0	3.67		922.63	920.23		M.8	
P-26B	26A	26B	2000	24		72.0	27.28		920.23	900.7		M.8	
P-30A	e30	30AA	2000	18		58.7	4.09		911.18	908.78		M.9	
P-30AA	30AA	30A	2000	18		17.7	4.09		909.5	908.78		M.9	
P-30B	30A	30B	2000	18		87.0	25.88		908.78	886.27		M.9	
P-32A	e32	32A	2000	18		39.2	4.07		899.04	897.44		M.10	
P-32AA	32A	32AA	2000	18		18.7	4.07		897.4	896.64		M.10	
P-32B	32AA	32B	2000	18		91.0	22.3		896.64	876.35		M.10	
P-34A	34	34AA	2000	18		39.3	4.05		887.16	885.57		M.10	
P-34AA	34AA	34A	2000	18		18.0	4.05		885.49	884.76		M.10	
P-34B	34A	34B	2000	18		72.8	21.75		884.76	868.93		M.10	
P36A	36	36AA	2000	18		42.8	4.06		875.22	873.48		M.13	
P36AA	36AA	36A	2000	18		15.6	4.06		873.44	871.81		M.13	
P36B	36A	36B	2000	18		56.2	21.41		872.81	860.78		M.13	
	Proposed Pipes												
P-26C	26B	26C	2000	24	128	124.0	5.33		900.7	894.06		M.8	
P-26D	26c	26Apr	2000	24	22	20.0			894.06	894.06		M.8	
P-27a	27	27A	2000	24	20	16.0	31		918.91	918.5		M.8	Stub out and cap
P-27B	27B	27C	2000	24	68	64.0	0.4		918.5	917.55		M.8	
P-27C	27C	27D	2000	24	83	78.5	30		917.55	894		M.8	
P-26D	27D	27Apr	2000	24	22	20.0	0.4		894	893.92		M.8	
P-29B	29A	29B	2000	24	60	56.0	3.21		915.75	914		M.9	
P-29C	29B	29C	2000	24	84	80.0	30		914	889.69		M.9	
P-29D	29C	29Apr	2000	24	26	24.0			889.69	889.69		M.9	
P-30C	30B	30C	2000	18	106	104.0	1.59		886.27	884.63		M.9	
P-32C	30B	32Apr	2000	18	80	77.3	3.3		876.35	873.8		M.10	
P-34C	30C	34Apr	2000	18	74	71.2	3.39		868.93	866.52		M.10	
P36C	36B	36Apr	2000	18		72.5	20.8		860.78	859.27		M.13	NEMM Stg. 5

SURVEY SYMBOLS

- PPA Power Pole Co. 1
- PRA Power Riser Co. 1
- UB Utility Box
- TSG Traffic Signal
- TSL Traffic Signal and Luminare
- TCB Traffic Signal Box
- LUM Luminaire
- TPD Telephone Pedestal
- MH Utility Access (Manhole)
- IN Storm Sewer Intake
- INB Storm Sewer Beehive Intake
- WV Water Valve
- FHYD Fire Hydrant
- SI Sign
- SL Speed Limit Sign
- BB Billboard
- MM Mile Marker Post
- ROW Right of Way Rail
- TEV Evergeen Tree
- SHR Shrub
- TDC Tree Deciduous
- SWAMP
- FLG Flagpole
- BCL Bridge Centerline
- BD Bridge Deck
- BLS Bridge Low Steel
- UE Utility Elevation
- PRO Profile Shot
- BRG Bridge
- PLG Location of General Photo
- PIP Pipe Culvert
- SOP Size of Pipe or Culvert
- DU Centerline Draw or Stream (Up)
- D Centerline Draw or Stream (Down)
- DIK Centerline of Dike or Dam
- GDL Guard Rail Steel
- GPR Guard Post (4 or More Posts)
- GDC Guard Rail Cable
- RIP Rip-Rap
- TLN Tree Line
- TIL Tile Line
- FCL Chain Link and Security Fence
- FW Wire Fence
- RET Retaining Walls

- EP Edge of Paved Roads (ML or SR)
- SNP Unpaved Shoulder
- CU Back of Curb
- GU Gutter In Front of Curb
- ENT Centerline BL of Entrance
- ENP Edge Paved Entrance & Park Lot
- ENU Edge Unpaved Entrance & Parking
- SWK Sidewalk
- CON Concrete or A/C Slab
- E1 — ELA Underground Electric Line Co. 1
- E2 — ELA Underground Electric Line Co. 2
- ELA Underground Electric Line Co. 3
- T1 — ELA Underground Telephone Line Co. 1
- FO — FOA Underground Fiber Optic Co. 1
- FO2 — FOB Underground Fiber Optic Co. 2
- FO3 — FOB Underground Fiber Optic Co. 3
- FO4 — FOB Underground Fiber Optic Co. 4
- G — GLA Underground Gas Line Co. 1
- W — WLA Underground Water Line Co. 1
- St.S. — STA Storm Sewer Line Co. 1
- STA Storm Sewer Line Co. 2

UTILITY LEGEND

This is a POINT 25 Project and is subject to the provisions of IAC 761-115.25.

Mid American Energy - Power and Gas
Michael Younts
E1 / G — 10510 Douglas Avenue
Urbandale, Iowa 50322
515-252-6565 - myounts@midamerican.com

Iowa D. O. T. - Lighting and Fiber Optic
E2 — Tony Taylor
800 Lincoln Way
FO3 — Ames, Iowa 50010
515-239-1902 - Tony.Taylor@dot.iowa.gov
Olsson Associates - Gregory T. Seib
601 P Street
Lincoln, Nebraska 68508
402-458-5037
gseib@olssonassociates.com

Polk County - Lighting and Traffic Signals
Kurt Bailey
5885 NE 14th Street
Des Moines, Iowa 50313
515-286-3705
Kurt.Bailey@polkcountyiowa.gov

Century Link - Telephone and Fiber Optics
T1 — Dustin Withers
2103 East University Avenue
FO — Des Moines, Iowa 50317
515-263-7202
Dustin.Withers@centurylink.com

Windstream - Fiber Optics
Jim Wiand
FO2 — 115 South 2nd Avenue West
Newton, Iowa 50208
641-787-2270
jim.wiand@windstream.com

Iowa Communications Network (ICN) - Fiber Optics
Larry Klawitter
FO3 — Grimes State Office Building
400 East 14th Street
Des Moines, Iowa 50319
515-229-2046
larry.klawitter@iowa.gov

Iowa Network Services (INS) - Fiber Optics
Jeff Klocko
FO4 — 7760 Office Plaza Drive South
West Des Moines, Iowa 50266
515-830-0445
Jeff@netins.com

Des Moines Water Works - Water
Matt Smith
W — 2201 George Flagg Parkway
Des Moines, Iowa 50321
515-283-8781
msmith@dmww.com

St.S. — IDOT or Private

Polk County - Storm Sewer
Kurt Bailey
5885 NE 14th Street
Des Moines, Iowa 50313
515-286-3705
Kurt.Bailey@polkcountyiowa.gov

PLAN VIEW COLOR LEGEND OF STORM SEWER SHEETS

LINEWORK	Design Color No.	
Gray, Dark	(112)	Existing Topographic Features, Utilities, and Labels
Black	(17)	Proposed Storm Sewer Details, Alignment, Stationing, Tic Marks, and Alignment Annotation
SHADING	Design Color No.	
Gray, Light	(48)	Proposed Pavement Shading

PROFILE VIEW COLOR LEGEND OF STORM SEWER SHEETS

LINEWORK	Design Color No.	
Gray, Dark	(112)	Existing Ground Line Profile and Existing Utilities Information
Black	(17)	Proposed Pipes and Intakes

PLAN VIEW LINE STYLE LEGEND OF STORM SEWER SHEETS

- Plug and Abandon Existing Pipe or Structure
- Removal of Existing Pipe or Structure
- Previously Constructed Pipe or Structure
- Direction of Pipe Flow

PROFILE VIEW LINE STYLE LEGEND OF STORM SEWER SHEETS

- Existing Ground
- Proposed Ground
- Previously Constructed Pipe or Structure
- Proposed Pipe or Structure

- Reference Point / Station — Survey Line
- Section Corner
- Ground Line Intercept
- Saw Cut
- Guardrail
- Clearing & Grubbing Area
- Pavement Removal

RIGHT-OF-WAY LEGEND

- Proposed Right-of-Way
- Existing and Proposed Right-of-Way
- Easement and Existing Right-of-Way
- Borrow
- Easement (Temporary)
- Easement
- Excess
- A/C Access Control

STORM SEWER LEGEND AND SYMBOL INFORMATION SHEET

(COVERS SHEET SERIES M)

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.2

8:53:37 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194lgd.sht

Sta. 2030+13,
58' Lt.
12" X 70' C.M.P.

Extend Existing 12" CMP
w/12" x 120' Lt. DR-621

Sta. 2032+30,
59' Lt
12" X 74'
C.M.P.

Extend Existing 12" CMP
w/12" x 152' Lt. DR-621

N

APPROX. SECTION LINE

E2

St. Rt. 28

12" CMP

12" CMP


2028 2029 2030 2032 2033

0 20
FEET

STORM SEWER

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.3

8:53:44 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194M03.sht



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.5

8:53:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194M03.sht

Sta. 1135+07
24" X 131' Conc Pipe

Sta. 5135+06, 115.28' Lt.
Extend Existing 18" RCP
w/18" x 124' DR-601
Skew 17.5° Lt. Ahd.

STA 5135+53, 94.50' LT
AREA INLET SW-562
w/24" x 164' Lt. DR-621

STA 5135+24, 83.00' LT
AREA INLET SW-562
w/24" x 158' Lt. DR-621

Sta. 1138+99
18" X 146' Conc Pipe

Sta. 5139+03
Extend Existing 18" RCP LT
w/18" x 104' DR-621

STA 5139+00.00, 25.00 LT
AREA INLET SW-511

N

26APRON
27APRON
29APRON
30Outlet
30APRON

P-26D
P-27D
P-29D
P-30D

26C
27C
29C
30C

P-26C
P-27C
P-29C
P-30C

F03

27B
29B
30B

P-27B
P-30B

26B
27A
29A
30A
30AA

P-27A
P-30AA
P-30A

26A
P26A

5135
5136
5137
5138
5139
5140

PIPE DONE
IN STAGE 5

FUTURE INLET


e26
30

0 20
FEET

STORM SEWER


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.7

8:53:53 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194M03.sht



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.9

8:53:57 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194M03.sht



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.11

8:54:01 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194M03.sht

Sta. 1146+99
18" X 132'
Conc Pipe

Sta. 5146+99
Extend Existing 18" RCP
w/18" x 72' Lt. DR-621


STA 5147+00.00, 25.00 LT
TEMPORARY INLET SW-511

STA 5147+00.00 TO 5151+00, 25.0 LT
TEMPORARY DR-502 SLOTTED DRAIN

Sta. 1150+99
18" X 116'
Conc Pipe

Sta. 5151+00
Extend Existing 24" RCP
w/24" x 48' Lt. DR-621

STA 5151+00.00, 25.00 LT
TEMPORARY INLET SW-511



STORM SEWER


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER M.12

8:54:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194M03.sht

KEY MAP

LEGEND

- Existing Structure
- Proposed Structure
- Existing Sign (EAST 80 Davenport)
- Proposed Sign (EAST 80 Davenport)



NO SCALE

SHEET LAYOUT OVERVIEW

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.1

9:22:42 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

NOTE:

1. A structural analysis of the existing structure may be necessary to verify the existing structure can support the modified sign loads.

995 1000 1005 1010 1015 1020

80/35-77-X
M3000__STAGE__3



REPLACE REMOVED SIGN



REMOVE



EXISTING TO REMAIN

EXISTING STRUCTURE TO REMAIN

SEE NOTE 1







REMOVE ALL EXISTING SIGNS

EXISTING STRUCTURE TO REMAIN

0 100 FEET

STAGE 3 SIGN LOCATION DETAILS ALONG I-80/I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.2

9:24:56 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

NOTES:

1. Structure to be located in ultimate location outside of future widening.

2. Structure to be located outside of future widening.

3. Structure lengths shown are approximate and are rounded to the nearest 5 feet.



REMOVE ALL EXISTING SIGNS

EXISTING STRUCTURE TO REMAIN

1025 1030 1035 1040 1045 1050

80/35-77-X M305


80/35-77-X M304



STA. 1030+87.01
PULL THRU & ADVANCE ON
120 FT OVERHEAD TRUSS

SEE NOTE 1

80/35-77-X
M3001__STAGE__3



STA. 1046+00.00
INTERIM ARROW-PER-LANE ADVANCE ON
120 FT INTERIM OVERHEAD TRUSS

SEE NOTE 2

0 100 FEET

STAGE 3 SIGN LOCATION DETAILS ALONG I-80/I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.3

9:26:03 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

NOTES:

1. Structure to be located in ultimate location outside of future widening.

2. Structure to be located outside of future widening.

3. Structure lengths shown are approximate and are rounded to the nearest 5 feet.




REMOVE ALL EXISTING SIGNS

EXISTING STRUCTURE TO REMAIN

1055 1060 1065 1070 1075 1080

8465 8470 8475 8480

80/35-77-X
M3002__STAGE__3



STA. 1056+00.00
INTERIM ARROW-PER-LANE ON
125 FT INTERIM OVERHEAD TRUSS

SEE NOTE 2

80/35-77-X
M3003__STAGE__3



STA. 1063+45.07
INTERIM ADVANCE ON
40 FT INTERIM CANTILEVER

35-77-X R310

35-77-X R311



STA. 8471+08.83
PULL THRU & EXIT DIRECTION ON
105 FT OVERHEAD TRUSS


SEE NOTE 1

0 100
FEET

STAGE 3 SIGN
LOCATION DETAILS
ALONG I-80/I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.4


9:27:54 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht



STAGE 3 SIGN LOCATION DETAILS ALONG I-80

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.5

9:29:16 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht



STAGE 3 SIGN LOCATION DETAILS ALONG I-80


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.6

9:30:22 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

NOTE:

1. A structural analysis of the existing structure may be necessary to verify the existing structure can support the modified sign loads.

80-77-X
M4002__STAGE__3



EXISTING TO REMAIN

EXISTING TO REMAIN

REMOVE

REPLACE REMOVED SIGN

EXISTING STRUCTURE TO REMAIN

SEE NOTE 1

5140 5145 5150 5155 5160 5165

0 100 FEET

STAGE 3 SIGN LOCATION DETAILS ALONG I-80

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.7	

9:31:28 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

80-77-X M4001__STAGE__3



STA. 5170+31.40
INTERIM ADVANCE ON
85 FT INTERIM OVERHEAD TRUSS

SEE NOTE 1

DMS

EXISTING DYNAMIC MESSAGE
SIGN TO REMAIN

5170 5175 5180 5185 5190 5195

NOTES:

1. Structure lengths shown are approximate and are rounded to the nearest 5 feet.

0 100
FEET

STAGE 3 SIGN
LOCATION DETAILS
ALONG I-80

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.8

9:32:36 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

80-77-X M4000__STAGE__3



STA. 5201+63.12
INTERIM ADVANCE ON
85 FT INTERIM OVERHEAD TRUSS

SEE NOTE 1

5200 5205 5210 5215 5220 5225

NOTES:

1. Structure lengths shown are approximate and are rounded to the nearest 5 feet.

0 100
FEET

STAGE 3 SIGN LOCATION DETAILS ALONG I-80

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.9

9:33:43 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht

DMS

STA. 2018+00.00
DYNAMIC MESSAGE SIGN
105 FT OVERHEAD TRUSS

SEE NOTE 1

REMOVE EXISTING DYNAMIC
MESSAGE SIGN AND STRUCTURE

2015 2020 2025 2030 2035 2040 2045

NOTES:

1. Structure to be located in ultimate location outside of future widening.


2. Structure lengths shown are approximate and are rounded to the nearest 5 feet.

0 100
FEET

STAGE 3 SIGN
LOCATION DETAILS
ALONG I-235

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.10

9:35:28 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht



STAGE 3 SIGN LOCATION DETAILS ALONG I-35

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.11

9:37:40 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N01.sht


80/35-77-X M3000_STAGE_3



12.0" Radius, 2.0" Border, White on Green;
[N ORTH] E; [W EST] E; [Minneapolis] E Mod;
[Des Moines] E Mod; [1 MILE] E;
Table of letter and object lefts.

N 28.0	O 44.6	R 57.6	T 69.7	H 81.0	W 105.5	E 125.9	S 137.1	T 149.2
41.3	109.3							
M 18.4	i 39.6	n 48.8	n 65.3	e 80.6	a 94.7	p 111.2	o 125.0	l 140.6	l 149.8	s 157.3
D 22.3	e 39.2	s 53.0	M 79.3	o 99.5	i 115.1	n 124.3	e 139.6	s 153.4
l 68.1	M 85.1	l 96.9	L 101.1	E 110.6				

80/35-77-X M3001_STAGE_3



12.0" Radius, 2.0" Border, White on Green;
[EAST] E: [Davenport] E; [ ] E;
12.0" Radius, 2.0" Border, White on Green;
[NORTH] E; [WEST] E; [Minneapolis] E; [Des Moines] E;
12.0" Radius, 2.0" Border, White on Green;
Arrow Custom - 66.0° 90°; Arrow Custom - 66.0° 90°; 30D; Rounded Rectangle 3.0" Radius Yellow;
48A; Rounded Rectangle 3.0" Radius Yellow;
Table of letter and object lefts.

E 132.9	A 145.8	S 160.2	T 172.3
139.0			
D 93.8	a 110.7	v 125.5	e 140.7	n 156.1	p 172.7	o 186.5	r 202.1	t 212.1
l 312.0	N 353.0	O 368.4	R 381.5	T 393.5	H 404.8	W 438.3	E 456.8	S 468.1	T 480.2
365.7	441.2								
M 337.3	i 361.2	n 371.2	n 389.8	e 407.0	a 422.9	p 441.4	o 457.0	l 474.6	l 484.9	s 493.0
D 341.6	e 360.6	s 376.1	M 405.7	o 428.5	i 446.0	n 456.0	e 473.3	s 488.7
l 23.4	l 167.4	293.9	380.7	447.7	468.6					

80/35-77-X M304



12.0" Radius, 2.0" Border, White on Green;
[E AST] E; [Davenport] E Mod; [LEFT LANES] E;
Table of letter and object lefts.

28.5	E 82.5	A 98.2	S 112.6	T 124.7
D 17.8	a 34.7	v 49.5	e 64.7	n 80.1	p 96.7	o 110.5	r 126.1	t 136.1
L 34.6	E 44.0	F 53.4	T 62.1	L 79.4	A 87.5	N 99.5	E 110.1	S 119.5

80/35-77-X M305



12.0" Radius, 2.0" Border, White on Green;
[N ORTH] E; [W EST] E; [Minneapolis] E Mod;
[Des Moines] E Mod; [½ MILE] E;
Table of letter and object lefts.

N 28.0	O 44.6	R 57.6	T 69.7	H 81.0	W 105.5	E 125.9	S 137.1	T 149.2
41.3	109.3							
M 18.4	i 39.6	n 48.8	n 65.3	e 80.6	a 94.7	p 111.2	o 125.0	l 140.6	l 149.8	s 157.3
D 22.3	e 39.2	s 53.0	M 79.3	o 99.5	i 115.1	n 124.3	e 139.6	s 153.4
½ 60.5	M 92.7	l 104.5	L 108.8	E 118.2						


NOTE: SIGN DIMENSIONS ARE IN INCHES

SIGN DETAILS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.12

9:37:44 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N12.sht

80/35-77-X M3002_STAGE_3



12.0" Radius, 2.0" Border, White on Green;
[EAST] E; [Davenport] E; [ ] E;
12.0" Radius, 2.0" Border, White on Green;
[NORTH] E; [WEST] E; [Minneapolis] E; [Des Moines] E;
12.0" Radius, 2.0" Border, White on Green;
Arrow Custom - 66.0° 90°; Arrow Custom - 66.0° 90°; 30D; Rounded Rectangle 3.0" Radius Yellow;
48A; Rounded Rectangle 3.0" Radius Yellow;
Table of letter and object lefts.

E 132.9	A 145.8	S 160.2	T 172.3
139.0			

D 93.8	a 110.7	v 125.5	e 140.7	n 156.1	p 172.7	o 186.5	r 202.1	t 212.1	
I 312.0	N 353.0	O 368.4	R 381.5	T 393.5	H 404.8	W 438.3	E 456.8	S 468.1	T 480.2
365.7	441.2								
M 337.3	i 361.2	n 371.2	n 389.8	e 407.0	a 422.9	p 441.4	o 457.0	i 474.6	i 484.9	s 493.0
D 341.6	e 360.6	s 376.1	M 405.7	o 428.5	i 446.0	n 456.0	e 473.3	s 488.7	
I 23.4	I 167.4	293.9	380.7	447.7	468.6				

80/35-77-X M3003_STAGE_3



12.0" Radius, 2.0" Border, White on Green:
[WEST] E; [Des Moines] E; [RIGHT LANE] E;
Table of letter and object lefts.

41.5	W 110.5	E 128.9	S 140.2	T 152.3

D 21.9	e 40.9	s 56.4	M 86.0	o 108.8	l 126.3	n 136.3	e 153.5	s 169.0	
R 46.8	I 59.5	G 64.6	H 77.3	T 89.3	L 110.1	A 119.8	N 134.2	E 146.9	

35-77-X R310




12.0" Radius, 2.0" Border, White on Green;
[N ORTH] E; [Minneapolis] E Mod; Arrow 8 - 25.0" 120°;
Arrow 8 - 25.0" 120°;
Table of letter and object lefts.

37.7	N 91.7	O 108.3	R 121.4	T 133.4	H 144.7

M 21.4	i 42.6	n 51.8	n 68.3	e 83.6	a 97.7	p 114.2	o 128.0	i 143.6	i 152.8	s 160.3
14.4	158.4									

35-77-X R311



12.0" Radius, 3.0" Border, White on Green;
[W EST] E; [Des Moines] E Mod;
12.0" Radius, 1.5" Border, 0.5" Indent, Black on Yellow;
[EXIT] E Mod specified length; Arrow I-F - 35.0" 45°;
[ONLY] E Mod specified length;
Table of letter and object lefts.

30.3	W 91.3	E 111.6	S 122.9	T 134.9

D 16.3	e 33.2	s 47.0	M 73.3	o 93.5	l 109.1	n 118.3	e 133.6	s 147.4
E 17.7	X 29.6	I 43.0	T 48.3	69.3	O 108.5	N 121.7	L 134.5	Y 144.3

NOTE: SIGN DIMENSIONS ARE IN INCHES

SIGN DETAILS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER N.13

9:37:44 AM 10/7/2021 JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Roadway\Stage3\(194)_Grading\77035194N12.sht

80-77-X M4000_STAGE_3



12.0" Radius, 2.0" Border, White on Green;
[N ORTH] E: [Minneapolis] E Mod; [1 MILE] E;
Table of letter and object lefts.

34.7	N 88.7	O 105.3	R 118.4	T 130.4	H 141.7	
M 18.4	i 39.6	n 48.8	n 65.3	e 80.6	a 94.7	p 111.2	o 125.0	l 140.6	l 149.8	s 157.3
1 69.4	M 83.8	I 95.6	L 99.9	E 109.3		

80-77-X M4001_STAGE_3



12.0" Radius, 2.0" Border, White on Green;
[N ORTH] E: [Minneapolis] E Mod; [½ MILE] E:
Table of letter and object lefts.

34.7	N 88.7	O 105.3	R 118.4	T 130.4	H 141.7	
M 18.4	i 39.6	n 48.8	n 65.3	e 80.6	a 94.7	p 111.2	o 125.0	l 140.6	l 149.8	s 157.3
½ 60.5	M 92.7	I 104.5	L 108.8	E 118.2		

80-77-X M4002_STAGE_3



12.0" Radius, 2.0" Border, White on Green;
[N ORTH] E: [Minneapolis] E Mod; Arrow 8 - 25.0° 60°;
Table of letter and object lefts.


34.7	N 88.7	O 105.3	R 118.4	T 130.4	H 141.7	
M 18.4	i 39.6	n 48.8	n 65.3	e 80.6	a 94.7	p 111.2	o 125.0	l 140.6	l 149.8	s 157.3
18.4						

NOTE: SIGN DIMENSIONS ARE IN INCHES


SIGN DETAILS

SILT BASINS

Possible Standard: EW-403



Cross Section View



Longitudinal Profile View


* The functional height used in the volume equation is 95% of effective height. Effective height is 3 feet as shown in EW-403.
* Volume equation: (0.5*Length*(Width*Height+Width*(Height-Length*Avg%Slope))

Basin No.	Location		Bid Items		Stormwater Storage Volume Summary					Remarks
	Station	Side	Installation	Removal	Basin Width	Basin Length	Height	Avg. % Slope	Volume*	
			EACH	EACH	FT	FT	FT		CF	
1	8465+60.00	RT	1	1	10.0	50.0	2.85	4.3%	887.5	
1	8467+05.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
1	8468+05.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
1	8469+05.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
1	8470+05.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
1	8471+70.00	LT	1	1	30.0	50.0	2.85	0.5%	4087.5	
1	8476+60.00	LT	1	1	10.0	50.0	2.85	3.6%	975.0	210' LT
1	1066+10.00	LT	1	1	10.0	50.0	2.85	4.3%	887.5	
1	1067+30.00	LT	1	1	10.0	50.0	2.85	4.1%	912.5	
1	32584+70.00	LT	1	1	10.0	50.0	2.85	1.2%	1275.0	
1	32577+30.00	RT	1	1	10.0	50.0	2.85	0.2%	1400.0	
1	32580+40.00	RT	1	1	10.0	50.0	2.85	0.2%	1400.0	
2	32586+05.00	RT	1	1	10.0	50.0	2.85	0.2%	1400.0	
2	32586+95.00	RT	1	1	10.0	50.0	2.85	2.6%	1106.3	
2	32588+15.00	RT	1	1	10.0	50.0	2.85	2.6%	1106.3	
2	32589+55.00	RT	1	1	10.0	50.0	2.85	2.6%	1106.3	
2	32587+30.00	LT	1	1	10.0	50.0	2.85	1.9%	1187.5	
2	32588+60.00	LT	1	1	10.0	50.0	2.85	1.9%	1187.5	
2	32590+00.00	LT	1	1	10.0	50.0	2.85	0.6%	1350.0	
2	32590+64.00	LT	1	1	10.0	50.0	2.85	2.4%	1125.0	
3	32591+50.00	RT	1	1	10.0	50.0	2.85	1.0%	1300.0	
3	32591+85.00	LT	1	1	10.0	50.0	2.85	1.0%	1300.0	
4	38567+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
4	38568+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
4	38569+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
5	38562+00.00	LT	1	1	10.0	50.0	2.85	0.2%	1400.0	
5	38563+00.00	LT	1	1	10.0	50.0	2.85	0.2%	1400.0	
5	38560+50.00	LT	1	1	10.0	50.0	2.85	6.0%	712.5	114' LT
6	38558+35.00	LT	1	1	10.0	50.0	2.85	1.0%	1300.0	
6	38559+60.00	LT	1	1	10.0	35.0	2.85	2.3%	856.6	
7	38555+50.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
7	38557+50.00	LT	1	1	10.0	50.0	2.85	1.0%	1300.0	
8	2025+10.00	LT	1	1	10.0	50.0	2.85	1.3%	1262.5	
8	2024+45.00	LT	1	1	10.0	50.0	2.85	1.8%	1200.0	
8	2022+80.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
8	2021+80.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
8	2020+80.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
9	2018+40.00	LT	1	1	10.0	50.0	2.85	1.0%	1300.0	
10	2110+00.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
10	2108+50.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
10	2107+00.00	RT	1	1	10.0	50.0	2.85	1.9%	1187.5	
10	2105+50.00	RT	1	1	10.0	50.0	2.85	1.6%	1225.0	
10	2104+00.00	RT	1	1	10.0	50.0	2.85	1.6%	1225.0	
10	2102+50.00	RT	1	1	10.0	50.0	2.85	1.6%	1225.0	
10	2101+00.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
10	2099+50.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
10	8531+25.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
10	8529+75.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
10	8528+25.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
10	8526+70.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
11	4200+80.00	Both	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	4201+80.00	Both	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	4202+80.00	Both	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2238+55.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2239+75.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2240+75.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2241+75.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2242+75.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2243+75.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	2244+75.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	54th Ditch
11	8517+40.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
11	8518+70.00	RT	1	1	10.0	50.0	2.85	0.7%	1337.5	
11	8520+25.00	RT	1	1	10.0	50.0	2.85	0.7%	1337.5	
11	8521+80.00	RT	1	1	10.0	50.0	2.85	0.7%	1337.5	
11	8523+35.00	RT	1	1	10.0	50.0	2.85	0.7%	1337.5	
11	8524+90.00	RT	1	1	10.0	50.0	2.85	0.7%	1337.5	
11	8517+40.00	LT	1	1	10.0	50.0	2.85	3.0%	1050.0	


100-14
10-17-17

SILT BASINS

Possible Standard: EW-403



Cross Section View




Longitudinal Profile View

* The functional height used in the volume equation is 95% of effective height. Effective height is 3 feet as shown in EW-403.
* Volume equation: (0.5*Length*(Width*Height+Width*(Height-Length*Avg%Slope))


Basin No.	Location		Bid Items		Stormwater Storage Volume Summary					Remarks
	Station	Side	Installation	Removal	Basin Width	Basin Length	Height	Avg. % Slope	Volume*	
			EACH	EACH	FT	FT	FT		CF	
11	8518+60.00	LT	1	1	10.0	50.0	2.85	1.0%	1300.0	
11	8520+15.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
11	8521+15.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
11	8522+15.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
11	8523+30.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	8511+40.00	LT	1	1	10.0	50.0	2.85	0.8%	1325.0	
12	8512+40.00	LT	1	1	10.0	50.0	2.85	0.8%	1325.0	
12	8513+50.00	LT	1	1	10.0	50.0	2.85	1.9%	1187.5	
12	8504+70.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	130' RT
12	8506+15.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	150' RT
12	8509+00.00	RT	1	1	10.0	50.0	2.85	1.4%	1250.0	
12	8510+00.00	RT	1	1	10.0	50.0	2.85	1.4%	1250.0	
12	38494+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38495+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38496+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38497+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38498+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38499+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38500+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38501+10.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38502+30.00	RT	1	1	10.0	50.0	2.85	4.0%	925.0	
12	38503+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38504+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38505+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38506+25.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38613+90.00	RT	1	1	10.0	50.0	2.85	3.0%	1050.0	
12	38615+50.00	RT	1	1	10.0	50.0	2.85	0.6%	1350.0	
12	38617+00.00	RT	1	1	10.0	50.0	2.85	0.6%	1350.0	
12	38619+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38620+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38621+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38622+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38623+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38624+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38625+00.00	RT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38493+80.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38493+90.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38495+90.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38496+90.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38498+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38499+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38500+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38501+00.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38502+25.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38503+25.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38504+40.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38505+40.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38506+40.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38507+50.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38508+50.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38509+50.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38613+00.00	LT	1	1	10.0	50.0	2.85	0.2%	1400.0	
12	38614+00.00	LT	1	1	10.0	50.0	2.85	0.2%	1400.0	
12	38615+00.00	LT	1	1	10.0	50.0	2.85	0.2%	1400.0	
12	38616+50.00	LT	1	1	10.0	50.0	2.85	0.2%	1400.0	
12	38617+50.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
12	38618+50.00	LT	1	1	10.0	50.0	2.85	0.5%	1362.5	
13	38807+35.00	LT	1	1	10.0	50.0	2.85	4.0%	925.0	
13	38808+35.00	LT	1	1	10.0	50.0	2.85	5.6%	730.0	
13	38808+60.00	RT	1	1	10.0	50.0	2.85	2.0%	1175.0	
13	38637+25.00	LT	1	1	10.0	50.0	2.85	2.3%	1137.5	
13	5144+75.00	LT	1	1	10.0	50.0	2.85	1.8%	1200.0	
13	5146+25.00	LT	1	1	10.0	50.0	2.85	1.8%	1200.0	
13	5148+50.00	LT	1	1	10.0	50.0	2.85	1.8%	1200.0	
13	5150+00.00	LT	1	1	10.0	50.0	2.85	1.8%	1200.0	

SILT FENCES FOR DITCH CHECKS

Possible Standard: EC-201



Cross Section View



Longitudinal Profile View


* The functional height used in the volume equation is 85% of effective height. Effective height is 1.58 feet as shown on EC-201.
* Volume equation: $[0.5*Spacing*(0.5*H^2*FS+DW*H+0.5*H^2*BS)]$

Basin No.	Type	Location		Bid Items			Stormwater Storage Volume Summary					Remarks
		Station	Side	Installation	Maintenance	Removal	Foreslope	Backslope	Ditch Width	Avg.% Slope	Volume*	
				LF	LF	LF	FS:1	BS:1	FT	Ditch Grade	CF	
1	1	8466+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	8471+45.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	1	8471+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	1	8472+25.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	1	8472+65.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	1	8473+05.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	1	8473+45.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	1	8473+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.8%	385.8	
1	4	8468+00.00	LT	71.0	8.0	36.0	3.5	3.0	8.2	2.8%	421.9	
1	4	8468+50.00	LT	72.0	8.0	36.0	3.5	3.0	12.1	2.8%	552.8	
1	4	8469+00.00	LT	81.0	9.0	41.0	3.5	3.0	15.0	2.8%	650.2	
1	4	8469+50.00	LT	86.0	9.0	43.0	3.5	3.0	23.0	2.8%	918.8	
1	4	8470+00.00	LT	88.0	9.0	44.0	3.5	3.0	26.5	2.8%	1036.3	
1	1	8476+96.00	LT	40.0	4.0	20.0	3.0	3.0	28.0	3.0%	1075.4	198' LT
1	1	8477+38.00	LT	37.0	4.0	19.0	3.0	3.0	25.0	3.0%	974.6	164' LT
1	1	32574+30.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	32574+65.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	32575+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	32575+35.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	32575+70.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	4	32576+05.00	RT	55.0	6.0	28.0	3.5	3.0	10.0	4.3%	337.6	
1	4	32576+40.00	RT	55.0	6.0	28.0	3.5	3.0	10.0	4.3%	337.6	
1	4	32576+75.00	RT	315.0	32.0	158.0	3.5	3.0	10.0	0.2%	3038.5	
1	4	32579+90.00	RT	286.0	29.0	143.0	3.5	3.0	10.0	0.2%	2749.1	
1	3	32585+20.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
1	1	32585+60.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
1	1	32586+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
1	1	1065+35.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	1065+70.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	1	1066+05.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	3	1066+60.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.3%	337.6	
1	3	1066+80.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.1%	337.6	
1	1	1067+35.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.1%	337.6	
1	1	1067+70.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.1%	337.6	
2	4	32590+30.00	RT	193.0	20.0	97.0	3.5	3.0	10.0	1.0%	1495.1	
2	1	32588+65.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	723.4	
2	1	32588+05.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	723.4	
2	1	32587+45.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	723.4	
2	4	32586+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	723.4	
2	4	32587+00.00	LT	72.0	8.0	36.0	3.5	3.0	10.0	1.9%	482.3	
2	4	32587+75.00	LT	98.0	10.0	49.0	3.5	3.0	10.0	1.9%	723.4	
2	4	32588+50.00	LT	98.0	10.0	49.0	3.5	3.0	10.0	1.9%	723.4	
2	5	32590+05.00	LT	184.0	19.0	92.0	3.5	3.0	10.0	1.0%	1495.1	
2	5	32590+40.00	LT	60.0	6.0	30.0	3.5	3.0	10.0	5.0%	337.6	
2	5	32590+65.00	LT	40.0	4.0	20.0	3.5	3.0	10.0	5.0%	337.6	
3	5	32591+35.00	RT	176.0	18.0	88.0	2.0	0.0	10.0	1.0%	1180.6	
3	5	32591+85.00	LT	124.0	13.0	62.0	2.0	0.0	10.0	1.0%	1180.6	
4	4	38569+50.00	LT	77.0	8.0	39.0	3.5	3.0	10.0	0.5%	3038.5	
5	1	38560+70.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.4%	3038.5	
5	1	38563+85.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.5%	964.6	
5	1	38564+85.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.5%	964.6	
5	1	38561+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38561+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38562+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38562+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38563+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38563+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38564+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38564+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
5	1	38565+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
6	5	38557+75.00	LT	97.0	10.0	49.0	3.5	3.0	10.0	1.0%	771.7	
6	1	38558+50.00	RT	13.0	2.0	7.0	3.5	3.0	0.0	0.5%	439.6	
7	5	38556+00.00	LT	150.0	15.0	75.0	3.5	0.0	10.0	0.5%	1078.1	
7	5	38557+00.00	LT	90.0	9.0	45.0	3.5	3.0	10.0	1.0%	723.4	
8	5	2023+25.00	LT	113.0	12.0	57.0	3.0	0.0	10.0	1.2%	806.8	
8	5	2024+25.00	LT	298.0	30.0	149.0	3.0	0.0	10.0	0.5%	2218.6	
8	5	2025+25.00	LT	93.0	10.0	47.0	3.0	0.0	10.0	1.0%	605.1	
9	1	2018+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.0%	1495.1	


100-18
10-16-18

SILT FENCES FOR DITCH CHECKS

Possible Standard: EC-201



Cross Section View




Longitudinal Profile View

* The functional height used in the volume equation is 85% of effective height. Effective height is 1.58 feet as shown on EC-201.
* Volume equation: $[0.5*Spacing*(0.5*H^2*FS+DW*H+0.5*H^2*BS)]$


Basin No.	Type	Location		Bid Items			Stormwater Storage Volume Summary					Remarks
		Station	Side	Installation	Maintenance	Removal	Foreslope	Backslope	Ditch Width	Avg.% Slope	Volume*	
				LF	LF	LF	FS:1	BS:1	FT	Ditch Grade	CF	
9	1	2019+55.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.4%	434.1	
9	1	2020+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.4%	434.1	
10	1	2113+75.00	RT	22.0	3.0	11.0	4.0	3.0	8.0	4.5%	298.5	
10	1	2113+53.00	RT	23.0	3.0	12.0	4.0	3.0	9.0	4.5%	322.0	
10	1	2113+30.00	RT	27.0	3.0	14.0	4.0	3.0	13.0	4.5%	416.0	
10	1	2113+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2112+70.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2112+40.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2112+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2111+80.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2111+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2111+20.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2110+90.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	5.6%	289.4	
10	1	2110+60.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.9%	723.4	
10	1	2109+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.9%	723.4	
10	1	2109+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.9%	723.4	
10	1	2108+35.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.9%	723.4	
10	1	2107+60.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.9%	723.4	
10	1	2106+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2106+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2105+35.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2104+60.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2103+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2103+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2102+35.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2101+60.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.6%	723.4	
10	1	2100+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	2100+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	2099+35.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	8531+80.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	8531+05.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	8530+30.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	8529+55.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
10	1	8528+80.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.0%	1495.1	
10	1	8527+25.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.6%	1495.1	
10	1	8525+70.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.6%	289.4	
11	1	4200+13.00	BOTH	22.0	3.0	11.0	3.0	3.0	10.0	0.5%	2967.4	54th Ditch
11	1	4203+28.00	BOTH	114.0	12.0	57.0	3.0	3.0	10.0	0.5%	2967.4	54th Ditch
11	1	2239+10.00	LT	22.0	3.0	11.0	3.0	3.0	10.0	0.5%	1224.7	54th Ditch
11	1	2242+25.00	LT	22.0	3.0	11.0	3.0	3.0	10.0	0.5%	2967.4	54th Ditch
11	1	8517+90.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	2.0%	723.4	
11	1	8518+20.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.7%	1495.1	
11	1	8519+75.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.7%	1495.1	
11	1	8521+30.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.7%	1495.1	
11	1	8522+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.7%	1495.1	
11	1	8524+40.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.7%	1495.1	
11	3	8517+90.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.0%	1495.1	
11	3	8518+10.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
11	1	8519+65.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
11	1	8522+80.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
12	1	8509+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	289.4	
12	1	8509+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
12	1	8510+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
12	1	8510+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
12	1	8511+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.6%	482.3	
12	3	8512+90.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.8%	1495.1	
12	1	8514+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.1%	482.3	
12	1	8514+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.1%	482.3	
12	1	8515+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.1%	482.3	
12	1	8515+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.1%	482.3	
12	1	8516+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.1%	482.3	
12	1	8516+50.00	LT	28.0	3.0	14.0	6.0	3.0	10.0	3.1%	538.7	
12	1	8508+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.4%	964.6	
12	1	8509+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.4%	964.6	
12	1	8510+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	1.4%	964.6	
12	1	38494+70.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	1688.0	
12	1	38497+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
12	1	38501+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	

SILT FENCES FOR DITCH CHECKS

Possible Standard: EC-201



Cross Section View



Longitudinal Profile View


* The functional height used in the volume equation is 85% of effective height. Effective height is 1.58 feet as shown on EC-201.
* Volume equation: [0.5*Spacing*(0.5*H^2*FS+DW*H+0.5*H^2*BS)]

Basin No.	Type	Location		Bid Items			Stormwater Storage Volume Summary					Remarks
		Station	Side	Installation	Maintenance	Removal	Foreslope	Backslope	Ditch Width	Avg.% Slope	Volume*	
				LF	LF	LF	FS:1	BS:1	FT	Ditch Grade	CF	
12	1	38502+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
12	1	38505+65.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	2749.1	
12	1	38508+75.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38509+10.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38509+45.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38509+80.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38510+15.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38510+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38510+85.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38511+20.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38511+55.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	4.4%	337.6	
12	1	38612+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
12	1	38612+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
12	1	38613+00.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
12	1	38613+50.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
12	1	38614+90.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.6%	1495.1	
12	1	38616+45.00	RT	23.0	3.0	12.0	3.5	3.0	10.0	0.6%	1495.1	
12	5	38618+00.00	RT	332.0	34.0	166.0	3.5	0.0	10.0	0.5%	2612.4	
12	5	38621+15.00	RT	336.0	34.0	168.0	3.5	0.0	10.0	0.5%	2612.4	
12	5	38624+30.00	RT	135.0	14.0	68.0	3.5	0.0	10.0	0.5%	2612.4	
12	1	38489+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.5%	964.6	
12	1	38489+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38490+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38490+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38491+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38491+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38492+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38492+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38493+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38494+30.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38497+45.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38500+60.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38503+75.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38506+90.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.7%	482.3	
12	1	38510+05.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
12	1	38510+45.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
12	1	38510+85.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
12	1	38511+25.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
12	1	38611+70.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
12	3	38612+10.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	4.0%	385.8	
12	3	38612+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.2%	3038.5	
12	1	38615+65.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.2%	3038.5	
12	1	38618+80.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
13	3	38626+00.00	RT	65.0	7.0	33.0	3.5	10.0	38.0	0.4%	9955.4	
13	1	38629+15.00	RT	43.0	5.0	22.0	3.5	3.0	30.0	0.4%	4615.2	
13	1	38620+05.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	482.3	
13	1	38623+20.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
13	1	38626+35.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
13	1	38629+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	0.5%	3038.5	
13	4	38636+25.00	LT	45.0	5.0	23.0	3.5	3.0	10.0	2.3%	723.4	
13	1	38637+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	2.3%	723.4	
13	4	38637+75.00	LT	94.0	10.0	47.0	3.5	3.0	10.0	2.3%	723.4	
13	4	5138+25.00	LT	64.0	7.0	32.0	3.5	3.0	10.0	3.0%	482.3	
13	4	5138+75.00	LT	71.0	8.0	36.0	3.5	3.0	10.0	3.0%	482.3	
13	4	5139+25.00	LT	71.0	8.0	36.0	3.5	3.0	10.0	3.0%	482.3	
13	4	5139+75.00	LT	71.0	8.0	36.0	3.5	3.0	10.0	3.0%	482.3	
13	4	5140+25.00	LT	71.0	8.0	36.0	3.5	3.0	10.0	3.0%	482.3	
13	1	5140+75.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
13	1	5141+25.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
13	1	5141+75.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
13	1	5142+25.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	3.0%	482.3	
13	4	5143+00.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	
13	4	5143+75.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	
13	4	5144+50.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	
13	4	5145+25.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	
13	4	5146+00.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	
13	4	5146+75.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	
13	4	5147+50.00	LT	96.0	10.0	48.0	3.5	3.0	10.0	1.8%	723.4	


100-18
10-16-18

SILT FENCES FOR DITCH CHECKS

Possible Standard: EC-201



Cross Section View



Longitudinal Profile View

* The functional height used in the volume equation is 85% of effective height. Effective height is 1.58 feet as shown on EC-201.
* Volume equation: [0.5*Spacing*(0.5*H^2*FS+DW*H+0.5*H^2*BS)]

Basin No.	Type	Location		Bid Items			Stormwater Storage Volume Summary					Remarks
		Station	Side	Installation	Maintenance	Removal	Foreslope	Backslope	Ditch Width	Avg.% Slope	Volume*	
				LF	LF	LF	FS:1	BS:1	FT	Ditch Grade	CF	
13	1	5148+25.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.8%	723.4	
13	1	5149+00.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.8%	723.4	
13	1	5149+75.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.8%	723.4	
13	1	5150+50.00	LT	23.0	3.0	12.0	3.5	3.0	10.0	1.8%	723.4	
13	1	18+75.00	LT	17.0	2.0	9.0	3.0	3.0	5.0	3.1%	303.1	
13	1	19+25.00	LT	17.0	2.0	9.0	3.0	3.0	5.0	3.1%	303.1	
13	1	19+75.00	LT	17.0	2.0	9.0	3.0	3.0	5.0	3.1%	303.1	
13	3	20+50.00	LT	17.0	2.0	9.0	3.0	3.0	5.0	2.4%	454.7	
13	1	38806+50.00	LT	22.0	3.0	11.0	3.0	3.0	5.0	4.0%	242.5	
13	1	38806+90.00	LT	22.0	3.0	11.0	3.0	3.0	5.0	4.0%	242.5	
13	1	38807+30.00	LT	22.0	3.0	11.0	3.0	3.0	5.0	4.0%	242.5	
					0.0	0.0						
					0.0	0.0						

PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE

Possible Standards: EC-204

Location			Length of Installation			Remarks
Begin Station	End Station	Side	9 inch Dia	12 inch Dia	20 inch Dia	
			LF	LF	LF	
1066+70.00		LT		40.0		I-80 WB Inlet Apron Protection
8470+96.00		LT		40.0		I-35 NB Inlet Apron Protection
8474+85.00		RT		40.0		I-35 NB Inlet Protection
8475+95.00		LT		40.0		I-35 NB Inlet Apron Protection
8504+37.00		RT		40.0		I-35 NB Inlet Apron Protection
8512+98.00		LT		40.0		I-35 NB Inlet Apron Protection
8518+00.00		LT		40.0		I-35 NB Inlet Apron Protection
8529+50.00		LT		40.0		I-35 NB Inlet Protection
38501+70.00		RT		40.0		Ramp A Inlet Apron Protection
32585+12.00		LT		40.0		Ramp B Inlet Apron Protection
32584+58.00		LT		40.0		Ramp B Inlet Apron Protection
32589+00.00		LT		40.0		Ramp B Inlet Apron Protection
38559+63.00		LT		20.0		Ramp G Inlet Apron Protection
38560+50.00		LT		20.0		Ramp G Inlet Apron Protection
38566+00.00		RT		40.0		Ramp G Inlet Apron Protection
38612+28.00		LT		40.0		Ramp G Inlet Apron Protection
38625+80.00		RT		40.0		Ramp G Inlet Apron Protection
38805+80.00		LT		40.0		NE 29th St. Inlet Apron Protection
38807+87.00		LT		40.0		NE 29th St. Inlet Apron Protection
20+72.00		LT		40.0		Chichaqua Valley Trail Inlet Apron Protection

100-22
04-21-15

ROLLED EROSION CONTROL

Refer to EC-101, EC-103, and EC-104.

Location				L	W	Turf Reinforcement Mat (TRM) (EC-104)				Slope Protection (EC-103)	Special Ditch Control (EC-101)	Remarks
Road Identification	Begin Station	End Station	Side			Type 1	Type 2	Type 3	Type 4			
				FT	FT	Squares	Squares	Squares	Squares	Squares	Squares	
I-80 WB Survey	1065+00.00	1068+00.00	LT	300	16						48	
I-35 NB	8465+42.00	8466+22.00	RT	80	16						13	
I-35 NB	8470+65.00	8474+22.45	RT	357	16						57	
I-35 NB	8504+51.37	8505+14.43	RT	63	58					37		Bridge Abutment
I-35 NB	8504+52.56	8505+15.53	LT	63	41					26		Bridge Abutment
Ramp A	38510+20.00	38511+66.22	LT	146	16						23	
Ramp G	38611+66.00	38611+80.00	LT	14	16						2	
Ramp G	38508+50.00	38511+66.22	RT	316	16						51	
Ramp B	32574+22.46	32576+50.00	RT	228	16						36	
Ramp B	32590+00.00	32590+63.80	RT	64	45					29		Bridge Abutment
Ramp B	32590+00.00	32590+63.69	LT	64	37					24		Bridge Abutment
Ramp B	32592+18.20	32592+57.74	RT	40	42					17		Bridge Abutment
Ramp B	32591+85.00	32592+56.00	LT	71	27					19		Bridge Abutment
Ramp G	38559+03.17	38559+61.53	LT	58	47							
Ramp G	38558+95.23	38559+35.96	RT	41	11							
Ramp G	38560+23.16	38560+79.21	LT	56	43							
Ramp G	38560+31.37	38560+71.28	RT	40	15							
Ramp G	38631+07.13	38631+60.67	RT	54	39					21		Bridge Abutment
Ramp G	38631+10.29	38631+64.24	LT	54	47					25		Bridge Abutment
Ramp G	38632+92.87	38633+42.10	RT	49	52					25		Bridge Abutment
Ramp G	38632+96.78	38633+47.04	LT	50	51					26		Bridge Abutment

100-17
04-20-10

TABULATION OF SILT FENCES

Refer to EC-201

Location			Length	Remarks
Begin Station	End Station	Side	LF	
32575+89.00	32587+20.00	RT	1139.0	Ramp B ROW Line
32588+50.00	32590+37.00	RT	179.0	Ramp B ROW Line
32590+36.00	32590+90.00	BOTH	138.0	Ramp B Bridge Area
32592+10.00	32592+75.00	BOTH	240.0	Ramp B Bridge Area
38556+84.00	38559+15.00	LT	234.0	Ramp G Toe of Slope
38556+84.00	38559+15.00	LT	234.0	Ramp G On Slope
38560+20.00	38560+65.00	BOTH	170.0	Ramp G Bridge Area
38559+40.00	38559+63.00	BOTH	130.0	Ramp G Bridge Area
38552+86.00	38559+54.00	LT	590.0	Ramp G ROW Line
38560+69.00	38569+90.00	LT	944.0	Ramp G Toe of Slope
38560+89.00	38569+96.00	LT	927.0	Ramp G On Slope
38633+32.00	38637+77.87	LT	444.0	Ramp G Top of Slope
38633+52.00	38637+77.87	LT	424.0	Ramp G On Slope
38633+52.00	38637+77.87	LT	424.0	Ramp G Top of Slope
38633+12.00	38636+21.00	LT	306.0	Ramp G Entrance 29th
2018+02.00	2024+18.00	LT	642.0	I-235 ROW Line
2024+28.00	2025+35.00	LT	123.0	I-235 Near Outlet
5138+25.00	5140+43.00	LT	220.0	I-80 ROW Line
5142+25.00	5147+68.00	LT	560.0	I-80 ROW Line
5137+78.00	5143+17.00	LT	550.0	I-80 Top of Slope
5137+78.00	5150+75.00	LT	1315.0	I-80 On Slope
5137+78.00	5150+75.00	LT	1315.0	I-80 Toe of Slope

100-23
04-17-18

ROCK EROSION CONTROL


Refer to EC-301 and Detail 570-8


Location				L	W	Rock Erosion Control (REC)					Material Bid Quantities			Remarks
Road Identification	Begin Station	End Station	Side			Type 1	Type 2	Type 3	Type 4	Type 5	Eng. Fabric	Class E Revetment	Erosion Stone	
			Lt./Rt.	FT	FT	Rock Ditch Check	Rock Ditch	Rock Flume	Rock Splash Basin	Rock Slope Protection	SY	TON	TON	
I-80 WB Survey	1066+25.00	1066+50.00	LT	16	26.4			X			66.0	44.4		Temporary Flume
Ramp G	38611+80.00	38612+00.00	LT	20	32.6			X			96.0	68.5		
Ramp B	32590+45.00	32590+90.00	RT	10	44			X			70.8	44.2		

100-32
10-16-18

ROCK CHECK DAM

Possible Standard: EC-302






* The functional height used in the volume equation is 90% of effective height. Effective height is 2 feet as shown in EC-302.

* Volume equation: $[0.5*Spacing*(0.5*H^2*FS+DW*H+0.5*H^2*BS)]$

Basin No.	Location			Bid Items			Stormwater Storage Volume Summary					Remarks
	Station	Side	Offset	Installation	Maintenance	Removal	Foreslope	Backslope	Ditch Width	Avg. % Slope	Volume*	
			FT	LF	Each	Each	FS:1	BS:1	FT		CF	
1	8466+55.00	RT	96.9	28.0	3	1	3.5	3.0	10.0	1.9%	1426.5	
1	8467+55.00	RT	89.5	28.0	3	1	3.5	3.0	10.0	1.9%	1426.5	
1	8468+55.00	RT	84.4	28.0	3	1	3.5	3.0	10.0	1.9%	1426.5	
1	8469+55.00	RT	82.8	28.0	3	1	3.5	3.0	10.0	1.9%	1426.5	
1	8471+25.00	LT	128.0	46.0	3	1	3.5	3.0	29.0	0.5%	12546.0	
1	8476+15.00	LT	242.5	23.0	3	1	3.0	2.0	10.0	3.6%	652.5	

TEMPORARY SEDIMENT CONTROL BASIN

Possible Standard: EC-601



* The functional height used in the volume equation is 95% of effective height. Effective height is 2.5 feet as shown in EC-601.
* Volume equation: $[(1/4(FS*H^2))+(DW*H)+(1/4*(BS*H^2))]*(H/Avg\%Slope)$

Basin No.	Location		Bid Items			Stormwater Storage Volume Summary					Remarks
	Station	Side	Installation	Maintenance	Removal	Foreslope	Backslope	Ditch Width	Average % Slope	Volume*	
			Each	Each	Each	FS:1	BS:1	FT		CF	
1	8470+75.00	RT	1	3	1	3.5	3.0	10.00	3.8%	1315.1	
1	8470+85.00	LT	1	3	1	3.5	3.0	32.00	2.8%	4000.7	
5	38566+15.00	RT	1	3	1	3.5	3.0	10.00	0.3%	19989.0	
5	38565+85.00	RT	1	3	1	3.5	3.0	10.00	2.6%	1922.0	

STORMWATER DRAINAGE BASIN AND STORAGE

Refer to EC Standards and 570s Details.

Drainage Basin Location						Summary of Stormwater Storage							Remarks
Basin No.	Station to Station		Side	Discharge Point		Total Disturbed Area	Disturbed Area with Storage Provided	Disturbed Area without Storage Provided	Best Management Practice	Total Storage Volume Provided	Total Storage Volume Required	Storage Volume Met?	
				Station	Side	Acres	Acres	Acres		CF	CF	Yes/No	
1	1057+35.00	32587+75.00	BOTH	1066+00.00	RT	16.4	16.4	0.0	Silt Fence for Ditch Check (EC-201)	10297.4	59040.0	Yes	
									Silt Basin (EW-403)	16575.0			
									Rock Check Dam (EC-302)	18904.5			
									Temporary Sediment Control Basin (EC-601)	5315.8			
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	10042.7			
2	32584+76.00	32592+18.00	BOTH	32590+80.00	RT	5.0	5.0	0.0	Silt Fence for Ditch Check (EC-201)	2170.3	18000.0	Yes	
									Silt Basin (EW-403)	9568.8			
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	6318.1			
3	32591+05.00	32593+55.00	BOTH	32591+30.00	RT	1.0	1.0	0.0	Silt Fence for Shallow Ditch or No Ditch (EC-201)	2361.2	3600.0	Yes	
									Silt Basin (EW-403)	2600.0			
4	38566+15.00	38570+50.00	BOTH	38569+55.00	LT	1.7	1.7	0.0	Silt Basin (EW-403)	4087.5	6120.0	Yes	
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	3038.5			
5	38560+00.00	38570+00.00	BOTH	38560+50.00	LT	5.4	5.4	0.0	Silt Fence for Ditch Check (EC-201)	9308.3	19440.0	Yes	
									Silt Basin (EW-403)	3512.5			
									Temporary Sediment Control Basin (EC-601)	21911.0			
6	38557+72.00	38560+00.00	BOTH	38559+80.00	LT	0.8	0.8	0.0	Silt Fence for Ditch Check (EC-201)	439.6	2880.0	Yes	
									Silt Basin (EW-403)	2156.6			
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	771.7			
7	38554+62.00	38557+72.00	LT	38556+65.00	LT	1.1	1.1	0.0	Silt Basin (EW-403)	2662.5	3960.0	Yes	
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	1801.6			
8	2020+50.00	2026+00.00	LT	2024+25.00	LT	1.7	1.7	0.0	Silt Basin (EW-403)	6550.0	6120.0	Yes	
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	3630.5			
9	2017+96.00	2020+50.00	LT	2017+95.00	LT	0.6	0.6	0.0	Silt Fence for Ditch Check (EC-201)	2363.3	2160.0	Yes	
									Silt Basin (EW-403)	1300.0			
10	2092+30.00	2114+60.00	RT	2113+10.00	RT	6.3	6.3	0.0	Silt Fence for Ditch Check (EC-201)	21100.0	22680.0	Yes	
									Silt Basin (EW-403)	14287.5			
11	8517+00.00	8530+05.00	BOTH	8519+50.00	RT	6.4	6.4	0.0	Silt Fence for Ditch Check (EC-201)	28936.6	23040.0	Yes	
									Silt Basin (EW-403)	29287.5			
12	38487+76.00	38625+43.45	BOTH	38616+40.00	RT	24.3	24.3	0.0	Silt Fence for Ditch Check (EC-201)	49732.9	87480.0	Yes	
									Silt Basin (EW-403)	69750.0			
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	7837.1			
13	1119+65.00	1157+55.00	BOTH	1157+55.00	LT	10.5	10.5	0.0	Silt Fence for Ditch Check (EC-201)	31806.4	37800.0	Yes	
									Silt Basin (EW-403)	8767.5			
									Silt Fence for Shallow Ditch or No Ditch (EC-201)	8922.5			

POLLUTION PREVENTION PLAN

This project is regulated by the requirements of the Iowa Department of Natural Resources (DNR) National Pollutant Discharge Elimination System (NPDES) General Permit No. 2 OR an Iowa Department of Natural Resources (DNR) National Pollutant Discharge Elimination System (NPDES) individual storm water permit. The Contractor shall carry out the terms and conditions of this permit and the Pollution Prevention Plan (PPP).

This Base PPP includes information on Roles and Responsibilities, Project Site Description, Controls, Maintenance Procedures, Inspection Requirements, Non-Storm Water Controls, Potential Sources of Off Right-of-Way Pollution, and Definitions. This plan references other documents rather than repeating the information contained in the documents. A copy of this Base Pollution Prevention Plan, amended as needed during construction, will be readily available for review.

All contractors shall conduct their operations in a manner that controls pollutants, minimizes erosion, and prevents sediments from entering waters of the state and leaving the highway right-of-way. The Contractor shall be responsible for compliance and implementation of the PPP for their entire contract. This responsibility shall be further shared with subcontractors whose work is a source of potential pollution as defined in this PPP.

I. ROLES AND RESPONSIBILITES

A. Designer:
1. Prepares Base PPP included in the project plan.
2. Prepares Notice of Intent (NOI) submitted to Iowa DNR.
3. Is signature authority on the Base PPP. If consultant designed, signature from Contracting Authority is also required.

B. Contractor:
1. Signs a co-permittee certification statement adhering to the requirements of the NPDES permit and this PPP. All co-permittees are legally required under the Clean Water Act and the Iowa Administrative Code to ensure compliance with the terms and conditions of this PPP.
2. Designates a Water Pollution Control Manager (WPCM), who has the duties and responsibilities as defined in Section 2602 of the Standard Specifications.
3. Submits an Erosion Control Implementation Plan (ECIP) and ECIP updates according to Section 2602 of the Standard Specifications.
4. Installs and maintains appropriate controls. This work may be subcontracted as documented through Subcontractor Request Forms (Form 830231).
5. Supervises and implements good housekeeping practices according to Paragraph III, C, 2.
6. Conducts joint required inspections of the site with inspection staff. When Contractor is not mobilized on site, Contractor may delegate this responsibility to a trained or certified subcontractor. Contracting Authority also may waive joint inspection requirement during winter shutdown. In both circumstances, WPCM (or trained or certified delegate from the Contractor) is still responsible to review and sign inspection reports.
7. Complies with training and certification requirements of Section 2602 of the Standard Specifications.
8. Submits amended PPP site map according to Section 2602 of the Standard Specifications.

C. Subcontractors:
1. Sign a co-permittee certification statement adhering to the requirements of the NPDES permit and this PPP if: responsible for sediment or erosion controls; involved in land disturbing activities; or perorming work that is a source of potential pollution as defined in this PPP. Subcontracted work items are identified in Subcontractor Request Forms (Form 830231). All co-permittees are legally required under the Clean Water Act and the Iowa Administrative Code to ensure compliance with the terms and conditions of this PPP.
2. Implement good housekeeping practices according to Paragraph III, C, 2.

D. RCE/Project Engineer:
1. Is Project Storm Water Manager.
2. On projects where DOT is the Contracting Authority, is current with erosion control training or certification.
3. Takes actions necessary to ensure compliance with storm water requirements including, where appropriate, issuing stop work orders, and directing additional inspections at construction project sites that are experiencing problems with achieving permit compliance.
4. Orders the taking of measures to cease, correct, prevent, or minimize the consequences of non-compliance with the storm water requirements of the Applicable Permit.
5. Supervises all work necessary to meet storm water requirements at the Project, including work performed by contractors and subcontractors.
6. Requires employees, contractors, and subcontractors to take appropriate responsive action to comply with storm water requirements, including requiring any such person to cease or correct a violation of storm water requirements, and to order or recommend such other actions as necessary to meet storm water requirements.
7. Is familiar with the Project PPP and storm water site map.
8. On projects where DOT is Contracting Authority, is responsible for periodically monitoring inspection reports to determine whether deficiencies identified in inspection reports were adequately and timely addressed, and if not, has the authority and responsibility to direct immediate actions to correct the deficiencies.
9. Is the point of contact for the Project for regulatory officials, Inspector, contractors, and subcontractors regarding storm water requirements.
10. Is signature authority on Notice of Discontinuation.
11. Maintains an up-to-date record of contractors, subcontractors, and subcontracted work items through Subcontractor Request Forms (Form 830231).
12. Makes information to determine permit compliance available to the DNR upon their request.

E. Inspector:
1. Updates PPP through fieldbook entries and storm water site inspection reports if there is a change in design, construction, operation, or maintenance which has a significant effect on the discharge of pollutants from the project.
2. Makes information to determine permit compliance available to the DNR upon their request.
3. Conducts joint required inspections of the site with the contractor/subcontractor.
4. Completes an inspection report after each inspection.
5. Is signature authority on storm water inspection reports.

II. PROJECT SITE DESCRIPTION

A. This Pollution Prevention Plan (PPP) is for the construction of a *Describe Type of Facility*.

B. This PPP covers approximately *Provide # Of Acres* acres with an estimated *Provide # of Acres* acres being disturbed. The portion of the PPP covered by this contract has *Provide # of Acres* acres disturbed.

C. The PPP is located in an area of *Provide # of Types Of Soil Association* soil association (*Provide Soil Association Type or* *Types*). The estimated weighted average runoff coefficient number for this PPP after completion will be *Provide runoff coefficient Number*.

D. Storm Water Site Map is located in the R sheets. Proposed slopes are shown in cross sections, details, or standard road plans. Supplemental information is located in the Tabulations in the C or CE sheets.

E. The base storm water site map is amended by contract modifications and progress payments (fieldbook entries) of completed erosion control work. Also, due to project phasing, erosion and sediment controls shown on project plans may not be installed until needed, based on site conditions. For example, silt fence ditch checks will typically not be installed until the ditch has been

110-12
10-20-20

POLLUTION PREVENTION PLAN

installed. Installed locations may also be modified from tabulation locations by field staff. Installed locations will be documented by fieldbook entries and amended PPP site map.

F. Runoff from this work will flow into *List Outlets for Runoff*.

III. CONTROLS

A. The Contractor’s ECIP specified in Article 2602.03 of the Standard Specifications for accomplishment of storm water controls should clearly describe the intended sequence of major activities, and for each activity define the control measure and the timing during the construction process that the measure will be implemented.

B. Preserve vegetation in areas not needed for construction.

C. Sections 2601 and 2602 of the Standard Specifications define requirements to implement erosion and sediment control measures. Actual quantities used and installed locations may vary from the Base PPP and amendment of the plan will be documented via fieldbook entries, amended PPP site map, or by contract modification. Additional erosion and sediment control items may be required as determined by the inspector and/or contractor during storm water site inspections. If the work involved is not applicable to any contract items, the work will be paid for according to Article 1109.03 paragraph B of the Standard Specifications.

1. EROSION AND SEDIMENT CONTROLS

a. Stabilization Practices

1) Site plans will ensure that existing vegetation or natural buffers are preserved where attainable and disturbed portions of the site will be stabilized.

2) Initialize stabilization of disturbed areas immediately after clearing, grading, excavating, or other earth disturbing activities have:
a) Permanently ceased on any portion of the site, or
b) Temporarily ceased on any portion of the site and will not resume for a period exceeding 14 calendar days.

3) Staged permanent and/or temporary stabilizing seeding and mulching shall be completed as the disturbed areas are completed. Incomplete areas shall be stabilized according to paragraph III, C, 1, a, 2, b above.

4) Permanent and Temporary Stabilization practices to be used for this project are located in the storm water site map, Estimated Project Quantities (100-0A, 100-1A, or 100-1C), and Estimate Reference Information (100-4A) located in the C or R sheets. Typical drawings detailing construction of the practices to be used on this project are referenced in the Standard Road Plans Tabulation (105-4) in the C or R sheets.

5) Preservation of existing vegetation within right-of-way or easements will act as vegetative buffer strips.

6) Preservation of topsoil: Bid items to be used for this project are located in the Estimated Project Quantities (100-0A, 100-1A, or 100-1C) and Estimate Reference Information (100-4A) located in the C or R sheets. Additional information may be found in the Tabulations in the C or T Tabulation sheets, or is referenced in Section 2105 of the Standard Specifications.

b. Structural Practices

1) Structural practices will be implemented to divert flows from exposed soils and detain or otherwise limit runoff and the discharge of pollutants from exposed areas of the site. Additionally, structural practices may include: silt basins that provide 3600 cubic feet of storage per acre drained or equivalent sediment controls, outlet structures that withdraw water from surface when discharging basins, and controls to direct storm water to vegetated areas.

2) Structural practices to be used for this project are located in the storm water site map, Estimated Project Quantities (100-0A, 100-1A, or 100-1C), and Estimate Reference Information (100-4A) located in the C or R sheets, as well as all other item specific Tabulations. Typical drawings detailing construction of the devices to be used on this project can be found on the B or R sheets or are referenced in the Standard Road Plans Tabulation (105-4) located in the C or R sheets.

c. Storm Water Management

Measures shall be installed during the construction process to control pollutants in storm water discharges that will occur after construction operations have been completed. This may include velocity dissipation devices at discharge locations and along length of outfall channel as necessary to provide a non-erosion velocity flow from structure to water course. If included with this project, these items are located in the storm water site map and Estimated Project Quantities (100-0A, 100-1A, or 100-1C) and Estimate Reference Information (100-4A) located in the C or R sheets, as well as all other item specific Tabulations. Typical drawings detailing construction of the practices to be used on this project are referenced in the Standard Road Plans Tabulation. The installation of these devices may be subject to Section 404 of the Clean Water Act.

2. OTHER CONTROLS

Contractor disposal of unused construction materials and construction material wastes shall comply with applicable state and local waste disposal, sanitary sewer, or septic system regulations. In the event of a conflict with other governmental laws, rules and regulations, the more restrictive laws, rules or regulations shall apply.

a. Vehicle Entrances and Exits - Construct and maintain entrances and exits to prevent tracking of sediments onto roadways.

b. Material Delivery, Storage and Use - Implement practices to prevent discharge of construction materials during delivery, storage, and use.

c. Stockpile Management - Install controls to reduce or eliminate pollution of storm water from stockpiles of soil and paving.

d. Waste Disposal - Do not discharge any materials, including building materials, into waters of the state, except as authorized by a Section 404 permit.

e. Spill Prevention and Control - Implement chemical spill and leak prevention and response procedures to contain and clean up spills and prevent material discharges to the storm drain system and waters of the state.

f. Concrete Residuals and Washout Wastes - Waste shall not be discharged to a surface water and is not allowed to adversely affect a water of the state. Designate temporary concrete washout facilities for rinsing out concrete trucks. Provide directions to truck drivers where designated washout facilities are located. Designated washout areas should be located at least 50 feet away from storm drains, streams or other water bodies. Care should be taken to ensure these facilities do not overflow during storm events.

g. Concrete Grooving/Grinding Slurry – Do not discharge slurry to a waterbody or storm drain. Slurry may be applied on foreslopes or removed from the project.

h. Vehicle and Equipment Storage and Maintenance Areas - Perform on site fueling and maintenance in accordance with all environment laws such as proper storage of onsite fuels and proper disposal of used engine oil or other fluids on site. Employ washing practices that prevent contamination of surface and ground water from wash water. Wash waters must be treated in a sediment basin or alternative control that provides equivalent or better treatment prior to discharge.

i. Litter Management - Ensure employees properly dispose of litter. Minimize exposure of trash if exposure to precipitation or storm water would result in a discharge of pollutants.

j. Dewatering – Properly treat water to remove suspended sediment before it re-enters a waterbody or discharges off-site. Measures are also to be taken to prevent scour erosion at dewatering discharge point.

3. APPROVED STATE OR LOCAL PLANS

During the course of this construction, it is possible that situations will arise where unknown materials will be encountered. When such situations are encountered, they will be handled according to all federal, state, and local regulations in effect at the time.

POLLUTION PREVENTION PLAN

IV. MAINTENANCE PROCEDURES

The Contractor is required to maintain all temporary erosion and sediment control measures in proper working order, including cleaning, repairing, or replacing them throughout the contract period. This shall begin when the features have lost 50% of their capacity.

V. INSPECTION REQUIREMENTS

A. Inspections shall be made jointly by the Contractor and the Contracting Authority's inspector at least once every seven calendar days. Storm water site inspections will include:
   1. Date of the inspection.
   2. Summary of the scope of the inspection.
   3. Name and qualifications of the personnel making the inspection.
   5. Review of erosion and sediment control measures within disturbed areas for the effectiveness in preventing impacts to receiving waters.
   6. Major observations related to the implementation of the PPP.
   7. Identification of corrective actions required to maintain or modify erosion and sediment control measures.

B. Include storm water site inspection reports in the Amended PPP. Incorporate any additional erosion and sediment control measures determined as a result of the inspection. Immediately begin corrective actions on all deficiencies found within 3 calendar days of the inspection and complete within 7 calendar days following the inspection. If it is determined that making the corrections less than 72 hours after the inspection is impracticable, it should be documented why it is impracticable and indicate an estimated date by which the corrections will be made.

VI. NON-STORM WATER DISCHARGES

This includes subsurface drains (i.e. longitudinal and standard subdrains) and slope drains. The velocity of the discharge from these features may be controlled by the use of headwalls or blocks, Class A stone, erosion stone or other appropriate materials. This also includes uncontaminated groundwater from dewatering operations, which will be controlled as discussed in Section III of the PPP.

VII. POTENTIAL SOURCES OF OFF RIGHT-OF-WAY (ROW) POLLUTION

Silts, sediment, and other forms of pollution may be transported onto highway right-of-way (ROW) as a result of a storm event. Potential sources of pollution located outside highway ROW are beyond the control of this PPP. Pollution within highway ROW will be conveyed and controlled per this PPP.

VIII. DEFINITIONS

A. Base PPP - Initial Pollution Prevention Plan.
B. Amended PPP - Base PPP amended during construction. May include Plan Revisions or Contract Modifications for new items, storm water site inspection reports, fieldbook entries made by the inspector, amended PPP site map by the Contractor, ECIP, NOI, co-permittee certifications, and Subcontractor Request Forms. Items amending the PPP are stored electronically and are readily available upon request.
C. Fieldbook Entries – This contains the inspector’s daily diary and bid item postings.
D. Controls - Methods, practices, or measures to minimize or prevent erosion, control sedimentation, control storm water, or minimize contaminants from other types of waste or materials. Also called Best Management Practices (BMPs).
E. Signature Authority - Representative authorized to sign various storm water documents.

CERTIFICATION STATEMENT

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.


_____
Signature

_____
Printed or Typed Name

_____
Signature

_____

LINE STYLE LEGEND OF EROSION CONTROL SHEETS



Silt Fence
Perimeter and Slope Sediment Control Device (9")
Perimeter and Slope Sediment Control Device (12")
Perimeter and Slope Sediment Control Device (20")
Open-Throat Curb Intake Sediment Filter
Concentrated Flow
Sheet Flow

CELL LEGEND OF EROSION CONTROL SHEETS




Temporary Sediment Control basin
Erosion Control for Circular Intake or Manhole Well
Erosion Control for Rectangular Intake or Manhole Well
Grate Intake Sediment Filter Bag
Silt Basin
Silt Fence Tail
Stormwater Drainage Basin Discharge Point

PLAN VIEW COLOR LEGEND OF EROSION CONTROL SHEETS

LINEWORK	Design Color No.	
Green	(2)	Existing Topographic Features and Labels
Blue	(1)	Proposed Alignment, Stationing, Tic Marks, and Alignment Annotation
Magenta	(5)	Existing Utilities
Black	(0)	Permanent Erosion Control Features
Blaze Orange	(222)	Temporary Erosion Control Features

SHADING	Design Color No.		Transparency
Citron	(234)	Mulching, All Types	50%
Light Brown	(238)	Special Ditch Control, Wood Excelsior Mat	0%

PATTERN LEGEND OF EROSION CONTROL SHEETS



Seeding and Fertilizing
Seeding and Fertilizing (Rural)
Seeding and Fertilizing (Urban)
Native Grass Seeding
Salt Tolerant Seeding
Wetland Grass Seeding
Wildflower Seeding
Sodding
Turf Reinforcement Mat Type 1
Turf Reinforcement Mat Type 2
Turf Reinforcement Mat Type 3
Turf Reinforcement Mat Type 4
Slope Protection, Wood Excelsior Mat
Transition Mat
Rock Features, Permanent
Rock Features, Temporary

EROSION CONTROL LEGEND AND SYMBOL INFORMATION SHEET

(COVERS SHEET SERIES R)

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.1

9:12:36 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194lgd.sht

BASIN 1

BASIN 1

BASIN 1

I-80 (SUR080)

NB I-35 (IML035N)

RAMP B (235B)

NE 22ND ST

1060

1065

1070

8465

8470

8475

8480

32575

32580

32585

38580

38575

0 FEET 100

DRAINAGE BASINS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.2

I-235 (ML235)

RAMP G (235G)

RAMP B (235B)

NE 46TH AVE

NE 22ND ST

BASIN 2

BASIN 3

BASIN 4

BASIN 5

BASIN 6

BASIN 7

BASIN 8

BASIN 9

2045

32590

2040

32595

2035

38575

38570

38565

2030

38560

2025

38555

2020

2015

0 FEET 100

DRAINAGE BASINS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.3

DRAINAGE BASINS

I-235 (ML235)

NB I-35 (ML035N)

ML035N

RAMP A (235A)

RAMP G (235G)

NE 54TH AVE

BASIN 12

BASIN 11

BASIN 10


2065 2070 2075 2080 2085 2090 2095

8500 8505 8510 8515 8520 8525

38600 38605 38500 38505 38495 38490 38485

0 100 FEET

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.4



0 100 FEET

DRAINAGE BASINS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.5

NE 54TH AVE

38500

38505

38510

38610

38615

38620

38625

38630

38605

38600

BASIN 12

BASIN 13

RAMP A (235A)

RAMP G (235G)

RAMP G (235G)

I-80 (SUR080)

1105

1110

1115

1120


1125

1130

0 100 FEET

DRAINAGE BASINS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.6



DRAINAGE BASINS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.7

SAYLOR TWP.
T-79-N R-24W
SEC. 13

DELAWARE TWP.
T-79-N R-23W
SEC. 18

SAYLOR TWP.
T-79-N R-24W
SEC. 13

SIGN

SIGN

SIGN

SIGN BRIDGE

FUTURE WB I-80

WESTBOUND I-80

SUR080 B

FUTURE EB I-80

EASTBOUND I-80

SIGN

SIGN

SIGN

SIGN

SIGN

3.5:1

3:1

6:1

3.5:1

3:1

4%

3:1

3.5:1

6:1

NB I-35 (ML035N)

8465

8475

Billboard

SAYLOR TWP.
T-79-N R-24W
SEC. 13

0 FEET 50

DELAWARE TWP.
T-79-N R-23W
SEC. 18

I-35 NB & RAMP B EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.8

9:13:47 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht

I-35 NB & RAMP B EROSION CONTROL

0 FEET 50

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.9

9:13:58 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht

FUTURE WB I-80 to SB I-235

EB I-80 to SB I-235 RAMP B (235B)

WB I-80 to SB I-235
RAMP G (235G)

NORTHBOUND I-235

SOUTHBOUND I-235

Open Storage

Open Storage

Gate

SIGN


SIGN

0 FEET 50

RAMP B & G
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.10


9:14:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



RAMP G
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.11


9:14:19 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



I-235
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.12


9:14:29 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



I-35 NB
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.13

9:14:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



I-35 NB & RAMP A EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.14

9:14:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht

FUTURE ROW/CA LINE

385OS

385SS

385IO

386OS

WB I-80 to NB I-35
RAMP A (235A)

FUTURE WB I-80 to SB I-235

F03


SIGN

0 FEET 50

RAMP A & G
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.15

9:14:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



RAMP G
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.16

9:15:07 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht

NE 29TH STREET

38630

38635

1130

1135

1140

F03

WB I-80 to SB I-235
RAMP G (235G)

SIGNAL BRIDGE

WESTBOUND I-80

SIGNAL BRIDGE

EASTBOUND I-80

SIGN

NGVS

FO2


T1

0 FEET 50

RAMP G & I-80
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.17


9:15:16 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



I-80
EROSION CONTROL

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER RR.18

9:15:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194RR02.sht



Refer to detail project plans for mainline and ramp alignment and grade data.


Construct ramp exit pavement the same thickness as mainline pavement.

Ramp exit pavement shown by shaded area is 1097 square yards.

This design is based on 60 mph design speed at e max = 6%.

(1) For header construction details at the beginning of taper see Typical 7101.

(2) Construct subbase for ramp exit pavement the same thickness as mainline subbase.



SECTION A-A

Ⓒ


TABLE OF OFFSETS AND DROPS FOR 16' RAMP TAPER																		
DISTANCE FROM POINT Ⓒ ALONG LINE 'A' (Ft.)		400	375	350	325	300	280	250	225	200	175	150	125	100	75	50	25	0
From Line 'A' To Line 'B'	OFFSET (Ft.)						3.06	5.05	6.72	8.39	10.05	11.72	13.39	15.05	16.72	18.62	21.00	23.88
	SLOPE (%)						0.09	0.05	-0.20	← Constant -1.0% Slope →								
	DROP (Ft.)						0.03	0.01	-0.03	-0.08	-0.10	-0.12	-0.13	-0.15	-0.17	-0.18	-0.21	-0.24
From Line 'B' To Line 'C'	OFFSET (Ft.)						← Constant 16' Offset →											
	SLOPE (%)						← Constant 2.0% Slope →											
	DROP (Ft.)						0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32
From Line 'A' To Line 'C'	OFFSET (Ft.)	12.00	12.76	14.42	16.09	17.76												
	SLOPE (%)	← Constant 2.0% Slope →																
	DROP (Ft.)	0.24	0.26	0.29	0.32	0.35	0.35	0.33	0.29	0.24	0.22	0.20	0.19	.017	0.15	0.14	0.11	0.08

Ⓜ

ML035NB
RAMP B - EXIT

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.1

9:15:45 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



16' EXIT RAMP

③ 'CD' Joints at 20' spacing.

④ 'BT-2' joint for existing pavement
or 'KT-2' for new pavement .

⑤ 'C' Joint.

⑥ 'B' Joint. 2' minimum. 4' maximum.


⑦ 10' minimum or equal to mainline shoulder width.

⑧ 'B' or 'C' Joint. 2' minimum. 4' maximum.

ML035NB
RAMP B - EXIT


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.2

9:16:02 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



Pt. 'F' to Pt. 'G'
△ = 6°50'41.78"
D = 1°38'13"
T = 209.32'
L = 418.13'
E = 6.25'
R = 3500.00'

PLAN



PROFILE

Refer to detail project plans for mainline and ramp alignment and grade data.


Construct ramp exit pavement the same thickness as mainline pavement.

Ramp exit pavement shown by shaded area is 1515 square yards.

This design is based on 60 mph design speed at e max = 6%.

(1) For header construction details at the end of taper see Typical 7101.

(2) Construct subbase for ramp entrance pavement the same thickness as mainline subbase.



SECTION A-A

H — E


TABLE OF OFFSETS AND DROPS FOR 16' RAMP TAPER																			
Dist. From Pt. Ⓔ Along ML035NB ℄ (Ft.)		420	400	375	350	325	300	275	250	225	200	175	150	125	100	75	50	25	0
From Line 'A' To Line 'B'	Offset (Ft.)	25.11	22.97	20.19	17.59	15.17	12.92	10.86	8.97	7.27	5.74	4.39	3.22	2.24					
	Slope (%)	← Constant 4.0% Slope →																	
	Drop (Ft.)	1.00	0.92	0.81	0.70	0.61	0.52	0.43	0.36	0.29	0.23	0.18	0.13	0.09					
From Line 'B' To Line 'C'	Offset (Ft.)	← Constant 24.0' Offset →																	
	Slope (%)	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00					
	Drop (Ft.)	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96					
From Line 'A' To Line 'C'	Offset (Ft.)														25.43	24.80	24.35	24.00	24.00
	Slope (%)														4.00	4.00	4.00	3.50	3.00
	Drop (Ft.)	1.96	1.88	1.77	1.66	1.57	1.48	1.39	1.32	1.25	1.19	1.14	1.09	1.05	1.02	0.99	0.97	0.84	0.72
Distance From Point Ⓖ Along Line 'C' (Ft.)		418.13	400.00	375.00	350.00	325.00	300.00	275.00	250.00	225.00	200.00	175.00	150.00	125.00	100.00	75.00	50.00	25.00	0.00

F — G

ML035NB
RAMP A - ENTRANCE

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.3

9:16:19 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



16' ENTRANCE RAMP

③ 'CD' Joints at 20' spacing.

④ 'BT-2' joint for existing pavement or 'KT-2' for new pavement .

⑤ 'C' Joint.

⑥ 'B' Joint. 2' minimum. 4' maximum.

⑦ 10' minimum or equal to mainline shoulder width.

⑧ 'B' or 'C' Joint. 2' minimum. 4' maximum.

⑨ 'L-2' Joint


⑩ 'C' joint parallel to ramp baseline

⑪ Construct transverse joints on entrance ramp taper perpendicular to tapered edge where gore area is greater than 4'

ML035NB
RAMP A - ENTRANCE

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.4

9:16:37 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



Pt. 'F' to Pt. 'G'
△ = 4°53'28.99"
D = 0°28'38"
T = 512.54'
L = 1024.13
E = 10.94'
R = 12,000.00'


PLAN

Refer to detail project plans for mainline and ramp alignment and grade data.


Construct ramp exit pavement the same thickness as mainline pavement.

Ramp exit pavement shown by shaded area is 4482 square yards.

For jointing layout, see Standard Road Plan PV-411.
This design is based on 60 mph design speed at e max = 6%.



SECTION A-A



PROFILE

1 For header construction details at the end of taper see Typical 7101.

2 Construct subbase for ramp entrance pavement the same thickness as mainline subbase.

TABLE OF OFFSETS AND DROPS FOR 24' RAMP TAPER

Dist. From Pt. (H) Along ML035NB ℄ (Ft.)		1024.3	1000	950	900	850	800	750	700	650	600	550	500	450	400	350	300	275	250	225	200	175	150	125	100	75	50	25	0
From Line 'A' To Line 'B'	Offset (Ft.)	48.30	47.05	44.82	42.67	40.71	38.80	37.01	35.33	33.77	32.32	30.99	29.78	28.68	27.69	26.83	26.07	25.74	25.44	25.17	24.92	24.70	24.52	24.36	24.22	24.13	24.05	24.00	24.00
	Slope (%)	← Constant 2.6% Slope →																											
	Drop (Ft.)	1.26	1.22	1.17	1.11	1.06	1.01	0.96	0.92	0.88	0.84	0.81	0.77	0.75	0.72	0.70	0.68	0.67	0.66	0.65	0.65	0.64	0.64	0.63	0.63	0.63	0.63	0.62	0.62
From Line 'B' To Line 'C'	Offset (Ft.)	← Constant 12.0' Offset →						11.49	10.72	9.95	9.18	8.41	7.64	6.88	6.11	5.34	4.57	4.18	3.80	3.41	3.03	2.65	2.26	1.88	1.49	1.11	0.72	0.33	0.00
	Slope (%)	← Constant 2.6% Slope →																											
	Drop (Ft.)	0.31	0.31	0.31	0.31	0.31	0.31	0.30	0.28	0.26	0.24	0.22	0.20	0.18	0.16	0.14	0.12	0.11	0.10	0.09	0.08	0.07	0.06	0.05	0.04	0.03	0.02	0.01	0.00
From Line 'A' To Line 'C'	Offset (Ft.)																												
	Slope (%)	← Constant 2.6% Slope →																											
	Drop (Ft.)	1.57	1.53	1.48	1.42	1.37	1.32	1.26	1.20	1.14	1.08	1.03	0.97	0.93	0.88	0.84	0.80	0.78	0.76	0.74	0.73	0.71	0.70	0.68	0.67	0.66	0.65	0.63	0.62
Distance From Point (G) Along Line 'C' (Ft.)		1024.3	1000	950	900	850	800	750	700	650	600	550	500	450	400	350	300	275	250	225	200	175	150	125	100	75	50	25	0

(F) (G)

ML235
ML035NB - ENTRANCE

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.5

9:16:54 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht

Refer to detail project plans for mainline and ramp alignment and grade data.

Construct ramp exit pavement the same thickness as mainline pavement.

Ramp exit pavement shown by shaded area is 3065 square yards.

For jointing layout, see Standard Road Plan PV-410.

This design is based on 60 mph design speed at e max = 6%.






TABLE OF OFFSETS AND DROPS FOR 24' RAMP TAPER

DISTANCE FROM POINT Ⓒ ALONG LINE 'A' (Ft.)		949.91	925	900	875	850	825	800	775	750	725	700	675	650	625	600	575	550	525	500	475	450	425	400	375	350	325	300	275	250	225	200	175	150	125	100	75	50	25	0
From Line 'A' To Line 'B'	OFFSET (Ft.)																			2.97	4.22	5.47	6.72	7.97	9.22	10.47	11.72	12.97	14.22	15.47	16.72	17.97	19.22	20.47	21.72	22.97	24.22	25.47	26.72	27.97
	SLOPE (%)																			← Constant 3.0% Slope →																				
	DROP (Ft.)																			0.09	0.13	0.16	0.20	0.24	0.28	0.31	0.35	0.39	0.43	0.47	0.50	0.54	0.58	0.61	0.65	0.69	0.73	0.76	0.80	0.84
From Line 'B' To Line 'C'	OFFSET (Ft.)																			← Constant 24' Offset →																				
	SLOPE (%)																			← Constant 3.0% Slope →																		3.00	3.01	3.78
	DROP (Ft.)																			0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.72	0.91
From Line 'A' To Line 'C'	OFFSET (Ft.)	12.00	12.05	12.21	12.47	12.83	13.30	13.87	14.55	15.33	16.22	17.21	18.30	19.50	20.75	22.00	23.25	24.50	25.75																					
	SLOPE (%)	← Constant 3.0% Slope →																																						
	DROP (Ft.)	0.36	0.36	0.37	0.37	0.38	0.40	0.42	0.44	0.46	0.49	0.52	0.55	0.59	0.62	0.66	0.70	0.74	0.77	0.81	0.85	0.88	0.92	0.96	1.00	1.03	107	1.11	1.15	1.19	1.22	1.26	1.30	1.33	1.37	1.41	1.45	1.48	1.52	1.75



SECTION A-A



SECTION B-B


1 For header construction details at the beginning of taper see Typical 7101.

2 Construct subbase for ramp exit pavement the same thickness as mainline subbase.

RAMP G
WESTBOUND
RAMP A - EXIT

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.6

9:17:11 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



16' EXIT RAMP

③ 'CD' Joints at 20' spacing.

④ 'BT-2' joint for existing pavement
or 'KT-2' for new pavement .

⑤ 'C' Joint.

⑥ 'B' Joint. 2' minimum. 4' maximum.

⑦ 10' minimum or equal to mainline shoulder width.

⑧ 'B' or 'C' Joint. 2' minimum. 4' maximum.

RAMP G
WESTBOUND
RAMP A - EXIT

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.7

9:17:29 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht





TABLE OF OFFSETS AND DROPS FOR 16' RAMP

Dist. From Pt. (E) Along Ramp G ℄ (Ft.)		230	225	200	175	150	125	100	75	50	25	0	25	50	75	100	125	150	175	200	225	250	275	300	325	350	375	400	450	500	550	600	650	700	750	800	850	900	950	1000
From Line 'A' To Line 'B'	Offset (Ft.)	23.06	22.34	18.92	15.85	13.12	10.74	8.71	7.02	5.67	4.66	4.00																												
	Slope (%)	← Constant Slope 4.00% →																																						
	Drop (Ft.)	0.92	0.89	0.76	0.63	0.52	0.43	0.35	0.28	0.23	0.19	0.16																												
From Line 'B' To Line 'C'	Offset (Ft.)	← Constant Offset 16.00' →																																						
	Slope (%)	← Constant Slope 4.60% →									3.90	3.22																													
	Drop (Ft.)	0.74	0.74	0.74	0.74	0.74	0.74	0.74	0.74	0.74	0.62	0.52																												
From Line 'A' To Line 'C'	Offset (Ft.)											20.00	19.50	19.00	18.50	18.00	17.50	17.00	16.50	16.00	15.50	15.00	14.50	14.00	13.50	13.00	12.50	12.00	11.00	10.00	9.00	8.00	7.00	6.00	5.00	4.00	3.00	2.00	1.00	0.00
	Slope (%)											3.22	← Constant Slope 3.00% →								2.22	← Constant Slope 2.00% →																	
	Drop (Ft.)	1.66	1.64	1.50	1.38	1.27	1.17	1.09	1.02	0.97	0.81	0.68	0.59	0.57	0.55	0.54	0.53	0.51	0.50	0.48	0.34	0.30	0.29	0.28	0.27	0.26	0.25	0.24	0.22	0.20	0.18	0.16	0.14	0.12	0.10	0.08	0.06	0.04	0.02	0.00
Distance From Point (G) Along Line 'C' (Ft.)		228.62	225.91	200.67	176.76	150.33	125.21	100.13	75.07	50.03	25.01	0																												

(F) (H) (E) (G) (P)



Refer to detail project plans for mainline and ramp alignment and grade data.

Construct ramp exit pavement the same thickness as mainline pavement.

Ramp exit pavement shown by shaded area is 1800 square yards.

For jointing layout, see Standard Road Plan PV-411.

This design is based on 60 mph design speed at e max = 6%.


(1) For header construction details at the end of taper see Typical 7101.

(2) Construct subbase for ramp entrance pavement the same thickness as mainline subbase.

RAMP G
RAMP B - ENTRANCE

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.8

9:18:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



16' ENTRANCE RAMP

③ 'CD' Joints at 20' spacing.

④ 'BT-2' or 'KT-2' Joint.

⑤ 'C' Joint.

⑥ 'B' Joint. 2' minimum, 4' maximum.

⑦ Construct transverse joints on the entrance ramp taper perpendicular to the tapered edge where the gore area is greater than 4 feet.

⑧ 'C' Joint parallel to ramp baseline.

⑨ 10' minimum, or equal to mainline shoulder width.

⑩ 'B' or 'C' Joint. 2' minimum. 4' maximum.

⑪ 'EF' Joint

RAMP G
RAMP B - ENTRANCE

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.9

9:18:22 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht

Refer to detail project plans for mainline and ramp alignment and grade data.


Construct ramp exit pavement the same thickness as mainline pavement.

Ramp exit pavement shown by shaded area is 2247 square yards..


This design is based on 60 mph design speed at e max = 6%.

(1) For header construction details at the beginning of taper see Typical 7101.


(2) Construct subbase for ramp exit pavement the same thickness as mainline subbase.



PLAN



PROFILE



SECTION A-A

C


	TABLE OF OFFSETS AND DROPS FOR 36' RAMP TAPER																						
DISTANCE (Ft.)	559.40	525	500	475	450	425	400	375	350	325	300	275	250	225	200	175	150	125	100	75	50	25	0
OFFSET (Ft.)	35.96	37.76	39.01	40.26	41.51	42.76	44.01	45.26	46.51	47.76	49.01	50.26	51.51	52.76	54.01	55.26	56.51	57.76	59.01	60.26	61.51	62.76	64.01
SLOPE (%)	← Constant Slope 3.00% →																						
DROP (Ft.)	1.08	1.13	1.17	1.21	1.25	1.28	1.32	1.36	1.40	1.43	1.47	1.51	1.55	1.58	1.62	1.66	1.70	1.73	1.77	1.81	1.85	1.88	1.92

M

MAINLINE I-80
WESTBOUND
RAMP A & G - EXIT

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.10

9:18:41 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



16' EXIT RAMP

③ 'CD' Joints at 20' spacing.

④ 'BT-2' joint for existing pavement or 'KT-2' for new pavement .

⑤ 'C' Joint.

⑥ 'B' Joint. 2' minimum. 4' maximum.

⑦ 10' minimum or equal to mainline shoulder width.

⑧ 'B' or 'C' Joint. 2' minimum. 4' maximum.


⑨ Construct transverse joints on the exit ramp taper perpendicular to tapered edge

⑩ 'L-2' Joint

MAINLINE I-80
WESTBOUND
RAMP A & G - EXIT

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.11	

9:18:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U01.sht



CLEARING AND GRUBBING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.12

9:19:26 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u02.sht

STA 32587+03.30
250.8 RT 235B

STA 38571+47.15
239.3 RT 235G

STA 38559+93.18
89.7 RT 235G

STA 38559+53.67
83.4 RT 235G

STA 2017+96.19
60.6 RT ML235

STA 32591+88.21
114.9 RT 235B

STA 32590+38.84
102.6 RT 235B

STA 38565+26.78
145.5 RT 235G

STA 38566+08.10
152.5 RT 235G

STA 38560+34.12
148.7 RT 235G

STA 38562+49.73
155.0 RT 235G

STA 38559+83.98
93.1 RT 235G

STA 38556+47.40
131.2 RT 235G

STA 2017+97.15
155.0 RT ML235

NE 46TH AVE

NE 22ND ST

235B

ML035N

ML235

LEGEND

CLEARING AND GRUBBING AREA

0 FEET 100

CLEARING AND GRUBBING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.13

9:19:34 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u02.sht

STA 8503+66.50
57.6 LT ML035N

STA 8504+41.87
55.6 LT ML035N

STA 8505+60.98
150.9 LT ML035N

STA 8508+33.89
148.4 LT ML035N

STA 8509+06.41
155.6 LT ML035N

STA 8510+06.17
120.7 LT ML035N

STA 8517+42.33
119.2 LT ML035N

STA 8524+03.01
90.4 LT ML035N

STA 8526+53.47
59.0 LT ML035N

STA 8503+66.45
33.6 RT ML035N

STA 8504+34.43
35.4 RT ML035N

STA 8504+78.39
140.1 RT ML035N

STA 8505+15.09
164.8 RT ML035N

STA 8505+95.77
94.5 RT ML035N

STA 8505+49.16
159.9 RT ML035N

STA 8508+34.58
119.8 RT ML035N

STA 38503+04.92
86.0 LT 235A

STA 38495+51.89
70.2 LT 235A

STA 38497+99.44
79.7 LT 235A

STA 38488+30.46
84.3 LT 235A

STA 38489+04.99
70.1 LT 235A

STA 8516+02.96
830.8 RT ML035N

STA 8516+65.47
795.6 RT ML035N

STA 8518+50.90
108.4 RT ML035N

STA 8519+59.59
912.4 RT ML035N

STA 8519+48.72
939.8 RT ML035N

ML235

ML035N

235A

NE 54TH AVE

Pond

Conc.

LEGEND


CLEARING AND GRUBBING AREA

0 FEET 100

CLEARING AND GRUBBING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.14

9:19:41 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u02.sht


23.68 CH AR 1558.715 NOM
Conc.
Open Storage
Billboard
Billboard
Rip Rap
Rip Rap
8530
8535
8540
2100
2105
2110
2115
2120
2125
SIGN BRIDGE
SIGN BRIDGE
SIGN BRIDGE
SIGN BRIDGE
ML235
ML035N
STA 8541+96.98
12.2 RT ML035N
STA 8530+87.49
100.3 RT ML035N
STA 8530+33.80
92.1 RT ML035N
STA 8534+79.38
107.9 RT ML035N
STA 8537+54.04
96.0 RT ML035N
STA 2110+25.00
225.0 RT ML235
STA 2113+09.15
309.0 RT ML235
STA 2114+59.42
85.0 RT ML235
STA 2114+59.42
205.4 RT ML235
STA 2113+09.15
205.4 RT ML235
F03
F03
F03

LEGEND

CLEARING AND GRUBBING AREA

NE 54TH AVE

STA 8516+02.96
830.8 RT ML035N

STA 8516+65.47
795.6 RT ML035N

STA 38497+99.44
79.7 LT 235A

STA 38503+04.92
86.0 LT 235A

STA 38508+94.75
109.0 LT 235A

STA 38619+28.76
127.0 LT 235G

STA 38626+04.25
132.9 LT 235G

STA 38629+76.06
108.3 LT 235G

STA 38615+25.20
108.4 RT 235G

STA 38615+23.97
190.4 RT 235G

STA 38616+48.87
225.0 RT 235G

STA 38616+26.21
254.7 RT 235G

38500 38505 38510 38600 38605 38610 38615 38620 38625 38630

1105 1110 1115 1120 1125

235A 235G


SUR080

0 100 FEET

CLEARING AND GRUBBING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.16

9:20:02 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u02.sht




LEGEND

CLEARING AND GRUBBING AREA


CLEARING AND GRUBBING

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.17

9:20:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u02.sht



SECTION A-A
Bent Bar Placement



ELEVATION


For loop bars 6d1, 6d2, and 6d3, use $\frac{3}{4}$" smooth steel bars with a minimum yield strength of 60 ksi, a tensile strength of not less than 1.25 times the yield strength but a minimum of 80 ksi, a minimum 14% elongation in 8 inches, and passing a 180 degree bend test using a 2 $\frac{3}{4}$" pin bend diameter.

Install loops within $\frac{1}{8}$" of the plan dimensions.


Use Grade 60, ASTM A615 for all other reinforcements. Do not lift or move using loop bars 6d1, 6d2 or 6d3.

Provide for an approved monitoring schedule with a person on call and available 24 hours a day, each day of the week, to realign barrier which has been struck. Initiate service within one hour of notification of need.

For BA-401 anchorage requirements, refer to detail "Freestading to Anchored Temporary Barrier Rail Connection".



PLAN




BARRIER CONNECTION
(Elevation)


Possible Contract Item:
Temporary to Permanent Barrier Connection

Possible Tabulation:
108-38

TBR CONNECTION
(FOR NEW BA-100 44" CONCRETE BARRIER)
SHEET 1 OF 2




Elevation




Plan
6d1, 6d2, 6d3


BENT BAR DETAILS
(Dimensions are out to out of bars unless otherwise noted.)



CONNECTION PIN
(A36 Steel - 10.9 lbs. each)




½" Top Plate




RETAINER BOLT & NUT
½" dia. bolt & nut
(ASTM A490, Grade 8)

CONNECTION PIN ASSEMBLY

REINFORCING A615 Gr. 60 - LOOP ASSEMBLY					
Bar	Bar Size	Shape	No. of Bars	Length Ft.	Weight Lbs.
6d1	6		1	8'-5"	12.7
6d2	6		1	7'-7"	11.4
6d3	6		1	8'-6"	12.8



Plan




Elevation

End View


HEIGHT TRANSITION
12-gauge ASTM A36 Steel
Galvanized after Welding

*Install anchor bolts to secure Height Transition to barriers. Ensure a minimum embedment depth of 4".

TBR CONNECTION
(FOR NEW BA-100 44" CONCRETE BARRIER)
SHEET 2 OF 2



SECTION A-A



HEIGHT TRANSITION
12-gauge ASTM A36 Steel
Galvanized after Welding

Install temporary barrier rail on a flat, level surface.

Upon removal of Temporary to Permanent Barrier Connection, use non-shrink grout complying with Materials I.M. 491.13 to fill any holes that were drilled in permanent median barrier.

Contract Item: Temporary to Permanent Barrier Connection

Item includes:
- 4 - 12'-6" Thrie Beam Guardrail Sections
- 4 - BA-202 Terminal Connectors
- 1 - Height Transition
- 48 - ⅝" dia. Guardrail Splice Bolts and Nuts
- 24 - ¾" dia. Rail Anchor Bolts: Powers Fasteners Wedge-Bolt Anchor OR Red Head Large Diameter Tapcon OR Simpson Titen HD Screw Anchor
- 4 - ⅝" dia. Height Transition Anchor Bolts: Powers Fasteners Wedge-Bolt Anchor OR Red Head Large Diameter Tapcon OR Simpson Titen HD Screw Anchor

The number of Temporary to Permanent Barrier Connections will be counted. The Contractor will be paid the contract unit price for each Temporary to Permanent Barrier Connection measured as provided above.


(1) Install five (5) Rail Anchor Bolts in each Terminal Connector as shown. Install two (2) Rail Anchor Blots through the center slots of each Thrie Beam Guardrail Section. Ensure a minimum embedment depth of 6". Drill pilot holes with a core bit. Avoid drilling through reinforcing steel within temporary barrier rail sections.

(2) Shift opposite side thrie-beam sections 16" upstream or downstream in order to prevent anchor bolt interference.


(3) 32" mounting height preferred. 30" minimum.

(4) Install anchor bolts to secure Height Transition to barriers. Ensure a minimum embedment depth of 4".

(5) Each connection requires nine (9) BA-401 stake anchors as shown. Use of the strap anchor is not allowed.



PLAN




ELEVATION

TBR CONNECTION (FOR EXISTING BA-100 44" CONCRETE BARRIER)

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.20

9:20:19 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U18.sht

Freestanding to Anchored Temporary Barrier Rail Connection Shall be Considered Incidental to the Temporary Barrier Rail, Concrete Item.



Freestanding to Anchored Temporary Barrier Rail Connection

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.21

9:20:21 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U18.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 19

Sta. 2028+23.86 225.78 LT (ML235) =
Sta. 38557+03.00 125.53 LT (235G)

Sta. 2027+70.05
224.00 LT (ML235)

Sta. 2017+97.14
154.00 LT (ML235)
Begin Install Fence

Billboard

Billboard

38555

EB

EB

SIGN BRIDGE

SIGN BRIDGE

St.S.

St.S.

St.S.

ML I-235 (ML235)

2015

2020

2025

0 FEET 50

FENCE LOCATION DETAILS

DELAWARE TWP.
T-79-N R-23W
SEC. 19

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Sta. 2028+23.86 225.78 LT (ML235) =
Sta. 38557+03.00 125.53 LT (235G)

Sta. 38559+53.90
95.63 LT (235G)
End Install Fence

Sta. 38560+64.32
148.60 LT (235G)
Begin Install Fence

Sta. 38565+27.09
144.47 LT (235G)

Sta. 38565+49.98
160.97 LT (235G)

Sta. 38562+49.73
154.00 LT (235G)

Sta. 38566+08.04
151.55 LT (235G)

Billboard

SIGN

38555

38560

38565

32595

EB

EB

WB I-80 to SB I-235
RAMP G (235G)

St.S.

ML I-235 (ML235)

2030

0 FEET 50


DELAWARE TWP.
T-79-N R-23W
SEC. 19


DELAWARE TWP.
T-79-N R-23W
SEC. 18

FENCE LOCATION DETAILS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.22

9:20:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u03.sht





FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.23

9:20:42 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u03.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 7

Sta. 2112+06.29
277.53 RT (ML235)
Begin Install Fence

Sta. 2110+25.20
224.02 RT (ML235)

Sta. 2109+33.27
214.01 RT (ML235)

F03

SIGN BRIDGE

MM

8540

2120

2115

2110

I-235 (ML235)

DELAWARE TWP.
T-79-N R-23W
SEC. 7

0 50
FEET

FENCE LOCATION DETAILS

DELAWARE TWP.
T-79-N R-23W
SEC. 7

Sta. 2104+30.00
174.00 RT (ML235)

Sta. 2101+59.96
194.00 RT (ML235)

Sta. 2099+22.01
197.83 RT (ML235) =
Sta. 8532+37.47
100.66 RT (ML035N)

Sta. 8530+87.57
99.25 RT (ML035N)

Sta. 8530+34.66
91.14 RT (ML035N)

8540

8535

8530

8525

2105

2100

2095

NB I-35 (ML035N)

I-235 (ML235)


DELAWARE TWP.
T-79-N R-23W
SEC. 7

0 50
FEET

FENCE LOCATION DETAILS


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.24


9:20:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u03.sht



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.25


9:21:00 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u03.sht





FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.26

9:21:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u03.sht



FENCE LOCATION DETAILS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.27

9:21:18 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u03.sht

DELAWARE TWP.
T-79-N R-24W
SEC. 13

SAYLOR TWP.
T-79-N R-23W
SEC. 18

Remove Apron
Sta. 1066+98.23
89.86 LT (SUR080)

Abandon Culvert
Sta. 1066+75.37
0.00 RT (SUR080)

Remove Apron
Sta. 8464+74.04
13.90 LT (ML035N)

Remove Fence
Sta. 1061+87.48
186.88 RT (SUR080)

Remove Fence
Sta. 1064+15.16
178.51 RT (SUR080)
Sta. 8464+19.42
71.84 RT (ML035N)

Remove Apron
Sta. 1066+43.14
129.38 RT (SUR080)

Remove Fence
Sta. 8475+64.35
2.40 LT (ML035N)

1065
1070
1075
8465
8470
8475

SIGN
SIGN BRIDGE
EB
WB
NB
SB
GV
WV
UP

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.28

9:21:30 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

SAYLOR TWP.
T-79-N R-23W
SEC. 18

8480

32585

38575

32580

32590

Remove Fence
Sta. 32585+04.35
13.89 LT (235B)

EB I-80 to SB I-235 RAMP B (235B)

Remove Fence
Sta. 32590+44.21
41.08 LT (235B)

Remove Fence
Sta. 32582+12.59
92.46 RT (235B)

Remove Fence
Sta. 32575+56.70
66.77 LT (235B)

32575

SIGN

Open Storage

Gate

8801

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.29	

9:21:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 19

Billboard

Billboard

Billboard

Remove Fence
Sta. 2017+97.62
154.03 LT (ML235)

Remove Apron
Sta. 2030+13.58
128.90 LT (ML235)

38555

BRIDGE

BRIDGE

2015

2020

2025

2030

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.30

9:21:49 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

APPROX. SEC. LINE

SIGN

Open Storage

Remove Fence
Sta. 2031+97.72
158.80 LT (ML235)

Remove Apron
Sta. 2032+30.02
136.51 LT (ML235)

Remove Fence
Sta. 2031+98.02
81.31 LT (ML235)

Remove Fence
Sta. 2030+43.55
63.36 LT (ML235)

Remove Apron
Sta. 2035+03.37
144.22 LT (ML235)

Remove Fence
Sta. 2043+33.22
398.41 LT (ML235)

Remove Fence
Sta. 2041+12.89
158.38 LT (ML235)

Remove Fence
Sta. 2041+18.53
91.06 LT (ML235)

Remove Fence
Sta. 2043+39.09
99.79 LT (ML235)

38560
38595
38570
32590

2030
2035
2040
2045

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.31

9:21:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

Remove Fence
Sta. 8512+07.22
159.65 LT (ML035N)

Remove Fence
Sta. 8508+00.00
165.08 RT (ML035N) =
Sta. 38496+65.39
126.64 RT (235A)

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.32

9:22:10 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 7

Pond

Billboard

SIGN

BRIDGE

St.S.

2085

2090

2095

2100

MM

F03

8520

8525

8530

38485

Remove Fence
Sta. 8532+37.47
73.53 RT (ML035N) =
Sta. 2099+20.78
170.73 RT (ML235)

N

0 50
FEET

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.33	

9:22:19 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 7

Billboard

Rip Rap

SIGN BRIDGE

SIGN BRIDGE

SIGN BRIDGE

SIGN BRIDGE

2100 BRIDGE

2105 BRIDGE

2110 BRIDGE

2115

8535

8540

MM

MM

MM

F03

F03

Remove Apron
Sta. 2107+00.46
128.26 RT (ML235)

Remove Fence
Sta. 2112+06.29
277.53 RT (ML235)

0 50
FEET

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.34	

9:22:47 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

38500

38505

38510

38605

8505

1105

Pc Sta 38502+68.51

Remove Fence
Sta. 38496+65.39
126.64 RT (235A) =
Sta. 8508+00.00
168.05 RT (ML035N)

F03

E2

SIGN

EB

UB

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.35

9:22:57 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

N

38510
38610
38615
38620
38625

Remove Fence
Sta. 38511+66.22
317.45 RT (235A) =
Sta. 38611+50.37
265.05 RT (RMPG)

FO3
SIGN
SIGN BRIDGE

1110
1115
1120
1125

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.36

9:23:06 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 18

DELAWARE TWP.
T-79-N R-23W
SEC. 17

N

Remove Pavement
Sta. 38807+99.00
14.44 LT (SR29TH)

Remove Pavement
Sta. 38807+75.00
14.40 LT (SR29TH)

Remove Pavement
Sta. 38807+99.00
16.02 RT (SR29TH)

Remove Pavement
Sta. 38807+75.00
16.15 RT (SR29TH)

Remove Trail
Sta. 21+18.01
5.00 LT (CV_TRAIL)

Remove Trail
Sta. 21+18.01
5.00 RT (CV_TRAIL)

Remove Fence
Sta. 38637+77.87
105.28 LT (235G) =
Sta. 5137+83.13
220.15 LT (ML080)

Remove 18" x 66.1'
RCP & Apron
Sta. 38637+77.87
21.90 LT (235G)

Remove 18" x 61.7'
RCP & Apron
Sta. 38630+76.57
65.91 RT (235G)

Remove Apron
Sta. 38635+07.56
17.75 RT (235G)

Remove Fence
Sta. 38634+57.98
90.56 RT (235G)

Remove Fence
Sta. 38631+39.95
126.56 RT (235G)

Remove Trail
Sta. 13+98.44
5.00 RT (CV_TRAIL)

Remove Trail
Sta. 13+98.44
5.00 LT (CV_TRAIL)

38625 38630 38635 1140 1135 1130 1125 5140 5135 5130

SIGNAL BRIDGE SIGN

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.37

9:23:15 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht

DELAWARE TWP.
T-79-N R-23W
SEC. 17

Remove 18" x 88.3'
RCP & Apron
Sta. 5143+03.82
134.64 LT (ML080)

Remove Fence
Sta. 5144+86.01
229.28 LT (ML080)

Remove 18" x728'
RCP & Apron
Sta. 5146+98.80
116.90 LT (ML080)

Remove Apron
Sta. 5151+00.67
100.02 LT (ML080)

1140 1145 1150 1155


5140 5145 5150 5155

0 FEET 50

STAGE 3
REMOVALS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.38

9:23:26 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194u04.sht



DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES

CASE A
TRANSITION DETAILS - TANGENT TO CURVE
WHEN NORMAL CROSS SLOPE IS IN THE OPPOSITE DIRECTION AS SUPERELEVATION

Refer to specific curve data contained in project plans for tangent runout length (x), runoff length (L) and full superelevation (e).

Place 90% of full superelevation at the P.C. and P.T.

Place 10% of the runoff length within the curve.

Unless otherwise specified, all lengths are measured along the baseline.

Smooth curves should be established at the time of construction at sections A-D along the profile edge of lines A and B.

Axis of rotation coincides with profile grade location.

m = 10% of Runoff Length (L)

Ⓦ = Pavement Width


g = Normal Cross Slope (2%)


L = Distance to Change Cross Slope from 0% to e

e = Superelevation Rate

x = Distance to Change Cross Slope from 0% to 2%

s = Normal Shoulder Slope





DIAGRAMMATIC PROFILES OF THE PAVEMENT EDGE LINES

CASE B
TRANSITION DETAILS - TANGENT TO CURVE
WHEN NORMAL CROSS SLOPE IS IN THE SAME DIRECTION AS SUPERELEVATION

Possible Tabulation:
101-18

MODIFIED
STANDARD ROAD PLAN

REVISION
2 | 04-21-20

PV-303

SHEET 1 of 3


REVISIONS: Modified "m" distance to 10% of Runoff Length.


APPROVED BY DESIGN METHODS ENGINEER

SUPERELEVATION DETAILS
RAMPS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.39

9:23:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U05.sht





SECTION WHERE SHOULDER SLOPE TRANSITION BEGINS

CASE A

1. High Side Shoulder: Maintain normal shoulder cross slope (s), until the cross slope break with the adjacent pavement reaches 8.0%. Maintain 8% breakover until superelevation rate reaches 7%. If superelevation rate exceeds 7.0%, maintain a 1% shoulder cross slope away from the adjacent pavement.
2. Low Side Shoulder: Maintain normal shoulder cross slope (s) until the adjacent pavement slope equals s, then slope the shoulder at the same cross slope as the adjacent pavement.
3. Subgrade Surface: Subgrade surface cross slope parallel to pavement surface cross slope.

MODIFIED
STANDARD ROAD PLAN

REVISION	
2	04-21-20

PV-303

SHEET 2 of 3


REVISIONS: Modified "m" distance to 10% of Runoff Length.

APPROVED BY DESIGN METHODS ENGINEER


SUPERELEVATION DETAILS
RAMPS

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.40

9:23:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U05.sht




SECTION D-D
(Full Superelevation)




SECTION C-C

m


L - x




SECTION A-A
(Typical Section)



CASE U
(Section where e ≥ 7.0%)



CASE T
(Section where high side shoulder crown break rule occurs)



CASE S (2)
(Section where low side shoulder crown break rule occurs)

SECTION WHERE SHOULDER SLOPE TRANSITION BEGINS

CASE B

(1) High Side Shoulder: Maintain normal shoulder cross slope (s), until the cross slope break with the adjacent pavement reaches 8.0%. Maintain 8% breakover until superelevation rate reaches 7%. If superelevation rate exceeds 7.0%, maintain a 1% shoulder cross slope away from the adjacent pavement.

(2) Low Side Shoulder: Maintain normal shoulder cross slope (s) until the adjacent pavement slope equals s, then slope the shoulder at the same cross slope as the adjacent pavement.

(3) Subgrade Surface: Subgrade surface cross slope parallel to pavement surface cross slope.

MODIFIED
STANDARD ROAD PLAN

REVISION	
2	04-21-20

PV-303

SHEET 3 of 3

REVISIONS: Modified "m" distance to 10% of Runoff Length.


APPROVED BY DESIGN METHODS ENGINEER

SUPERELEVATION DETAILS
RAMPS


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER U.41

9:23:33 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194U05.sht

BENCH MARK NO. 128, ELEV. 933.868, STA. 8478+62.35, 6457.91' RT., FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

Z

0 ENGLISH 40
SCALE IN FEET

I-35 TRAFFIC ESTIMATE

2012 AADT	75,200	V.P.D.
2050 AADT	125,800	V.P.D.
2050 DHV	13,000	V.P.H.
TRUCKS	14	%
TOTAL DESIGN ESALs	-	

LOCATION

US 35 NORTHBOUND
T-79 N R-24 W
SECTION 13
SAYLOR TOWNSHIP
POLK COUNTY
LATITUDE 41.6506° N
LONGITUDE 93.5847° W


HYDRAULIC DATA

DRAINAGE AREA = 57 ACRES - ROLLING
Q_{50} = 98 CFS
HW ELEV. = 926.57

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	75	104	40
TOTALS	75	104	72

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR A 0° SKEW RT. AHD.

54 in. x 330 ft (TRENCHLESS) REINFORCED CONCRETE PIPE (3000D)

PLAT PLAN

STA. 8466+33.34 (℄ ML35N) NOVEMBER 2016


POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION


DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####

DESIGN TEAM	Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.2

BENCH MARK NO. 128, ELEV. 933.868, STA. 8478+62.35, 6457.91' RT., FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION AT CULVERT INVERTS



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

I-35 TRAFFIC ESTIMATE

2012 AADT	75,200	V.P.D.
2050 AADT	125,800	V.P.D.
2050 DHV	13,000	V.P.H.
TRUCKS	14	%
TOTAL DESIGN ESALs	-	

LOCATION

US 35 NORTHBOUND
T-79 N R-24 W
SECTION 13
SAYLOR TOWNSHIP
POLK COUNTY
LATITUDE 41.6506° N
LONGITUDE 93.5833° W


HYDRAULIC DATA

DRAINAGE AREA = 117.6 ACRES - ROLLING
Q_{50} = 166 CFS
HW ELEV. = 927.90

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	161	208	216
TOTALS	161	208	216

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR A 15° SKEW LT. AHD.

66" X 150'
REINFORCED CONCRETE PIPE
PLAT PLAN

STA. 8470+71.58 (℄ ML35N) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER V.3

10/18/2021 3:33:36 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V3 11x17_pdf.pltcfg


BENCH MARK NO. 128, BENCH MARK NO. STA. 8478+62.35, 6457.91' RT., FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION AT CULVERT INVERTS



PLAT PLAN



0 ENGLISH 40
SCALE IN FEET

I-35 TRAFFIC ESTIMATE

2012 AADT	75,200	V.P.D.
2050 AADT	125,800	V.P.D.
2050 DHV	13,000	V.P.H.
TRUCKS	14	%
TOTAL DESIGN ESALs	-	

LOCATION

US 35 NORTHBOUND
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6575° N
LONGITUDE 93.5744° W


HYDRAULIC DATA

DRAINAGE AREA = 5.6 ACRES - ROLLING
Q_{50} = 16 CFS
HW ELEV. = 945.57

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	21	35	15
TOTALS	21	35	15

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR A 22° SKEW LT. AHD.

24" X 254'
REINFORCED CONCRETE PIPE
PLAT PLAN

STA. 8512+64 (℄ ML35N) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM	Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.4

10/18/2021 3:34:25 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V4 11x17_pdf.pltcfg

BENCH MARK NO. 128, ELEV. 933.868, STA. 8478+62.35, 6457.91' RT., FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

I-35 TRAFFIC ESTIMATE

2012 AADT	75,200	V.P.D.
2050 AADT	125,800	V.P.D.
2050 DHV	13,000	V.P.H.
TRUCKS	14	%
TOTAL DESIGN ESALs	-	

LOCATION

US 35 NORTHBOUND
T-79 N R-23 W
SECTION 17
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6589° N
LONGITUDE 93.5747° W


HYDRAULIC DATA

DRAINAGE AREA = 25.3 ACRES - ROLLING
Q_{50} = 52 CFS
HW ELEV. = 955.25

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	18	31	13
TOTALS	18	31	13

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

52" X 32" X 114' REINFORCED CONCRETE PIPE

PLAT PLAN

STA. 8518+00 (℄ ML35N) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM	Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.5

10/18/2021 3:34:33 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V5 11x17_pdf.pltcfg

BENCH MARK NO. 128, ELEV. 933.868, STA. 1990+51.45, 161.67' RT., FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	13,900	V.P.D.
2050 AADT	18,500	V.P.D.
2050 DHV	2,750	V.P.H.
TRUCKS	11	%
TOTAL DESIGN ESALs	-	

LOCATION

US 235
T-79 N R-23 W
SECTION 19
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6422° N
LONGITUDE 93.5761° W


HYDRAULIC DATA

DRAINAGE AREA = 7.9 ACRES - ROLLING
Q_{50} = 35 CFS

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	13	24	9
TOTALS	13	24	9

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

30" X 46' REINFORCED CONCRETE PIPE CULVERT EXTENSION LEFT

PLAT PLAN

STA. 2024+30.50 (℄ ML235) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER V.6

10/18/2021 3:34:41 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V6 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	13,900	V.P.D.
2050 AADT	18,500	V.P.D.
2050 DHV	2,750	V.P.H.
TRUCKS	11	%
TOTAL DESIGN ESALs	-	

LOCATION

RAMP G
T-79 N R-23 W
SECTION 19
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6439° N
LONGITUDE 93.5761° W


HYDRAULIC DATA

DRAINAGE AREA = 3.0 ACRES - ROLLING
Q_{50} = 10 CFS

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	11	20	8
TOTALS	11	20	8

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL.E REVETMENT PER EC-301.



DESIGN FOR 11° SKEW LT. AHD.

24" X 100' REINFORCED CONCRETE PIPE CULVERT EXTENSION LEFT

PLAT PLAN

STA. 38559+38.95 (℄ Ramp G) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER V.7

10/18/2021 3:34:50 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V7 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	13,900	V.P.D.
2050 AADT	18,500	V.P.D.
2050 DHV	2,750	V.P.H.
TRUCKS	11	%
TOTAL DESIGN ESALs	--	

LOCATION

RAMP G
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6442° N
LONGITUDE 93.5761° W


HYDRAULIC DATA

DRAINAGE AREA = 4.0 ACRES - ROLLING
Q_{50} = 12 CFS

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	11	20	8
TOTALS	11	20	8

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL.E REVETMENT PER EC-301.



DESIGN FOR 10° SKEW LT. AHD.

24" X 140' REINFORCED CONCRETE PIPE CULVERT EXTENSION LEFT PLAT PLAN

STA. 38560+37.39 (℄ Ramp G) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER V.8

10/18/2021 3:34:58 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V8 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG AT CULVERT INVERTS



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	13,900	V.P.D.
2050 AADT	18,500	V.P.D.
2050 DHV	2,750	V.P.H.
TRUCKS	11	%
TOTAL DESIGN ESALs	--	

LOCATION

RAMP G
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6450° N
LONGITUDE 93.5764° W


HYDRAULIC DATA

DRAINAGE AREA = 16.0 ACRES - ROLLING
Q_{50} = 37 CFS

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	16	28	11
TOTALS	16	28	11

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE.
QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 11° SKEW RT. AHD.

36" X 174'
REINFORCED CONCRETE PIPE (3000D) CULVERT EXTENSION LEFT
PLAT PLAN

STA. 38563+52.76 (℄ Ramp G) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER V.9

10/18/2021 3:35:07 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V9 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	13,900	V.P.D.
2050 AADT	18,500	V.P.D.
2050 DHV	2,750	V.P.H.
TRUCKS	11	%
TOTAL DESIGN ESALs	-	

LOCATION

RAMP G
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6458° N
LONGITUDE 93.5767° W


HYDRAULIC DATA

DRAINAGE AREA = 5.0 ACRES - ROLLING
Q_{50} = 15 CFS
HW ELEV. = 946.83

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	30.2	47	27
TOTALS	30.2	47	27

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

24" X 190'
REINFORCED CONCRETE PIPE (3000D)
PLAT PLAN

STA. 38566+00 (℄ Ramp G) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM	Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.10

10/18/2021 3:35:16 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V10 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG AT CULVERT INVERTS



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	N/A	V.P.D.
2050 AADT	22,400	V.P.D.
2050 DHV	2,620	V.P.H.
TRUCKS	18	%
TOTAL DESIGN ESALs	-	

LOCATION

RAMP G
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6544° N
LONGITUDE 93.5678° W


HYDRAULIC DATA

DRAINAGE AREA = 70.6 ACRES - ROLLING
Q_{50} = 115 CFS
HW ELEV. = 926.46

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	20.6	35	15
TOTALS	20.6	35	15

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 47° SKEW RT. AHD.

73" X 45" X 284' REINFORCED CONCRETE PIPE PLAT PLAN

STA. 38613+57.50 (℄ Ramp G) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER V.11

10/18/2021 3:35:24 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V11 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	N/A	V.P.D.
2050 AADT	22,400	V.P.D.
2050 DHV	2,620	V.P.H.
TRUCKS	18	%
TOTAL DESIGN ESALs	-	

LOCATION

RAMP G
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6547° N
LONGITUDE 93.5633° W


HYDRAULIC DATA

DRAINAGE AREA = 6.9 ACRES - ROLLING
Q_{50} = 19 CFS
HW ELEV. = 926.41

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	39	59	25
TOTALS	39	59	25

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE.
QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

24" X 124'
REINFORCED CONCRETE PIPE
PLAT PLAN

STA. 38625+80 (℄ Ramp G) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER V.12

10/18/2021 3:35:33 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V12 11x17_pdf.pltcfg

BENCH MARK NO. 100, ELEV. 904.541, N 601242.316, E 1613129.094, FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN



0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	N/A	V.P.D.
2050 AADT	6,400	V.P.D.
2050 DHV	1,040	V.P.H.
TRUCKS	13	%
TOTAL DESIGN ESALs	-	

LOCATION

EB I-80 TO SB I-235 - RAMP B
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6478° N
LONGITUDE 93.5775° W


HYDRAULIC DATA

DRAINAGE AREA = 3.6 ACRES - ROLLING
Q_{50} =11 CFS
HW ELEV. = 951.04

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	30	47	27.4
TOTALS	30	47	27.4

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

24" X 124' REINFORCED CONCRETE PIPE PLAT PLAN

STA. 32589+00 (℄ Ramp B) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM	Iowa DOT/HDR	POLK	COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.13

10/18/2021 3:35:41 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V14 11x17_pdf.pltcfg


BENCH MARK NO. 128, ELEV. 933.868, STA. 38509+14.31, 8020.79' RT., FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN



0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	5,400	V.P.D.
2050 AADT	10,300	V.P.D.
2050 DHV	900	V.P.H.
TRUCKS	30	%
TOTAL DESIGN ESALs	-	

LOCATION

WB I-80 TO NB I-35 - RAMP A
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6556° N
LONGITUDE 93.5719° W


HYDRAULIC DATA

DRAINAGE AREA = 10.6 ACRES - ROLLING
Q_{50} = 27 CFS
HW ELEV. = 940.59

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	47.3	68.9	54.4
TOTALS	47.3	68.9	54.4

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

30" X 90' REINFORCED CONCRETE PIPE PLAT PLAN

STA. 38501+70 (℄ Ramp A) NOVEMBER 2016


POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION


DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####

DESIGN TEAM	Iowa DOT/HDR	POLK	COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.14

BENCH MARK NO. 128, ELEV. 933.868, N 594971.978, E 1619970.2, FENO MONUMENT BTWN TOP OF BKSLP AND R.O.W. FENCE IN EAST R.O.W.



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	N/A	V.P.D.
2050 AADT	N/A	V.P.D.
2050 DHV	N/A	V.P.H.
TRUCKS	N/A	%
TOTAL DESIGN ESALs	-	

LOCATION

NE 29TH STREET
T-79 N R-23 W
SECTION 17-18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6553° N
LONGITUDE 93.5611° W


HYDRAULIC DATA

DRAINAGE AREA = 15.3 ACRES - ROLLING
Q_{50} = 35 CFS
HW ELEV. = 905.49

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	15.2	26.7	11
TOTALS	15.2	26.7	11

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

36" X 58' REINFORCED CONCRETE PIPE PLAT PLAN

STA. 38807+87 (℄ SR29TH) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER V.15

10/18/2021 3:35:58 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V16 11x17_pdf.pltcfg

BENCH MARK NO. 100, ELEV. 904.541, N 601242.316, E 1613129.094, FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	6,600	V.P.D.
2050 AADT	-	V.P.D.
2050 DHV	-	V.P.H.
TRUCKS	29	%
TOTAL DESIGN ESALs	-	

LOCATION

SB I-35 TO EB I-80 - EXIST. LOOP RAMP F
T-79 N R-23 W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6492° N
LONGITUDE 93.5778° W


HYDRAULIC DATA

DRAINAGE AREA = 9.0 ACRES - ROLLING
Q_{50} = 24 CFS
HW ELEV. = 950.44

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	12.7	23.2	37
TOTALS	12.7	23.2	37

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL. E REVETMENT PER EC-301.



DESIGN FOR 0° SKEW LT. AHD.

30" X 106' (TRENCHLESS) REINFORCED CONCRETE PIPE PLAT PLAN

STA. 32584+11.43 (℄ Ramp B) NOVEMBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####


DESIGN TEAM Iowa DOT/HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER V.16

10/18/2021 3:36:06 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V17 11x17_pdf.pltcfg

BENCH MARK NO. 101, ELEV. 932.935, STA. 38606+52.11, 9727.41' LT., FENO MONUMENT



LONGITUDINAL SECTION ALONG ℄ CULVERT



PLAT PLAN

N

0 ENGLISH 40
SCALE IN FEET

TRAFFIC ESTIMATE

2012 AADT	N/A	V.P.D.
2050 AADT	N/A	V.P.D.
2050 DHV	N/A	V.P.H.
TRUCKS	N/A	%
TOTAL DESIGN ESALs	-	

LOCATION

CHICHAQUA VALLEY TRAIL
T-79 N R-23 W
SECTION 17
DELAWARE TOWNSHIP
POLK COUNTY
LATITUDE 41.6553° N
LONGITUDE 93.5606° W


HYDRAULIC DATA

DRAINAGE AREA = 15.9 ACRES - ROLLING
Q_{10} = 26 CFS
HW ELEV. = 897.21

ESTIMATED REVETMENT QUANTITIES INCLUDED WITH ROAD PLANS

LOCATION	REVETMENT CL. "E" (TON)	ENGINEERING FABRIC (SY)	EXCAVATION (CY)
INLET	XX	XX	XX
OUTLET	20.2	33.8	14.2
TOTALS	20.2	33.8	14.2

EXCAVATION QUANTITY CALCULATED FROM GRADING SURFACE. QUANTITIES SHOWN FOR INFORMATION ONLY AND ARE INCIDENTAL TO CL.E REVETMENT PER EC-301.



PRELIMINARY

DESIGN FOR 30° SKEW RT. AHD.

44" X 27" X 26' REINFORCED CONCRETE PIPE PLAT PLAN

STA. 20+85 (℄ CV TRAIL) NOVEMBER 2016

POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION

DESIGN SHEET NO. 1 OF 1 FILE NO. XXXXX DESIGN NO. ####

DESIGN TEAM	Iowa DOT/HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	V.17

10/18/2021 3:36:16 PM JWINKELM pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10195812\6.0_CAD_BIM\6.2_WIP\Bridge\77035194.str 77035194V20 11x17_pdf.pltcfg

MSE RETAINING WALL CONSTRUCTION NOTES

RW
SPECIAL

(1) The MSE Wall shall be designed for a 250 psf surcharge load to account for traffic live loads.

(2) The MSE Wall shall be designed to accommodate the sloped backfill as shown on the cross sections.

(3) The MSE wall shall be designed according to Iowa Department of Transportation standard specifications and AASHTO LRFD Bridge Design Specification.

(4) The permanent wall shall be designed for a minimum service life of 75 years.

(5) The minimum depth of embedment for the MSE wall is 4.0 feet.

(6) The length of the reinforcement strips (or mesh) will vary by wall station and shall be based on a minimum width to wall height ratio of 0.8 or 8 feet, whichever is greater.

(7) The Contractor is responsible for ensuring the stability of the 1:1 temporary excavation slope. The Contractor shall provide the Iowa DOT Resident Construction Engineer with supporting calculations if a slope other than 1:1 or temporary excavation support is needed.

(8) The panels for the MSE Wall shall be cast as per the MSE Wall Details on Sheet V.18.

(9) Two MSE Wall subdrains are required; one directly behind the wall panels and one at the back of the reinforced zone (see MSE Wall Details on Sheet V.19).


(10) For estimating purposes only, the following assumptions were used:
(a) The wall height at a given station is the distance between the top elevation of the leveling pad and the elevation of the top of coping of the MSE wall.
(b) The quantities of the granular backfill material and/or the excavation behind the wall were calculated based on the average end area between cross sections. The average end area was computed with the estimated wall heights and reinforcement lengths. These quantities may need to be adjusted if the required reinforcement length is greater than the estimated length, and/or if the footing elevation is adjusted.

(11) The Contractor shall notify the Engineer if rip rap, boulders, unsuitable soil or miscellaneous fill material is encountered at the bottom of the MSE wall footing excavation.


(12) The Contractor shall submit 7 copies of the design computations and 7 copies of the MSE Wall shop drawings at least 4 weeks prior to construction for review. The submittal with cover letter shall be sent to:

Soils Design Section
Iowa Department of Transportation
Attn: Steve Megivern, P.E.
800 Lincoln Way Ames, Iowa 50010


Only copies of the submittal cover letter shall be sent to the applicable office(s) of the Resident Construction Engineer (RCE) and District Materials Engineer (DME) for their information and documentation that the plans have been submitted. The Soils Design section will distribute final approved documents to the RCE and DME.




PANEL LAPPING DETAILS




PANEL DIMENSIONS




RUSTICATION DIMENSIONS




COPING ELEVATION



SECTION



REINFORCING




TYPICAL REINFORCING

TYPICAL M.S.E. COPING SECTION

COPING DETAILS

(Joints for the coping shall be designed to accommodate settlement in the MSE wall. This will be incidental to the design of the MSE wall.)

M.S.E. RETAINING WALL DETAILS (SHEET 1 OF 2)



LEGEND

Granular Backfill

NOTES

Refer to Q Sheets for additional details.

Class 10 Excavation included on T Sheets.

Granular Backfill must meet specification 2432.


Refer to Wall Plan and Profile Sheets for Bottom of Wall Elevations

TYPICAL MSE WALL BACKFILL


M.S.E. RETAINING WALL DETAILS (SHEET 2 OF 2)

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER V.19	

1:54:13 PM 10/18/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194V01.sht




MSE WALL ALONG RAMP B




	132582	132583	132584	132585	132586
PROPOSED TOP OF WALL ELEVATIONS	956.85	957.04 957.22 957.35	957.48 957.60	957.73 957.84	957.91 957.90 957.84 957.75
PROPOSED GROUND ELEVATIONS AT FACE OF WALL	948.52	948.12 947.90	947.68 947.45	947.25 947.06	946.87 947.53 948.98 950.69

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER V.20

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.



LONGITUDINAL SECTION ALONG ℄ I-35 NORTH



SITUATION PLAN


BERM SLOPE LOCATION TABLE						
POINTS	SOUTH ABUTMENT			NORTH ABUTMENT		
	STATION	OFFSET	ELEV.	STATION	OFFSET	ELEV.
A1	8478+85.39	40.58' LT.	934.14	8504+44.31	40.58' LT.	953.71
A2	8478+84.51	16.58' RT.	936.84	8504+45.88	16.58' RT.	952.71
B1	8478+42.22	40.58' LT.	950.89	8504+81.22	40.58' LT.	963.95
B2	8478+42.22	16.58' RT.	953.96	8504+81.22	16.58' RT.	967.02
W1	8478+11.66	40.58' LT.	961.68	8505+12.40	40.58' LT.	974.68
W2	8478+12.50	16.58' RT.	964.64	8505+11.40	16.58' RT.	977.74

BERM SLOPE ELEVATIONS REFLECT THE GRADING SURFACE

UTILITIES LEGEND:

-E2- ELECTRIC - IDOT
-FO3- FIBER OPTIC - ICN/IDOT (WINDSTREAM)

0 ENGLISH 40
SCALE IN FEET



INTERCHANGE KEY PLAN

LOCATION

I-35 NORTH OVER
I-80, I-235 & SYSTEM
INTERCHANGE RAMPS
T-79N R-23W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
FHWA NO. 700885
BRIDGE MAINT. NO. XXXXX
LATITUDE 41.652178°
LONGITUDE -93.576116°

TRAFFIC ESTIMATE

2012 AADT	12,300	V.P.D.
2050 AADT	15,800	V.P.D.
2050 DHV	1,990	V.P.H.
TRUCKS	18	%
TOTAL DESIGN ESALs	-	

N

NOTES:
ALL UNITS ARE IN FEET UNLESS NOTED OTHERWISE.
ALL DIMENSIONS ARE IN THE HORIZONTAL PLANE UNLESS NOTED OTHERWISE.
FOR VERTICAL PROFILE AND HORIZONTAL CURVE DATA, SEE SHEET V.28.
NON-STANDARD ABUTMENT WING-WALL.
TL-5 BRIDGE RAILING PROPOSED.
ADDITIONAL BRIDGE AESTHETICS TO BE INCORPORATED DURING FINAL DESIGN.
* MEASURED TO LOCAL TANGENTS
** EXISTING RAMP MOVEMENT TO BE REMOVED AFTER PROPOSED RAMP MOVEMENT CONSTRUCTED.

NOTES TO DESIGNERS:
MINIMUM HORIZONTAL CLEARANCE AND CLEAR ZONE FOR FUTURE EXPANSION:
I-80, I-35, I-235,I-35 NORTH (EB TO NB) &
I-35 SOUTH (SB TO WB) = 36' FROM LANE LINE
RAMP "G" (WB TO SB), RAMP "A" (WB TO NB),
RAMP "F" (SB TO EB), RAMP "D" (NB TO EB) &
RAMP "B" (EB TO SB) = 32' FROM LANE LINE
RAMP "E" (NB TO WB)
(OUTSIDE OF LOOP) = 22' FROM LANE LINE
(AT LOOP) = 16' FROM LANE LINE

HORIZONTAL CLEARANCES TO PIERS WERE BASED ON AN ASSUMED PIER WIDTH OF 6 FEET AND, WHERE APPLICABLE, THE SLOPING PIER COLUMN.
MINIMUM HORIZONTAL CLEARANCE TO PIER NOS. 2, 3, 4 AND 11 IS LESS THAN 30'. THEREFORE, DESIGN PIER NOS. 2, 3, 4 AND 11 FOR VEHICULAR COLLISION FORCE.
EXISTING ROADS LABELED "TO REMAIN OPEN" MAY BE BARRIER PROTECTED WITH THE FACE OF BARRIER AT THE BACK OF EXISTING SHOULDER.
SUBSTRUCTURE TO BE STUB TYPE ABUTMENTS AND AESTHETIC DELTA PIERS. AESTHETIC TREATMENTS TO BE ESTABLISHED BY IOWA DOT AESTHETICS BRIDGE SPECIALIST.
EXPANSION JOINTS AT SOUTH ABUTMENT, PIER NO. 9 AND NORTH ABUTMENT TO BE MODULAR JOINTS. EXPANSION JOINT AT PIER NO. 6 TO BE EITHER MODULAR OR FINGER JOINT.

PRELIMINARY

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 1 OF 8 FILE NO. 31046 DESIGN NO. 1918


DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.21

12/23/2016 11:06:33 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_01 11x17c_pdf.pltcfg

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.



LONGITUDINAL SECTION ALONG ℄ I-35 NORTH



MINIMUM VERTICAL CLEARANCE (PT. A)

OVERHEAD STATION = 8482+47.51, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 979.33
DEPTH OF SUPERSTRUCTURE = 8.50'
UNDERPASS STATION = 3082+21.33, 60.00' RT. (FUTURE I-80 E.B.)
UNDERPASS ELEVATION = 939.02
MINIMUM VERTICAL CLEARANCE = 31.81'

MINIMUM VERTICAL CLEARANCE (PT. B)

OVERHEAD STATION = 8483+23.32, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 982.32
DEPTH OF SUPERSTRUCTURE = 8.50'
UNDERPASS ELEVATION = 940.39 (EXISTING I-80 E.B.)
MINIMUM VERTICAL CLEARANCE = 33.43'

MINIMUM VERTICAL CLEARANCE (PT. C)

OVERHEAD STATION = 8486+32.45, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 993.67
DEPTH OF SUPERSTRUCTURE = 8.50'
EXISTING UNDERPASS ELEVATION = 968.10 (EXISTING S.B. TO E.B. LOOP RAMP)
MINIMUM VERTICAL CLEARANCE = 17.07'

NOTE:
* MEASURED TO LOCAL TANGENTS.
** EXISTING RAMP MOVEMENT TO BE REMOVED AFTER PROPOSED RAMP MOVEMENT CONSTRUCTED.

SITUATION PLAN

INTERCHANGE KEY PLAN

PRELIMINARY

0 ENGLISH 40
SCALE IN FEET

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 2 OF 8 FILE NO. 31046 DESIGN NO. 1918


DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.22

12/23/2016 11:07:44 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_02 11x17c_pdf.pltcfg

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.



LONGITUDINAL SECTION ALONG ℄ I-35 NORTH




SITUATION PLAN

MINIMUM VERTICAL CLEARANCE (PT. D)

OVERHEAD STATION = 8487+71.46, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 996.97
DEPTH OF SUPERSTRUCTURE = 8.50'
EXISTING UNDERPASS ELEVATION = 961.52 (EXISTING W.B. TO S.B. RAMP)
MINIMUM VERTICAL CLEARANCE = 26.95'

NOTE:
** EXISTING RAMP MOVEMENT TO BE REMOVED AFTER PROPOSED RAMP MOVEMENT CONSTRUCTED.



INTERCHANGE KEY PLAN

0 ENGLISH 40
SCALE IN FEET

PRELIMINARY

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION


DESIGN SHEET NO. 3 OF 8 FILE NO. 31046 DESIGN NO. 1918

HDR


DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.23

12/23/2016 11:08:02 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_03 11x17c_pdf.pltcfg

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.



LONGITUDINAL SECTION ALONG ℄ I-35 NORTH



SITUATION PLAN

NOTE:
* MEASURED TO LOCAL TANGENTS.

MINIMUM VERTICAL CLEARANCE (PT. E)


OVERHEAD STATION = 36634+67.28, 34.50' LT. (℄ FUTURE RAMP F)
OVERHEAD ELEVATION = 1031.13
DEPTH OF SUPERSTRUCTURE = 10.00'
UNDERPASS STATION = 8492+57.96, 12.00' RT. (℄ I-35 NORTH)
UNDERPASS ELEVATION = 1004.09
MINIMUM VERTICAL CLEARANCE = 17.04

MINIMUM VERTICAL CLEARANCE (PT. F)

OVERHEAD STATION = 8492+90.11, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 1001.40
DEPTH OF SUPERSTRUCTURE = 10.00'
UNDERPASS STATION = 2061+56.51, 39.00' LT. (℄ EXISTING I-35/I-235)
UNDERPASS ELEVATION = 971.47
MINIMUM VERTICAL CLEARANCE = 19.93'

MINIMUM VERTICAL CLEARANCE (PT. G)

OVERHEAD STATION = 8494+01.76, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 1001.31
DEPTH OF SUPERSTRUCTURE = 10.00'
UNDERPASS STATION = 2062+32.17, 39.00' RT. (℄ EXISTING I-35/I-235)
UNDERPASS ELEVATION = 971.92
MINIMUM VERTICAL CLEARANCE = 19.39'



INTERCHANGE KEY PLAN

0 ENGLISH 40
SCALE IN FEET

PRELIMINARY

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 4 OF 8 FILE NO. 31046 DESIGN NO. 1918

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.24

12/23/2016 11:08:16 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_04 11x17c_pdf.pltcfg

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.



LONGITUDINAL SECTION ALONG ℄ I-35 NORTH

MINIMUM VERTICAL CLEARANCE (PT. H)


OVERHEAD STATION = 8498+36.78, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 996.44
DEPTH OF SUPERSTRUCTURE = 8.50'
UNDERPASS ELEVATION = 943.10 (EXISTING I-80 W.B.)
MINIMUM VERTICAL CLEARANCE = 44.84'

MINIMUM VERTICAL CLEARANCE (PT. I)

OVERHEAD STATION = 8498+45.60, 34.50' LT. (℄ I-35 NORTH)
OVERHEAD ELEVATION = 996.26
DEPTH OF SUPERSTRUCTURE = 8.50'
UNDERPASS STATION = 4095+34.85, 60.00' LT.
(FUTURE I-80 W.B.)
UNDERPASS ELEVATION = 943.59
MINIMUM VERTICAL CLEARANCE = 44.17'

MINIMUM VERTICAL CLEARANCE (PT. J)

OVERHEAD STATION = 8500+27.51, 34.50' LT. (℄I-35 NORTH)
OVERHEAD ELEVATION = 992.03
DEPTH OF SUPERSTRUCTURE = 8.50'
EXISTING UNDERPASS ELEVATION = 966.51
MINIMUM VERTICAL CLEARANCE = 17.02'



SITUATION PLAN

INTERCHANGE KEY PLAN

NOTES:
* MEASURED TO LOCAL TANGENTS.
** EXISTING RAMP MOVEMENT TO BE REMOVED AFTER PROPOSED RAMP MOVEMENT CONSTRUCTED.

PRELIMINARY

0 ENGLISH 40
SCALE IN FEET

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY


IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 5 OF 8 FILE NO. 31046 DESIGN NO. 1918


DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.25

12/23/2016 11:08:30 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_05 11x17c_pdf.pltcfg


BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.




LONGITUDINAL SECTION ALONG ℄ I-35 NORTH




SITUATION PLAN



TYPICAL APPROACH SECTION





INTERCHANGE KEY PLAN

PRELIMINARY

0 ENGLISH 40
SCALE IN FEET

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY
IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 6 OF 8 FILE NO. 31046 DESIGN NO. 1918

HDR

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.26

12/23/2016 11:08:43 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_06 11x17c_pdf.pltcfg

N

EXISTING TWIN 218'-8 x 61'-4 CONTINUOUS WELDED GIRDER BRIDGES, POLK DESIGN NO. 4906

℄ FUTURE I-35 SOUTH

EXISTING 332'-0 x 26'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 209

EXISTING N.B. TO W.B. LOOP

℄ RAMP A

EXISTING 302'-0 x 26'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 2308

EXISTING 304'-0 x 26'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 2408

℄ FUTURE I-80 W.B.

℄ EXISTING I-80

EXISTING E.B. TO N.B. RAMP

℄ FUTURE I-80 E.B.

EXISTING W.B. TO S.B. RAMP

℄ NE 22ND STREET

℄ I-35 NORTH

EXISTING 322'-0 x 28'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 4358

EXISTING 319'-0 x 26'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 309

℄ FUTURE RAMP F

EXISTING 330'-0 x 26'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 2208

EXISTING TWIN 218'-8 x 61'-4 CONTINUOUS WELDED GIRDER BRIDGES, POLK DESIGN NO. 4806

℄ FUTURE RAMP D

℄ EXISTING I-35/I-235

EXISTING 304'-0 x 26'-0 CONTINUOUS WELDED GIRDER BRIDGE, POLK DESIGN NO. 109

EXISTING E.B. TO S.B. RAMP (TO BE REMOVED)

EXISTING S.B. TO E.B. LOOP RAMP

℄ RAMP B

℄ FUTURE RAMP G

SITE PLAN

0 ENGLISH 200
SCALE IN FEET

PRELIMINARY

DESIGN FOR 0° SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN - SITE

STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016


POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION


DESIGN SHEET NO. 7 OF 8 FILE NO. 31046 DESIGN NO. 1918

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(195)87--13-77 | SHEET NUMBER V.27


12/23/2016 11:09:05 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_07 11x17c_pdf.pltcfg




TYPICAL SECTION - UNITS 1 & 3




TYPICAL SECTION - UNIT 2




CAP PLAN



FUTURE I-80 E.B. PROPOSED GRADE



I-35 NORTH



FUTURE I-80 W.B. PROPOSED GRADE



RAMP F PROPOSED GRADE




I-35 NORTH PROPOSED GRADE

I-35 NORTH
SUPERELEVATION DIAGRAM

℄ I-35 NORTH

PI STA. 8479+25.90	PI STA. 8499+65.23
Δ = 46°54'31.73" (LT.)	Δ = 59°52'18.89" (LT.)
T = 577.04'	T = 765.90'
L = 1088.89'	L = 1389.80'
E = 119.79'	E = 204.76'
R = 1330.00'	R = 1330.00'
PC STA. 8473+48.85	PC STA. 8491+99.33
PT STA. 8484+37.74	PT STA. 8505+89.13



ELEVATION

SIDE ELEVATION

TYPICAL PIER DETAILS

PRELIMINARY

DESIGN FOR VARIABLE SKEW RADIUS = 1,330'

2650'-0 X 48'-0 CONTINUOUS WELDED GIRDER BRIDGE

UNIT 1: 170'-0, 200'-0, 240'-0, 235'-0, 160'-0, 132'-0
UNIT 2: 210'-0, 299'-0, 230'-0
UNIT 3: 184'-0, 210'-0, 210'-0, 170'-0

SITUATION PLAN - MISC.


STA. 8491+61.72 (℄ I-35 NORTH) OCTOBER 2016

POLK COUNTY
IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION


DESIGN SHEET NO. 8 OF 8 FILE NO. 31046 DESIGN NO. 1918

DESIGN TEAM HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(195)87--13-77	SHEET NUMBER V.28

12/23/2016 11:09:22 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_1918_08 11x17c_pdf.pltcfg



LONGITUDINAL SECTION ALONG ℄ RAMP B




TYPICAL APPROACH SECTION

SITUATION PLAN

UTILITIES LEGEND:

POWER POLE - MIDAMERICAN



INTERCHANGE KEY PLAN

0 ENGLISH 40
SCALE IN FEET

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.

BERM SLOPE LOCATION TABLE

POINTS	NORTH ABUTMENT			SOUTH ABUTMENT		
	STATION	OFFSET	ELEV.	STATION	OFFSET	ELEV.
A1	32590+63.59	24.58' LT.	945.10	32592+14.11	24.58' LT.	943.64
A2	32590+63.69	12.58' RT.	944.41	32592+15.59	12.58' RT.	944.58
B1	32590+40.59	24.58' LT.	954.44	32592+42.86	24.58' LT.	955.43
B2	32590+38.51	12.58' RT.	954.44	32592+44.94	12.58' RT.	955.43
W1	32590+27.56	24.58' LT.	961.05	32592+55.88	24.58' LT.	962.10
W2	32590+25.61	12.58' RT.	959.75	32592+57.84	12.58' RT.	960.81

BERM SLOPE ELEVATIONS REFLECT THE GRADING SURFACE

G1 = +0.652% — G2 = -0.070%

VPI STA. = 32592+00.00
VPI ELEV. = 961.37
VC = 200'

RAMP B PROPOSED GRADE

℄ RAMP B CURVE DATA

PI STA. 32590+41.99
Δ = 31°51'07.08" (RT.)
T = 519.33'
L = 1,011.78'
E = 72.65'
R = 1,820.00'
PC STA. 32585+22.66
PT STA. 32595+34.44

MINIMUM VERTICAL CLEARANCE (PT. A)

OVERHEAD STATION = 32591+07.48, 6.08' RT. (℄ RAMP B)
OVERHEAD ELEVATION = 960.49
DEPTH OF SUPERSTRUCTURE = 3.83'
UNDERPASS ELEVATION = 932.50
PROVIDED MIN. VERTICAL CLEARANCE = 24.16'

LOCATION

RAMP B (E.B. TO S.B.)
OVER UPRR
T-79N R-23W
SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
FHWA NO. 700895
BRIDGE MAINT. NO. UNKNOWN
LATITUDE: 41.647150°
LONGITUDE: -93.577130°

TRAFFIC ESTIMATE

2012 AADT	5200	V.P.D.
2050 AADT	6400	V.P.D.
2050 DHV	1030	V.P.H.
TRUCKS	13	%
TOTAL DESIGN ESALs	-	

NOTES:
ALL UNITS ARE IN FEET UNLESS NOTED OTHERWISE.
ALL DIMENSIONS ARE IN THE HORIZONTAL PLANE UNLESS NOTED OTHERWISE.
"BTB" BEAMS ARE CHORDED AT STANDARD BEAM SPAN LENGTHS OF 65', 75' AND 70'.
* MEASURED FROM PHOTOGRAMMETRY FILE, VERIFY DURING FINAL DESIGN.
** MEASURED TO LOCAL TANGENT OF ℄ RAMP B.
RAILROAD DITCHES ARE NOT WELL DEFINED, BUT GENERALLY FLOW WESTWARD.

NOTES TO DESIGNERS:
BRIDGE SUPERSTRUCTURE TO BE PPC "BTB" BEAMS. SUBSTRUCTURE TO BE INTEGRAL ABUTMENTS AND FRAME PIERS.
MINIMUM HORIZONTAL CLEARANCE TO PIERS EXCEEDS 25' AS DEFINED IN THE AREMA MANUAL FOR RAILWAY ENGINEERING, THEREFORE, HEAVY CONSTRUCTION IS NOT REQUIRED.
HORIZONTAL CLEARANCE TO PIER BASED ON ASSUMED CAP WIDTH OF 4'.
TL-5 BRIDGE RAILING PROPOSED.
BRIDGE AESTHETICS TO BE INCORPORATED DURING FINAL DESIGN.
VERIFY RAILROAD EQUATION POINTS DURING FINAL DESIGN.

PRELIMINARY

DESIGN FOR VARIABLE SKEW RADIUS = 1,820'

214'-0 3/16 X 28'-0 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

66'-0 1/16, 77'-0 1/16, 71'-0 1/16 SPANS

SITUATION PLAN

STA. 32591+41.72 (℄ RAMP B) OCTOBER 2016

POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 1 OF 3 FILE NO. 31046 DESIGN NO. 2118

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(203)87--13-77 | SHEET NUMBER V.29

N

EXISTING 223'-0 x VARIES
PPCB BRIDGE, POLK DESIGN NO. 4706

℄ EXISTING I-235

EXISTING 223'-0 x VARIES
PPCB BRIDGE, POLK DESIGN NO. 4606

℄ RAMP G

℄ RAMP B

FUTURE 204'-0 x 42'-0 PPCB BRIDGE

EXISTING UPRR TRACK

38575

32590

38570


32595

38565

2040

2038

SIGN



TYPICAL SECTION

SITE PLAN

PRELIMINARY

DESIGN FOR VARIABLE SKEW RADIUS = 1,820'

214'-0 3/16 X 28'-0 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

66'-0 1/16, 77'-0 1/16, 71'-0 1/16 SPANS

SITUATION PLAN - SITE

STA. 32591+41.72 (℄ RAMP B) OCTOBER 2016

POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION


DESIGN SHEET NO. 2 OF 3 FILE NO. 31046 DESIGN NO. 2118

0 ENGLISH 80
SCALE IN FEET

HDR

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(203)87--13-77 | SHEET NUMBER V.30

12/23/2016 11:10:33 AM CPODANY pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\8.0_Deliverables\8.2_Work_in_Progress\Data_Out\161223_D5_Final\CADD\77035194.str TSL_77_2118_02 11x17c_pdf.pltcfg



GENERAL EXCAVATION ZONES

RAILROAD GENERAL NOTES:

1. RAILROAD REVIEW AND APPROVAL OF SHORING, ERECTION, DEMOLITION, AND FALSEWORK IS REQUIRED. ALLOW A MINIMUM OF FOUR WEEKS FOR THE REVIEW AND APPROVAL OF EACH SUBMITTAL.
2. THE PROPOSED GRADE SEPARATION PROJECT SHALL NOT INCREASE THE QUANTITY AND/OR CHARACTERISTICS OF THE FLOW IN THE RAILROAD'S DITCHES AND/OR DRAINAGE STRUCTURES.
3. THE ELEVATION OF THE EXISTING TOP-OF-RAIL PROFILE SHALL BE VERIFIED BEFORE BEGINNING CONSTRUCTION. ALL DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE RAILROAD PRIOR TO CONSTRUCTION.
4. THE CONTRACTOR MUST SUBMIT A PROPOSED METHOD OF EROSION AND SEDIMENT CONTROL AND HAVE THE METHOD APPROVED BY THE RAILROAD.
5. ALL SHORING SYSTEMS THAT IMPACT THE RAILROAD'S OPERATIONS AND/OR SUPPORTS THE RAILROAD'S EMBANKMENT SHALL BE DESIGNED AND CONSTRUCTED PER CURRENT RAILROAD GUIDELINES FOR TEMPORARY SHORING.
6. ALL DEMOLITIONS WITHIN THE RAILROAD'S RIGHT-OF-WAY AND/OR DEMOLITION THAT MAY IMPACT THE RAILROAD'S TRACKS OR OPERATIONS SHALL BE IN COMPLIANCE WITH THE RAILROAD'S DEMOLITION GUIDELINES.
7. ERECTION OVER THE RAILROAD'S RIGHT-OF-WAY SHALL BE DESIGNED TO CAUSE NO INTERRUPTION TO THE RAILROAD'S OPERATION, ENABLING THE TRACK(S) TO REMAIN OPEN TO TRAFFIC PER THE RAILROAD'S REQUIREMENTS.
8. ALL CONSTRUCTION PHASING THAT MAY IMPACT THE RAILROAD OPERATIONS SHALL BE DESIGNED TO CAUSE NO INTERRUPTION TO THE RAILROAD'S OPERATION, ENABLING THE TRACK(S) TO REMAIN OPEN TO TRAFFIC PER THE RAILROAD'S REQUIREMENTS.
9. FALSE-WORK CLEARANCES SHALL COMPLY WITH MINIMUM CONSTRUCTION CLEARANCES.
10. ALL PERMANENT CLEARANCES SHALL BE VERIFIED BEFORE PROJECT CLOSING.
11. FOR RAILROAD COORDINATION PLEASE REFER TO THE RAILROAD COORDINATION REQUIREMENTS AS PART OF SPECIAL PROVISIONS.

GENERAL SHORING NOTES:

1. ALL DIMENSIONS ARE MEASURED PERPENDICULAR TO TRACK.
2. PRIOR TO COMMENCING ANY WORK, THE CONTRACTOR SHALL SUBMIT FOR APPROVAL BY THE RAILROAD DETAILED PLANS INDICATING THE NATURE AND EXTENT OF THE TRACK PROTECTION SHORING PROPOSED. THE CONTRACTOR SHALL INSTALL THE TEMPORARY SHORING SYSTEM PER THE APPROVED PLANS. DESIGN OF THE TEMPORARY SHORING SYSTEM TO COMPLY WITH GUIDELINES FOR TEMPORARY SHORING.
3. FOR EXCAVATIONS WHICH ENCROACH INTO ZONE A OR B, SHORING PLANS SHALL BE ACCOMPANIED BY DESIGN CALCULATIONS. PLANS AND CALCULATIONS MUST BE SIGNED AND STAMPED BY A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF IOWA.

NOTE:
UPRR = UNION PACIFIC RAILROAD


TOP OF RAIL ELEVATIONS

(STATIONS INCREASE WITH MILEPOST INCREASE. MILEPOSTS INCREASE TO THE EAST.)

MAIN LINE UPRR			
ALIGNMENT: LEFT RAIL		ALIGNMENT: RIGHT RAIL	
STATION	ELEVATION	STATION	ELEVATION
03+77.02	926.94	03+75.41	926.92
04+25.71	927.58	04+23.95	927.52
04+73.02	928.15	04+71.26	928.02
05+16.50	928.79	05+15.05	928.70
05+69.44	929.26	05+67.59	929.35
06+32.30	929.76	06+30.50	929.69
06+81.56	930.13	06+79.77	930.14
07+30.59	930.60	07+28.66	930.61
07+80.50	930.89	07+78.70	930.90
08+03.03	931.08	08+01.10	931.09
08+23.34	931.25	08+21.06	931.26
08+50.47	931.47	08+48.68	931.47
08+85.15	931.73	08+83.34	931.73
09+35.24	932.13	09+33.34	932.17
09+87.12	932.53	09+85.29	932.60
(1) 10+00.00	932.65	(2) 10+00.00	932.75
10+40.71	933.03	10+39.06	933.14
10+90.64	933.50	10+88.97	933.61
11+36.11	933.88	11+34.18	934.04
11+86.69	934.34	11+85.24	934.58
12+37.31	934.77	12+35.68	935.00
12+87.08	935.13	12+85.79	935.32
13+38.50	935.32	13+36.96	935.63
13+91.30	935.66	13+89.90	936.01
14+40.28	936.26	14+38.98	936.41
14+63.06	936.44	14+60.58	936.55

(1) EXISTING TRACK STA. 10+00 = STA. 32591+34.79 ℄ RAMP B

(2) EXISTING TRACK STA. 10+00 = STA. 32591+39.99 ℄ RAMP B



MINIMUM CONSTRUCTION CLEARANCE ENVELOPE

(NORMAL TO RAILROAD)

* 12'-0" FOR UPRR

PRELIMINARY

DESIGN FOR VARIABLE SKEW RADIUS = 1,820'

214'-0 3/16 X 28'-0 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

66'-0 1/16, 77'-0 1/16, 71'-0 1/16 SPANS

UPRR SHORING DETAILS

STA. 32591+41.72 (℄ RAMP B) OCTOBER 2016


POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION


DESIGN SHEET NO. 3 OF 3 FILE NO. 31046 DESIGN NO. 2118

REVISED 09-13 - RAILROAD CHANGED THE MINIMUM VERTICAL CONSTRUCTION CLEARANCE TO 21'-6. DISTANCE FROM MAINLINE TRACK TO EDGE OF EMBANKMENT CHANGED TO 15'-6.
ENGLISH\MISCELLANEOUSBRIDGES.DGN - 1067 - THIS SHEET ISSUED 12-08.

DESIGN TEAM HDR	BNSF & UPRR GENERAL NOTES & SHORING	STANDARD SHEET 1067	POLK COUNTY	PROJECT NUMBER IM-035-3(203)87--13-77	SHEET NUMBER V.31




LONGITUDINAL SECTION ALONG ℄ RAMP G



SITUATION PLAN

0 ENGLISH 40
SCALE IN FEET

INTERCHANGE KEY PLAN




BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.

LOCATION

RAMP G OVER
EXISTING BROADWAY AVE.
T-79N R-23W
SECTION 18 / SECTION 19
DELAWARE TOWNSHIP
POLK COUNTY
FHWA NO. 700890
BRIDGE MAINT. NO. UNKNOWN
LATITUDE: 41.644118°
LONGITUDE: -93.576225°

TRAFFIC ESTIMATE

2012 AADT	13900	V.P.D.
2050 AADT	18500	V.P.D.
2050 DHV	2750	V.P.H.
TRUCKS	10	%
TOTAL DESIGN ESALs	-	



VPI STA. = 38560+00.00
VPI ELEV. = 962.04
VC = 350'

RAMP G PROPOSED GRADE

MINIMUM VERTICAL CLEARANCE (PT. A)

OVERHEAD STATION = 38559+90.54, 13.08' LT. (℄ RAMP G)
OVERHEAD ELEVATION = 960.90
DEPTH OF SUPERSTRUCTURE = 3.83'
UNDERPASS STATION = 1180+02.84, 0.00' (℄ EXISTING BROADWAY AVE.)
UNDERPASS ELEVATION = 941.14 (U.A.C.)
REQUIRED MIN. VERTICAL CLEARANCE = 15.00' (BASED ON EXISTING BROADWAY AVE.)
PROVIDED MIN. VERTICAL CLEARANCE = 15.93'

UTILITIES LEGEND:

- E1 — ELECTRIC - MIDAMERICAN
- E2 — ELECTRIC - IDOT
- G-HP — GAS LINE - MIDAMERICAN
- G-HP2 — GAS LINE - MIDAMERICAN
- POWER POLE - MIDAMERICAN
- W — CITY OF DES MOINES WATER WORKS

BERM SLOPE LOCATION TABLE

POINTS	SOUTH ABUTMENT			NORTH ABUTMENT		
	STATION	OFFSET	ELEV.	STATION	OFFSET	ELEV.
A1	38559+60.52	19.58' LT.	937.85	38560+23.00	19.58' LT.	937.98
A2	38559+50.97	34.58' RT.	941.98	38560+13.45	34.58' RT.	941.52
B1	38559+17.07	19.58' LT.	955.09	38560+66.93	19.58' LT.	955.18
B2	38559+07.52	34.58' RT.	955.09	38560+57.38	34.58' RT.	955.18
W1	38559+03.17	19.58' LT.	960.48	38560+79.21	19.58' LT.	960.57
W2	38558+95.23	34.58' RT.	961.33	38560+71.28	34.58' RT.	961.50

BERM SLOPE ELEVATIONS REFLECT THE GRADING SURFACE

NOTES:
ALL UNITS ARE IN FEET UNLESS NOTED OTHERWISE.
ALL DIMENSIONS ARE IN THE HORIZONTAL PLANE UNLESS NOTED OTHERWISE.

NOTES TO DESIGNERS:
BRIDGE SUPERSTRUCTURE TO BE PPC "BTB" BEAMS. SUBSTRUCTURE TO BE INTEGRAL ABUTMENTS AND FRAME PIERS.
MINIMUM HORIZONTAL CLEARANCE TO PIERS IS LESS THAN 30', THEREFORE, DESIGN PIERS FOR VEHICULAR COLLISION FORCE.
HORIZONTAL CLEARANCE TO PIER BASED ON ASSUMED CAP WIDTH OF 4'.
TL-5 BRIDGE RAILING PROPOSED.
BRIDGE AESTHETICS TO BE INCORPORATED DURING FINAL DESIGN.

PRELIMINARY

DESIGN FOR 10°00'00" SKEW (L.A.)

159'-0 X 45'-0 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

41'-0, 77'-0, 41'-0 SPANS

SITUATION PLAN

STA. 38559+88.54 (℄ RAMP G) OCTOBER 2016

POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 1 OF 2 FILE NO. 31046 DESIGN NO. 2018

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(196)87--13-77 | SHEET NUMBER V.32

N

SIGN

℄ EXISTING BROADWAY AVE.

℄ RAMP G

℄ I-235

38555

38560

38565


1179

1181

2030

2035

EXISTING DUAL 150'-10 x 56'-10 3/8
PPCB BRIDGES, POLK DESIGN NO. 905



TYPICAL SECTION

SITE PLAN

PRELIMINARY

DESIGN FOR 10°00'00" SKEW (L.A.)

159'-0 X 45'-0 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

41'-0, 77'-0, 41'-0 SPANS

SITUATION PLAN - SITE

STA. 38559+88.54 (℄ RAMP G) OCTOBER 2016

POLK COUNTY

IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION

DESIGN SHEET NO. 2 OF 2 FILE NO. 31046 DESIGN NO. 2018


0 ENGLISH 80
SCALE IN FEET

HDR

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(196)87--13-77 | SHEET NUMBER V.33

1/9/2018 3:25:47 PM cpodany pw:\\PWAPPOMA001:NorthCentral_Omaha\Documents\001210\CON0079631\0000000000237533\6.0_CAD_BIM\6.2_Work_in_Progress\Bridge\Submittal\12&slash;22&slash;2016\77035194.str TSL_77_2018_02 11x17c_pdf.pltcfg

BENCH MARK NO. 26: NORTHING: 604283.735, EASTING: 1624489.540, ELEV. 886.700
FENO. MONUMENT, W/CAP STAMPED "026", 6" DEEP, IN THE NORTH ROW/SHOULDER OF NE 54TH AVE., 9' NORTH OF EDGE AC SLAB; 128' FROM P.I. OF NE 54TH AVE. WITH OF RR CROSSING.




LONGITUDINAL SECTION ALONG ℄ RAMP G

LOCATION


RAMP G OVER
EXISTING NE 29TH ST.
T-79N R-23W
SECTION 17 / SECTION 18
DELAWARE TOWNSHIP
POLK COUNTY
FHWA NO. 700900
BRIDGE MAINT. NO. UNKNOWN
LATITUDE: 41.654763°
LONGITUDE: -93.561053°

TRAFFIC ESTIMATE


2012 AADT	N/A	V.P.D.
2050 AADT	22400	V.P.D.
2050 DHV	2620	V.P.H.
TRUCKS	18	%
TOTAL DESIGN ESALs	-	



CV TRAIL PROPOSED GRADE



RAMP G PROPOSED GRADE



SITUATION PLAN

℄ RAMP G CURVE DATA

PI STA. 38634+27.39
Δ = 4°57'40.47" (LT.)
T = 350.91'
L = 701.38'
E = 7.60'
R = 8100.00'
PC STA. 38630+76.49
PT STA. 38637+77.87

CV TRAIL CURVE DATA

PI STA. 16+96.28	PI STA. 17+16.67
Δ = 11°40'45.25" (LT.)	Δ = 11°40'45.25" (RT.)
T = 10.23'	T = 10.23'
L = 20.38'	L = 20.38'
E = 0.52'	E = 0.52'
R = 100.00'	R = 100.00'
PC STA. 16+86.06	PC STA. 17+06.44
PT STA. 17+06.44	PT STA. 17+26.82


MINIMUM VERTICAL CLEARANCE (PT. A)

OVERHEAD STATION = 38632+24.28, 22.88' LT. (℄ RAMP G)
OVERHEAD ELEVATION = 932.87
DEPTH OF SUPERSTRUCTURE = 4.58'
UNDERPASS STATION = 38806+44.80, 0.00' (℄ EXISTING NE 29TH ST.)
UNDERPASS ELEVATION = 911.39 (U.A.C.)
PROVIDED MIN. VERTICAL CLEARANCE = 16.90'

NOTES:
ALL UNITS ARE IN FEET UNLESS NOTED OTHERWISE.
ALL DIMENSIONS ARE IN THE HORIZONTAL PLANE UNLESS NOTED OTHERWISE.
* MEASURED TO LOCAL TANGENT OF ℄ RAMP G.
◕ MEASURED PERPENDICULAR TO LOCAL TANGENT OF ℄ RAMP G.
FINAL ALIGNMENT SHOWN FOR CV TRAIL. FOR TEMPORARY TRAIL ALIGNMENT REFER TO ROAD PLANS.
NOTES TO DESIGNERS:
BRIDGE SUPERSTRUCTURE TO BE PPCB "BTC" BEAMS. SUBSTRUCTURE TO BE INTEGRAL ABUTMENTS AND FRAME PIERS.
** BRIDGE BASELINE IS A CHORD LINE CONSTRUCTED FROM POINTS WHERE CENTERLINES OF BRIDGE ABUTMENT BEARINGS INTERSECT ℄ RAMP G.
MINIMUM HORIZONTAL CLEARANCE TO PIERS EXCEEDS 30', THEREFORE, PIERS ARE NOT REQUIRED TO BE DESIGNED FOR VEHICULAR COLLISION FORCE.
HORIZONTAL CLEARANCE TO PIER BASED ON ASSUMED CAP WIDTH OF 4'.
TL-5 BRIDGE RAILING PROPOSED.
BRIDGE AESTHETICS TO BE INCORPORATED DURING FINAL DESIGN.

PRELIMINARY

BRIDGE LOCATION



INTERCHANGE KEY PLAN

UTILITIES LEGEND:

—T1— TELEPHONE - CENTURY LINK
—FO2— FIBER OPTIC - CENTURY LINK
—FO3— FIBER OPTIC - ICN/IDOT (WINDSTREAM)
POWER POLE - MIDAMERICAN

0 ENGLISH 40
SCALE IN FEET

DESIGN FOR VARIABLE SKEW

209'-0 X 54'-10 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

51'-0, 97'-0, 61'-0 SPANS

SITUATION PLAN

STA. 38632+26.85 (℄ RAMP G) APRIL 2021


POLK COUNTY


IOWA DOT - TRANSPORTATION DEVELOPMENT DIVISION

DESIGN SHEET NO. 1 OF 2 FILE NO. 31046 DESIGN NO. 2218

DESIGN TEAM HDR	POLK COUNTY PROJECT NUMBER IM-080-4(70)139--13-77	SHEET NUMBER V.34

4/8/2021 3:51:02 PM ESORENS pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10196490\6.0_CAD_BIM\6.2_WIP\TS&L\2218 Updated TS&L\77035194.str TSL_77_2218_01 11x17c_pdf.pltcfg





TYPICAL SECTION

SITE PLAN

BERM SLOPE LOCATION TABLE						
POINTS	WEST ABUTMENT			EAST ABUTMENT		
	STATION	OFFSET	ELEV.	STATION	OFFSET	ELEV.
A1	38631+64.72	29.14' LT.	913.75	38632+91.30	29.13' LT.	910.25
A2	38631+61.08	34.89' RT.	913.47	38632+86.45	34.84' RT.	910.75
B1	38631+28.67	28.79' LT.	927.88	38633+29.36	28.74' LT.	924.01
B2	38631+24.66	35.28' RT.	927.88	38633+23.78	35.20' RT.	924.01
W1	38631+10.25	28.55' LT.	934.12	38633+47.09	28.49' LT.	929.74
W2	38631+07.07	35.51' RT.	935.27	38633+42.05	35.44' RT.	931.02

BERM SLOPE ELEVATIONS REFLECT THE GRADING SURFACE

PRELIMINARY

0 ENGLISH 80
SCALE IN FEET

DESIGN FOR VARIABLE SKEW

209'-0 X 54'-10 PRETENSIONED PRESTRESSED CONCRETE BEAM BRIDGE

51'-0, 97'-0, 61'-0 SPANS

SITUATION PLAN - SITE

STA. 38632+26.85 (℄ RAMP G) APRIL 2021

POLK COUNTY

IOWA DOT - TRANSPORTATION DEVELOPMENT DIVISION

DESIGN SHEET NO. 2 OF 2 FILE NO. 31046 DESIGN NO. 2218

DESIGN TEAM HDR | POLK COUNTY | PROJECT NUMBER IM-080-4(70)139--13-77 | SHEET NUMBER V.35

4/8/2021 3:51:05 PM ESORENS pw:\\pwhdruscen01:HDR_US_Central_01\Documents\3047\10196490\6.0_CAD_BIM\6.2_WIP\TS&L\2218 Updated TS&L\77035194.str TSL_77_2218_02 11x17c_pdf.pltcfg

LINE STYLE LEGEND OF CROSS SECTION SHEETS (ROAD)

- Existing Ground Line
- Proposed Template
- Proposed Topsoil Placement
- Additional Topsoil Removal
- Subgrade Treatment
- Granular Shoulder
- Pavement
- Existing Pipe\RCB
- Proposed Pipe\RCB
- Proposed Dike
- All Elements Associated with Proposed Entrances

LINE STYLE LEGEND OF CROSS SECTION SHEETS (SOILS)

- TS — Topsoil (Class 10)
- SLOPE DRESSING — Slope Dressing Only
- CL 10 — Class 10 Materials
- SEL LO — Select Loams And Clay-Loams
- SEL SA — Select Sand
- UNS A — Unsuitable Type A Disposal
- UNS B — Unsuitable Type B Disposal
- UNS C — Unsuitable Type C Disposal
- SHALE — Shale
- WASTE — Waste
- B&W LS — Broken and Weathered Rock
- ROCK — Solid Rock
- BLDRS — Boulders

Note: All layer lines and descriptions identify layers above the line.

Note: Vertical or near vertical lines connecting soil layers at edges of cross sections are only for the purpose of calculating template quantities and do not depict soil stratification.

SYMBOL LEGEND OF CROSS SECTION SHEETS

Existing ROW — Existing Right-of-Way Limit


Proposed ROW — Proposed Right-of-Way Limit

Temporary ROW — Temporary Right-of-Way Limit

CROSS SECTION LEGEND AND SYMBOL INFORMATION SHEET

(COVERS SHEET SERIES W, X, Y, & Z)


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.2

8:23:23 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.3

8:23:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.4

8:23:27 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.5

8:23:28 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.6

8:23:30 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.7

8:23:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.8

8:23:33 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.9

8:23:35 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary

8474+00.00

8473+50.00


8473+00.00

Existing ROW

| | | |

ML035N

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.11

8:23:38 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

8476+05.43

8476+00.00

8475+50.00

Existing ROW

Pro F

Prop Rt

FILE NO. | ENGLISH | DESIGN TEAM Iowa DOT\HDR | POLK COUNTY | PROJECT NUMBER IM-035-3(194)87--13-77 | SHEET NUMBER W.12

8:23:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

8477+50.00

961.50 0.00
959.11 32.00
Existing ROW
960.38 26.50
955.62 56.28
957.56 24.00
958.28 12.00
959.00 0.00
949.66 65.10
927.75 165.01
927.56 164.44
927.56 154.44

8477+00.00

959.50 0.00
Existing ROW
957.96 32.00
958.35 29.67
953.40 59.92
955.56 24.00
956.28 12.00
957.00 0.00
950.32 59.48
932.23 134.00

8476+50.00

957.50 0.00
Existing ROW
954.90 32.00
955.99 25.44
950.85 46.19
951.41 59.68
953.56 24.00
954.28 12.00
956.00 0.00
934.52 118.81
930.92 166.86
931.30 199.20

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.13

8:23:41 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

970 960 950 940 930

965.50
0.00

8478+50.00

964.97
0.00

8478+36.71

956.59
56.00

957.87
52.10

959.56
24.00

960.28
12.00

961.00
0.00

963.50
0.00

962.39
23.80

959.81
32.00

950.94
60.07

933.62
128.16

Existing
ROW

8478+00.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.14

8:23:43 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary

8480+00.00

971.50
0.00

940.00
63.96

947.77
87.27

933.96
183.10

969.50
0.00

8479+50.00

967.50
0.00

933.97
200.35

3.00
3.31

8479+00.00

934.00
214.81

936.39
169.72

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.15

8:23:44 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

980 970 960 950 940 930

975.50
0.00

933.96
136.61

938.84
13.54

8481+00.00

973.50
0.00

940.00
60.28

942.34
67.89

8480+50.00

940 930

933.94
162.79

190 180 170 160 150

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.16

8:23:45 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

990 980 970 960 950 940 930

979.50
0.00

15.76
10.86

.00
1.55

8482+00.00

977.50
0.00

.99
1.23

137.12
19.64

8481+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.17

8:23:47 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

990 980 970 960 950 940 930

983.49
0.00

8483+00.00

981.50
0.00

8482+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.18

8:23:48 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

990 980 970 960 950 940 930

985.97
0.00

8483+65.74

985.39
0.00

8483+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.19

8:23:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1000 990 980 970 960 950 940 930

988.91
0.00

8484+50.00

987.20
0.00


8484+00.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.20

8:23:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.21

8:23:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1000 990 980 970 960 950 940

993.49
0.00

8486+00.00

992.06
0.00

8485+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.22

8:23:54 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1000 990 980 970 960 950

996.06
0.00

8487+00.00

994.82
0.00

8486+50.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.23

8:23:55 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010 1000 990 980 970 960 950 940 930

998.25
0.00

8488+00.00

997.20
0.00


8487+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.24

8:23:56 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary



8489+00.00



8488+50.00


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.25

8:23:58 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940



8490+00.00



8489+50.00


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.26

8:23:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940



8491+00.00



8490+50.00


FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.27

8:24:00 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940



8491+50.00




8491+11.33

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.28

8:24:02 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.29

8:24:03 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010 1000 990 980 970 960 950

1003.49
0.00

8493+00.00

1003.44
0.00


8492+71.33

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.30

8:24:21 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.31

8:24:23 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940



8495+00.00




8494+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.32

8:24:24 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.33

8:24:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940

1000.82
0.00

8497+00.00

1001.49
0.00

8496+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.34

8:24:27 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940

999.20
0.00

8498+00.00

1000.06
0.00

8497+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.35

8:24:28 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

1010
1000
990
980
970
960
950
940

997.20
0.00

8499+00.00


998.25
0.00

8498+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.36

8:24:29 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.37

8:24:31 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.38

8:24:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

990 980 970 960 950

985.39
0.00

8503+00.00

1000 990 980 970 960

987.20
0.00

8502+50.00

1000 990 980 970 960

988.91
0.00

8502+00.00

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.39

8:24:34 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

990 980 970 960 950

979.50
0.00

8504+50.00

981.50
0.00

8504+00.00


983.49
0.00

8503+50.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.40

8:24:35 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.41

8:24:36 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

980 970 960 950 940

955.14
140.52

951.91
130.82

951.91
120.82

969.44
59.53

971.56
24.00

972.28
12.00

975.50
0.00

973.00
0.00

974.11
25.13

972.96
32.00

961.61
71.74

8505+50.00

980 970 960 950 940

955.14
128.65

952.07
119.44

952.07
109.44

969.72
56.00

971.24
51.48

972.87
24.00

973.59
12.00

976.81
0.00

974.31
0.00

975.54
23.48

972.85
32.00

956.45
82.00

8505+17.13

990 980 970 960 950 940

955.17
122.65

952.16
113.63

952.16
103.63

973.56
24.00

974.28
12.00

977.50
0.00

975.00
0.00

8505+00.00


140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR		POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.42

8:24:38 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.43


8:24:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.44


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.45

8:24:42 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.46

8:24:44 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.47

8:24:45 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML035N
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.48

8:24:46 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.49

8:24:48 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.50

8:24:49 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.51

8:24:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.52

8:24:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.53

8:24:54 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.54

8:24:55 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.55

8:24:57 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.56

8:24:58 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.57

8:25:00 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.58

8:25:01 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.59

8:25:03 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML035N


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.60

8:25:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML235
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.61

8:25:06 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML235
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.62

8:25:07 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML235
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.63

8:25:08 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML235
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.64

8:25:10 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht


ML235
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.65

8:25:11 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.66

8:25:13 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.67

8:25:14 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.68

8:25:15 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.69

8:25:17 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.70

8:25:18 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.71

8:25:19 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML235

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.72

8:25:21 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

930 920 910 900 890 880

888.72
257.60

887.74
254.67

887.73
244.66

Existing
ROW

913.45
154.06

914.54
125.91

914.88
113.89

915.22
101.88

915.57
89.86

916.37
63.00

916.73
48.00

919.17
51.00
918.23
48.00
918.34
43.47
918.06
43.47

5138+00.00

889.18
256.59

888.47
254.46

888.45
244.45

Existing
ROW

914.12
154.05

915.20
125.91

915.55
113.89

915.89
101.88

916.23
89.86

917.04
63.00

917.39
48.00

919.84
51.00
918.90
48.00
918.88
43.48
918.56
43.48

5137+77.87

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.73

8:25:22 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

920 910 900 890 880

sed

Existing ROW

885.10
251.25

884.74
250.19

884.73
240.18

910.60
149.06

911.68
120.91

912.03
108.89

912.37
96.88

912.72
84.86

913.37
63.00

913.73
48.00

916.17
51.00

915.23
48.00

915.31
44.00

915.35
42.93

5139+00.00

930 920 910 900 890 880

ed

Existing ROW

886.85
234.24

886.24
232.43

886.23
242.42

912.03
151.56

913.11
123.41

913.46
111.39

913.80
99.38

914.14
87.36

914.87
63.00

915.23
48.00

917.67
51.00

916.73
48.00

916.81
44.00

916.85
43.20

5138+50.00


260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.74

8:25:24 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.75

8:25:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

920 910 900 890 880 870

Proposed ROW

879.05
244.42

977.25
239.01

Existing ROW

877.23
229.00

903.48
136.56

904.56
108.41

904.91
96.39

905.25
84.38

905.69
72.36

905.87
63.00

906.23
48.00

908.67
51.00
907.93
48.00
907.81
42.72

5141+50.00

Proposed ROW

881.06
248.18

878.74
241.25

Existing ROW

878.73
231.24

904.90
139.06

905.99
110.91

906.33
98.89

906.67
86.88

907.02
74.86

907.37
63.00

907.73
48.00

910.17
51.00
909.23
48.00
909.31
42.70

5141+00.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.76

8:25:27 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

910 900 890 880 870

Proposed ROW

Existing ROW

877.16
240.03

874.74
232.78

874.74
222.75

900.63
131.56

901.71
103.41

902.06
91.39

902.40
79.38

902.74
67.36

902.87
63.00

903.23
48.00

905.67
51.00
904.73
48.00
904.81
42.50

5142+50.00

920 910 900 890 880 870

Proposed ROW

Existing ROW

878.27
244.33

875.75
236.77

875.73
226.76

902.05
134.06

903.14
105.91

903.48
93.89

903.82
81.88

904.17
69.86

904.37
63.00

904.73
48.00

907.17
51.00
906.23
48.00
906.31
42.72

5142+00.00


260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.77

8:25:28 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.78

8:25:29 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080
Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

910 900 890 880 870 860

Existing ROW

870.93
215.58

870.10
213.08

870.10
203.08

893.30
121.86

894.52
91.34

894.88
79.33

895.24
67.32

895.37
63.00

895.73
48.00

898.17
51.00

897.93
48.00

897.31
42.79

5145+00.00

Proposed ROW

871.62
218.31

871.00
216.43

871.00
206.43

894.74
123.23

895.96
93.45

896.32
81.43

896.68
69.42

896.87
63.00

897.23
48.00

899.67
51.00

898.93
48.00

898.81
42.75

5144+50.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.79

8:25:31 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

900 890 880 870 860

Existing ROW

868.01
207.13

867.40
205.27

867.40
195.27

888.83
120.27

890.14
87.51

890.50
75.61

893.67
51.00
891.23
48.00

5146+50.00

Existing ROW

868.87
209.22

868.30
207.50

868.30
197.50

890.33
120.38

891.61
88.37

891.97
76.36

895.17
51.00
892.73
48.00

5146+00.00

Existing ROW

869.71
211.65

869.20
210.10

869.20
200.10

891.82
120.91

893.07
89.64

893.43
77.64

893.79
63.00

896.67
51.00
894.23
48.00

5145+50.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.80

8:25:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

900 890 880 870 860

Existing ROW

866.65 205.38

864.70 199.52

864.70 189.52

884.27 121.00

884.30 120.85

885.65 87.00

886.01 75.00

886.37 63.00

886.73 48.00

889.17 51.00

888.23 48.00

888.31 42.78

5148+00.00

Existing ROW

866.99 205.81

865.60 201.62

865.60 191.62

885.77 121.00

885.80 120.85

887.15 87.00

887.51 75.00

887.87 63.00

888.23 48.00

890.67 51.00

889.73 48.00

889.81 42.81

5147+50.00

Existing ROW

867.84 207.46

866.50 203.42

866.50 193.42

887.34 121.00

887.37 120.57

888.65 87.07

889.01 75.07

889.37 63.00

889.73 48.00

892.17 51.00

891.23 48.00

891.31 42.93

5147+00.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.81

8:25:33 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

890 880 870 860 850

Existing ROW

864.25 200.12

862.00 193.36

862.00 183.36

879.81 121.00

879.84 120.85

881.19 87.00

881.55 75.00

881.91 63.00

882.27 48.00

884.71 51.00

883.77 48.00

883.85 42.79

5149+50.00

Existing ROW

865.35 202.73

862.90 195.35

862.90 185.36

881.28 121.00

881.31 120.85

882.66 87.00

883.02 75.00

883.38 63.00

883.74 48.00

886.18 51.00

885.24 48.00

885.32 42.78

5149+00.00

900 890 880 870 860

Existing ROW

865.76 203.30

863.80 197.42

863.80 187.42

882.77 121.00

882.80 120.85

884.15 87.00

884.51 75.00

884.87 63.00

885.23 48.00

887.67 51.00

886.73 48.00

886.81 42.81

5148+50.00


260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER W.82

8:25:35 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

ML080

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.83

8:25:36 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

SUR080

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.84

8:25:38 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

SUR080

Preliminary

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

940
930
920

929.20
123.15

927.29
117.43

927.29
107.43

932.56
89.00

935.99
69.00

936.29
65.00

1068+00.00

940
930
920

934.88
153.52

925.24
124.61

925.24
114.61

932.45
89.40

935.78
69.40

936.18
65.40

1067+50.00

Existing
ROW

940
930
920

934.56
165.40

923.19
131.30

923.19
121.30

932.26
89.55

935.60
69.55

936.00
65.55


1067+00.00

260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	W.85

8:25:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194W02.sht

Chichaqua Valley Trail
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.1

8:25:48 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

Chichaqua Valley Trail


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.2

8:25:48 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


Chichaqua Valley Trail
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.3

8:25:49 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

Chichaqua Valley Trail
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.4

8:25:49 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

NE 54th Avenue

Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

970 960 950 940

Proposed ROW

957.57 143.98

948.95 118.11

948.95 108.11

953.92 93.18

2239+00.00

Proposed ROW

Proposed ROW

Proposed ROW

957.92 149.29

949.20 124.03

949.20 114.03

954.25 98.87

2238+50.00

958.37 142.32

949.45 115.55

949.45 105.55

954.58 90.16

2238+00.00

958.52 142.97

949.50 115.40

949.50 105.40

954.65 89.96


2237+90.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.5

8:25:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

NE 54th Avenue


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.6

8:25:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


NE 54th Avenue
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.7

8:25:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


NE 54th Avenue
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.8

8:25:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


NE 54th Avenue
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.9

8:25:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


NE 29th Street
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.10

8:25:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

NE 29th Street
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.11

8:25:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

Special Ditch NE 54th Ave.

Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.12

8:25:53 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht

Special Ditch NE 54th Ave.


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.13

8:25:53 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


Special Ditch Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	X.14

8:26:10 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


Special Ditch Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER X.15

8:26:10 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194X01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.1

8:26:53 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.2

8:26:55 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.3

8:26:56 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.4

8:26:58 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.5

8:26:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.6

8:27:00 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.7

8:27:02 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.8

8:27:03 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp A
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.9

8:27:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp A


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.10

8:27:06 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.11

8:27:07 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER Y.12

8:27:08 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.13

8:27:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER Y.14

8:27:11 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp A
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.15

8:27:12 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp A


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.16

8:27:13 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp A
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.17

8:27:14 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.18

8:27:16 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.19

8:27:17 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.20

8:27:18 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.21

8:27:19 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.22

8:27:20 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.23

8:27:22 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.24

8:27:23 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.25

8:27:24 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.26

8:27:25 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.27

8:27:26 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.28

8:27:28 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.29

8:27:29 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B
Preliminary

960.40
0.00

Existing ROW

Proposed ROW

32590+50.00

960.30
0.00

954.44
39.47

954.44
23.00

947.20
66.51

Existing ROW

941.65
66.83

941.65
76.83

943.14
81.31

Proposed ROW

32590+34.70

958.52
38.00

960.07
0.00

948.49
73.10

Existing ROW

959.00
35.13

958.31
16.00

957.57
0.00

956.99
12.58

956.31
27.28

943.00
80.32

942.00
77.36

942.00
87.36

Proposed ROW

32590+00.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.30

8:27:30 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp B
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

970 960 950 940 930

961.19
0.00

Proposed
ROW

32592+00.00

961.00
0.00

Proposed
ROW

32591+50.00

960.72
0.00


Proposed
ROW

32591+00.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.31

8:27:31 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.32

8:27:32 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp B
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.33

8:27:33 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.34

8:27:35 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.35

8:27:36 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

970 960 950 940 930

961.09
0.00

Proposed ROW

Existing ROW

38559+50.00

960.93
0.00

Existing ROW

Proposed ROW

38559+09.03

960.88
0.00

957.77
27.47

958.31
3.40

958.38
0.00

958.62
12.00

958.86
24.00

959.17
39.57

955.75
49.82

Existing ROW

Proposed ROW

935.36
94.56

38559+00.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.36

8:27:37 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G

Preliminary

osed
)W

937.19
126.58

932.46
112.41

932.46
102.41

961.03
0.00

955.18
23.43

Existing
ROW

38560+68.04

961.09
0.00

Existing
ROW

Existing
ROW

38560+50.00


961.16
0.00

38560+00.00

FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.37

8:27:38 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.38

8:27:39 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G


Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.39

8:27:40 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.40

8:27:42 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.41

8:27:43 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.42

8:27:44 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.43

8:27:45 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.44

8:27:46 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER Y.45

8:27:48 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.46

8:27:49 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.47

8:27:50 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.48

8:27:51 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.49

8:27:52 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.50

8:27:53 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.51

8:27:55 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.52

8:27:56 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.53

8:27:57 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.54

8:27:58 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.55

8:27:59 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.56

8:28:00 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.57

8:28:02 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.58

8:28:03 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.59

8:28:04 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G
Preliminary

140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140

940
930
920
910

932.83
0.00

Existing
ROW

38632+50.00

933.74
0.00

Existing
ROW

38632+00.00

934.39
0.00


Existing
ROW

38631+50.00

FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.60

8:28:05 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.61

8:28:06 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.62

8:28:07 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht


Ramp G
Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.63

8:28:09 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G
Preliminary




FILE NO.	ENGLISH	DESIGN TEAM Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER IM-035-3(194)87--13-77	SHEET NUMBER Y.64

8:28:10 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht

Ramp G

Preliminary



FILE NO.	ENGLISH	DESIGN TEAM	Iowa DOT\HDR	POLK COUNTY	PROJECT NUMBER	IM-035-3(194)87--13-77	SHEET NUMBER	Y.65

8:28:11 AM 10/15/2021 JWINKELM pw://HDR_US_Central_01/3047/10195812/77035194Y01.sht