

BRIDGE APPROACH REPAIR
 MBIN-035-1(514)157--OM-35

LETTING DATE
 01-20-2021

FRANKLIN COUNTY

FRANKLIN COUNTY

LEGEND

INTERSTATE HIGHWAY	
PRIMARY HIGHWAY-DIVIDED	
PRIMARY HIGHWAY	
PORTLAND CEMENT CONCRETE ROAD	
ASPHALT ROAD	
BITUMINOUS ROAD	
GRAVEL ROAD	
EARTHEN ROAD	
INTERSTATE HIGHWAY	
UNITED STATES HIGHWAY	
STATE HIGHWAY	
COUNTY HIGHWAY	
RAILROAD	
PIPELINE	
AIRPORT	
HYDROLOGY	
BRIDGE	
STATE BOUNDARY	
COUNTY BOUNDARY	
CORPORATE BOUNDARY	
TOWNSHIP LINE	
SECTION LINE	
ROAD NAMES	
UNINCORPORATED PLACE	
	ABBAY ROAD
	ELWOOD



PLANS OF PROPOSED IMPROVEMENTS ON THE
INTERSTATE ROAD SYSTEM
 FRANKLIN COUNTY
 BRIDGE APPROACH REPAIR
 CO. RD. S13 OVER I-35
 5.2 MILES NORTH OF JCT. SR C70

THE IOWA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY AND BRIDGE CONSTRUCTION, SERIES 2015, PLUS APPLICABLE GENERAL SUPPLEMENTAL SPECIFICATIONS, DEVELOPMENTAL SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS SHALL APPLY TO CONSTRUCTION WORK ON THIS PROJECT.

TOTAL SHEETS	13
PROJECT NUMBER	MBIN-035-1(514)157--OM-35
R.O.W. PROJECT NUMBER	
PROJECT IDENTIFICATION NUMBER	17-35-035-010

NO.	DESCRIPTION
1	TITLE SHEET
2	BRIDGE ESTIMATE SHEET
2	BRIDGE SHEET
C.1	ESTIMATE SHEET FOR ROADWAY
A.1 - U.3	ROADWAY SHEETS

REVISIONS

IOWA ONE CALL
 1-800-292-8989
 www.iowaonecall.com
 811 Know what's below. Call before you dig.

REVISIONS TO THIS DESIGN PLAN AND/OR PROJECT SPECIFICATIONS SHOULD BE SUBMITTED BY _____


STANDARD ROAD PLANS
 STANDARD ROAD PLANS ARE LISTED ON SHEET NUMBER C.1

DESIGN DATA RURAL

2017 AADT	460	V.P.D.
TRUCKS	24	%

INDEX OF SEALS

SHEET NO.	NAME	TYPE
I	JAREMY D. KOTTA	STRUCTURAL DESIGN
A.1	BRIAN BIRKLAND	ROADWAY DESIGN



PROJECT DIRECTORY NAME: 3503501017

STRUCTURAL DESIGN

I hereby certify that this engineering report was prepared by me or under my direct personal supervision and that I am a duly licensed Professional Engineer under the laws of the State of Iowa.

Signature: Jeremy D. Kotta Date: _____
 Printed Name: Jeremy D. Kotta

My license renewal date is December 31, 2021

Pages or sheets covered by this seal: SHEETS 1 THRU 2

PRELIMINARY NOT FOR CONSTRUCTION

GENERAL NOTES:

THIS DESIGN IS FOR REPAIRS TO THE EXISTING 314'-0" x 30'-0" CONTINUOUS WELDED PLATE GIRDER BRIDGE LOCATED IN FRANKLIN COUNTY ON CO. RD. S13 OVER I-35.

ELECTRONIC COPIES OF ORIGINAL DESIGN PLANS AND REPAIR PLANS WILL BE MADE AVAILABLE TO THE CONTRACTOR AS PART OF THE E-FILES SUPPLIED WITH THE CONTRACT DOCUMENTS. DIMENSIONS SHOWN ON THESE PLANS ARE BASED ON DESIGN PLANS (ORIGINAL DESIGN NO. 2970 AND REPAIR DESIGN NO. 304).

SEE THIS SHEET FOR LIST OF REPAIR ITEMS.

FAINT LINES ON PLANS INDICATE EXISTING PORTIONS OF THE BRIDGE.

ALL DIMENSIONS AND DETAILS SHOWN ON THESE PLANS PERTINENT TO NEW CONSTRUCTION SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR BEFORE STARTING CONSTRUCTION.

THE UTILITY COMPANIES WHOSE FACILITIES ARE SHOWN ON THE PLANS OR KNOWN TO BE WITHIN THE CONSTRUCTION LIMITS SHALL BE NOTIFIED BY THE BRIDGE CONTRACTOR OF THE STARTING DATE.

THE TOP AND INTERIOR FACES OF THE CONCRETE RAILING ARE TO BE CLEANED AND SEALED IN ACCORDANCE WITH ARTICLE 2403.03, P, OF THE STANDARD SPECIFICATIONS. ALL COSTS ASSOCIATED WITH CLEANING AND SEALING OF THE CONCRETE RAILS SHALL BE INCLUDED IN THE UNIT PRICE BID ITEM "MOBILIZATION".

IN ADDITION TO THE REQUIREMENTS OF ARTICLE 2413.03, G, OF THE STANDARD SPECIFICATIONS, BOTH EXPOSED ABUTMENT BRIDGE SEATS AND WASH SURFACES SHALL HAVE AN APPLICATION OF CONCRETE SEALER IN ACCORDANCE WITH ARTICLE 2403.03, P, 3, OF THE STANDARD SPECIFICATIONS.

SPECIFICATIONS:

DESIGN: AASHTO SERIES 2002.


CONSTRUCTION: IOWA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY AND BRIDGE CONSTRUCTION, SERIES 2015, PLUS APPLICABLE GENERAL SUPPLEMENTAL SPECIFICATIONS, DEVELOPMENTAL SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS SHALL APPLY TO CONSTRUCTION WORK ON THIS PROJECT.

ESTIMATED BRIDGE QUANTITIES


ITEM NO.	ITEM CODE	ITEM	UNIT	TOTAL	AS BUILT QUANTITY
1	2533-4980005	MOBILIZATION	LS	1.00	

ESTIMATE REFERENCE INFORMATION:

ITEM NO.	DESCRIPTION
1	INCLUDES CLEANING EXISTING CONCRETE RAILS AND ABUTMENT BRIDGE SEATS AS NOTED AND SHOWN IN THESE PLANS, AND FURNISHING AND PLACING CONCRETE SEALER.



DETAILS OF CONCRETE SEALER AREA



SITUATION PLAN

DESIGN HISTORY AT THIS SITE
(INCLUDES THIS DESIGN)

DES. NO.	TYPE OF WORK
2970	ORIGINAL DESIGN
304	RETROFIT BARRIER RAIL
---	BRIDGE APPROACH REPAIR

TRAFFIC ESTIMATE

2017 AADT	460	V.P.D.
TRUCKS	24	%

REPAIRS SHALL CONSIST OF:

- ① REMOVE AND REPLACE FIRST TWO PANELS OF BOTH APPROACHES.
- ② CLEAN & SEAL BARRIER RAILS AND ABUTMENT BRIDGE SEATS.
- ③ REMOVE AND REINSTALL EXISTING GUARDRAIL.
- ④ PAVE FROM THE EDGE OF PAVEMENT TO GUARDRAIL POSTS.
- ⑤ REPLACE ALL FOUR BRIDGE END DRAINS WITH ROCK FLUMES.

TRAFFIC CONTROL PLAN:
THE ROADWAY WILL BE CLOSED TO THRU TRAFFIC. REFER TO THE TRAFFIC CONTROL PLAN SHOWN ELSEWHERE IN THESE PLANS.

ROADWAY QUANTITIES SHOWN ELSEWHERE IN THESE PLANS.

LOCATION:

CO. RD. S13 OVER I-35
T-90N, R-22W
SECTION 6
OAKLAND TOWNSHIP
FRANKLIN COUNTY
MAINT. NO. 3556.70035
FHWA NO. 602425
LATITUDE 42.630188°
LONGITUDE -93.483341°

DESIGN FOR REPAIRS TO A 21°14' SKEW (L.A.)
308'-0" x 30'-0" CONTINUOUS WELDED GIRDER BRIDGE
54'-0" END SPANS 2-100'-0" INTERIOR SPANS
QUANTITIES, NOTES & SITUATION PLAN
STA. 20075+66.51 (CL SURVEY - LOCAL ROAD) NOVEMBER, 2020
STA. 75+66.51 (CL SURVEY - I-35)
FRANKLIN COUNTY
IOWA DEPARTMENT OF TRANSPORTATION - HIGHWAY DIVISION
DESIGN SHEET NO. 1 OF 1 FILE NO. DESIGN NO.



INDEX OF SHEETS	
No.	DESCRIPTION
A Sheets	Title Sheets
A.1	Roadway Title Sheet
B Sheets	Typical Cross Sections and Details
B.1	Detail 7156
C Sheets	Quantities and General Information
C.1	Project Description
C.1	Estimated Roadway Quantities
C.1	Estimate Reference Information
C.1	General Notes and Standard Road Plans
C.1	Index of Tabulations
C.1 - 3	Tabulations
D Sheets	Mainline Plan and Profile Sheets
* D.1	Co. Rd. S13 / C55 Plan Sheet
J Sheets	Traffic Control and Staging Sheets
J.1	Traffic Control Plan
J.1	511 Travel Restrictions
* J.2	Detour Plan
U Sheets	500 Series, Mod.Stds. and Detail Sheets
U.1 - 3	Bridge Approach, As Per Plan
	* Color Plan Sheets




I hereby certify that this plan was prepared by me or under my direct personal supervision and that I am a duly licensed Professional Engineer under the laws of the State of Iowa.

Signature: Brian J. Birkland Date: _____

Printed or Typed Name: _____

My license renewal date is December 31, 2020

Pages or sheets covered by this seal: A.1, B.1, C.1-C.3, D.1, J.1-J.2, U.1-U.3



PLAN VIEW


9" HMA Paved Shoulder at guardrail. 8" PCC may be substituted with the following jointing layout:

Match mainline pavement joint spacing. When mainline pavement is 8" or greater in thickness, place additional transverse 'C' joints in shoulder at mid-panel of the mainline pavement. Place longitudinal 'C' joint at P/2 from edge of mainline pavement when P is greater than 10' wide. Terminate longitudinal joint at transverse joint less than 10' in length.


Compaction of HMA is required to face of guardrail post. Hand compaction will be allowed under guardrail. Removal and reinstallation of guardrail will be allowed with no additional payment.

Refer to Tabulation 112-9 for shoulder quantities.

- ① For subgrade treatment, refer to other details in the plan.
- ② PCC option only: When guardrail posts are installed prior to construction of PCC paved shoulder, fasten form board to the face of guardrail posts for the length shown. Refer to note 4 for final 2 posts.
- ③ Continue paved shoulder to existing paved shoulder or 20 feet beyond the center of the first post.
- ④ Shoulder may be notched for final 2 posts or post sleeves may be installed through pavement. Do not drive posts through pavement.
- ⑤ 'KT-1 joint for PCC shoulder.
'B' joint for HMA shoulder.




Section A-A




Section B-B

NEW CONSTRUCTION




Section A-A



Section B-B

EXISTING SHOULDER



Section C-C

Roll down at granular shoulder or earth.

PAVED SHOULDER AT GUARDRAIL

100-1D 10-18-05
PROJECT DESCRIPTION
This project is for bridge and roadway repair for the 314' x 30' Continuous Welded Plate Girder Bridge on Co. Rd. S13 / C55 over I-35, 5.0 mi. N of Jct. Co. Rd. C70.

100-0A 10-28-97																																																																																										
ESTIMATED ROADWAY QUANTITIES (1 DIVISION PROJECT)																																																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Item No.</th> <th>Item Code</th> <th>Item</th> <th>Unit</th> <th>Total</th> <th>As Built Qty.</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2102-2713090</td> <td>EXCAVATION, CLASS 13, WASTE</td> <td>CY</td> <td>100.2</td> <td></td> </tr> <tr> <td>2</td> <td>2122-5190501</td> <td>PAVED SHOULDER, PORTLAND CEMENT CONCRETE (PAVED SHOULDER PANEL FOR BRIDGE END DRAIN)</td> <td>SY</td> <td>76.8</td> <td></td> </tr> <tr> <td>3</td> <td>2122-5500090</td> <td>PAVED SHOULDER, HOT MIX ASPHALT MIXTURE, 9 IN.</td> <td>SY</td> <td>301.4</td> <td></td> </tr> <tr> <td>4</td> <td>2123-7450000</td> <td>SHOULDER CONSTRUCTION, EARTH</td> <td>STA</td> <td>2.72</td> <td></td> </tr> <tr> <td>5</td> <td>2301-0685550</td> <td>BRIDGE APPROACH PAVEMENT, AS PER PLAN</td> <td>SY</td> <td>237.2</td> <td></td> </tr> <tr> <td>6</td> <td>2401-6745065</td> <td>REMOVAL OF BRIDGE END DRAINS</td> <td>EACH</td> <td>4</td> <td></td> </tr> <tr> <td>7</td> <td>2503-0500402</td> <td>BRIDGE END DRAIN, DR-402</td> <td>EACH</td> <td>4</td> <td></td> </tr> <tr> <td>8</td> <td>2510-6745850</td> <td>REMOVAL OF PAVEMENT</td> <td>SY</td> <td>239.0</td> <td></td> </tr> <tr> <td>9</td> <td>2518-6910000</td> <td>SAFETY CLOSURE</td> <td>EACH</td> <td>2</td> <td></td> </tr> <tr> <td>10</td> <td>2527-9263109</td> <td>PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT-BASED</td> <td>STA</td> <td>3.20</td> <td></td> </tr> <tr> <td>11</td> <td>2528-8445110</td> <td>TRAFFIC CONTROL</td> <td>LS</td> <td>1.00</td> <td></td> </tr> <tr> <td>12</td> <td>2602-0000312</td> <td>PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 12 IN. DIA.</td> <td>LF</td> <td>540.0</td> <td></td> </tr> <tr> <td>13</td> <td>2602-0000320</td> <td>PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 20 IN. DIA.</td> <td>LF</td> <td>150.0</td> <td></td> </tr> <tr> <td>14</td> <td>2602-0000350</td> <td>REMOVAL OF PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE</td> <td>LF</td> <td>690.0</td> <td></td> </tr> </tbody> </table>	Item No.	Item Code	Item	Unit	Total	As Built Qty.	1	2102-2713090	EXCAVATION, CLASS 13, WASTE	CY	100.2		2	2122-5190501	PAVED SHOULDER, PORTLAND CEMENT CONCRETE (PAVED SHOULDER PANEL FOR BRIDGE END DRAIN)	SY	76.8		3	2122-5500090	PAVED SHOULDER, HOT MIX ASPHALT MIXTURE, 9 IN.	SY	301.4		4	2123-7450000	SHOULDER CONSTRUCTION, EARTH	STA	2.72		5	2301-0685550	BRIDGE APPROACH PAVEMENT, AS PER PLAN	SY	237.2		6	2401-6745065	REMOVAL OF BRIDGE END DRAINS	EACH	4		7	2503-0500402	BRIDGE END DRAIN, DR-402	EACH	4		8	2510-6745850	REMOVAL OF PAVEMENT	SY	239.0		9	2518-6910000	SAFETY CLOSURE	EACH	2		10	2527-9263109	PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT-BASED	STA	3.20		11	2528-8445110	TRAFFIC CONTROL	LS	1.00		12	2602-0000312	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 12 IN. DIA.	LF	540.0		13	2602-0000320	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 20 IN. DIA.	LF	150.0		14	2602-0000350	REMOVAL OF PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE	LF	690.0	
Item No.	Item Code	Item	Unit	Total	As Built Qty.																																																																																					
1	2102-2713090	EXCAVATION, CLASS 13, WASTE	CY	100.2																																																																																						
2	2122-5190501	PAVED SHOULDER, PORTLAND CEMENT CONCRETE (PAVED SHOULDER PANEL FOR BRIDGE END DRAIN)	SY	76.8																																																																																						
3	2122-5500090	PAVED SHOULDER, HOT MIX ASPHALT MIXTURE, 9 IN.	SY	301.4																																																																																						
4	2123-7450000	SHOULDER CONSTRUCTION, EARTH	STA	2.72																																																																																						
5	2301-0685550	BRIDGE APPROACH PAVEMENT, AS PER PLAN	SY	237.2																																																																																						
6	2401-6745065	REMOVAL OF BRIDGE END DRAINS	EACH	4																																																																																						
7	2503-0500402	BRIDGE END DRAIN, DR-402	EACH	4																																																																																						
8	2510-6745850	REMOVAL OF PAVEMENT	SY	239.0																																																																																						
9	2518-6910000	SAFETY CLOSURE	EACH	2																																																																																						
10	2527-9263109	PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT-BASED	STA	3.20																																																																																						
11	2528-8445110	TRAFFIC CONTROL	LS	1.00																																																																																						
12	2602-0000312	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 12 IN. DIA.	LF	540.0																																																																																						
13	2602-0000320	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 20 IN. DIA.	LF	150.0																																																																																						
14	2602-0000350	REMOVAL OF PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE	LF	690.0																																																																																						

111-25 10-18-11																																													
INDEX OF TABULATIONS																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Tabulation</th> <th>Tabulation Title</th> <th>Sheet No.</th> </tr> </thead> <tbody> <tr> <td>C Sheets</td> <td></td> <td></td> </tr> <tr> <td>100-0A</td> <td>ESTIMATED ROADWAY QUANTITIES (1 DIVISION PROJECT)</td> <td>C.1</td> </tr> <tr> <td>100-1D</td> <td>PROJECT DESCRIPTION</td> <td>C.1</td> </tr> <tr> <td>100-4A</td> <td>ESTIMATE REFERENCE INFORMATION</td> <td>C.1</td> </tr> <tr> <td>100-19</td> <td>PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE</td> <td>C.2</td> </tr> <tr> <td>104-8A</td> <td>SCOUR PROTECTION OR ROCK FLUME FOR BRIDGE END DRAIN</td> <td>C.2</td> </tr> <tr> <td>105-4</td> <td>STANDARD ROAD PLANS</td> <td>C.1</td> </tr> <tr> <td>108-13A</td> <td>SAFETY CLOSURES</td> <td>C.2</td> </tr> <tr> <td>108-22</td> <td>PAVEMENT MARKING LINE TYPES</td> <td>C.3</td> </tr> <tr> <td>110-1</td> <td>REMOVAL OF PAVEMENT</td> <td>C.2</td> </tr> <tr> <td>110-2</td> <td>REMOVAL OF EXISTING STRUCTURES</td> <td>C.2</td> </tr> <tr> <td>111-25</td> <td>INDEX OF TABULATIONS</td> <td>C.1</td> </tr> <tr> <td>112-6</td> <td>BRIDGE APPROACH SECTION</td> <td>C.2</td> </tr> <tr> <td>112-9</td> <td>SHOULDERS</td> <td>C.3</td> </tr> </tbody> </table>	Tabulation	Tabulation Title	Sheet No.	C Sheets			100-0A	ESTIMATED ROADWAY QUANTITIES (1 DIVISION PROJECT)	C.1	100-1D	PROJECT DESCRIPTION	C.1	100-4A	ESTIMATE REFERENCE INFORMATION	C.1	100-19	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE	C.2	104-8A	SCOUR PROTECTION OR ROCK FLUME FOR BRIDGE END DRAIN	C.2	105-4	STANDARD ROAD PLANS	C.1	108-13A	SAFETY CLOSURES	C.2	108-22	PAVEMENT MARKING LINE TYPES	C.3	110-1	REMOVAL OF PAVEMENT	C.2	110-2	REMOVAL OF EXISTING STRUCTURES	C.2	111-25	INDEX OF TABULATIONS	C.1	112-6	BRIDGE APPROACH SECTION	C.2	112-9	SHOULDERS	C.3
Tabulation	Tabulation Title	Sheet No.																																											
C Sheets																																													
100-0A	ESTIMATED ROADWAY QUANTITIES (1 DIVISION PROJECT)	C.1																																											
100-1D	PROJECT DESCRIPTION	C.1																																											
100-4A	ESTIMATE REFERENCE INFORMATION	C.1																																											
100-19	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE	C.2																																											
104-8A	SCOUR PROTECTION OR ROCK FLUME FOR BRIDGE END DRAIN	C.2																																											
105-4	STANDARD ROAD PLANS	C.1																																											
108-13A	SAFETY CLOSURES	C.2																																											
108-22	PAVEMENT MARKING LINE TYPES	C.3																																											
110-1	REMOVAL OF PAVEMENT	C.2																																											
110-2	REMOVAL OF EXISTING STRUCTURES	C.2																																											
111-25	INDEX OF TABULATIONS	C.1																																											
112-6	BRIDGE APPROACH SECTION	C.2																																											
112-9	SHOULDERS	C.3																																											

262-6 10-18-05
UTILITIES (NOT A POINT 25 PROJECT)
This is NOT a POINT 25 project and is not subject to the provisions of IAC 761-115.25.

232-3A 04-16-19
EROSION CONTROL (RURAL SEEDING)
<p>Following the completion of work in a disturbed area and according to the seeding dates in Section 2601 of the Standard Specifications, place seed, fertilizer, and mulch on the disturbed area lying 8 feet adjacent to shoulder and median as follows:</p> <p>Place seed and fertilize according to the requirements of Article 2601.03,C,3 and Section 4169 of the Standard Specifications.</p> <p>Place mulch according to the requirements of Articles 2601.03,E,2,a and 4169.07,A of the Standard Specifications.</p> <p>Preparing the seedbed, furnishing and applying seed, fertilizer, and mulch are all incidental to mobilization and will not be paid for separately.</p>

232-3C 04-16-19
EROSION CONTROL (NATIVE GRASS SEEDING)
<p>Following the completion of work in a disturbed area and according to the seeding dates in Section 2601 of the Standard Specifications, place seed and mulch on the disturbed area lying 8 feet or more beyond the shoulder as follows:</p> <p>SEED MIX:</p> <p>Big bluestem (Andropogon gerardii) 6 lbs. PLS/Acre (7.0 kg/ha) Indiangrass (Sorghastrum nutans) 6 lbs. PLS/Acre (7.0 kg/ha) Little bluestem (Schizachyrium scoparium) 6 lbs. PLS/Acre (7.0 kg/ha) Partridge Pea (Chamaecrista fasciculata) 4 lbs. PLS/Acre (4.5 kg/ha) Sideoats grama (Bouteloua curtipendula) 4 lbs. PLS/Acre (4.5 kg/ha) Canada wildrye (Elymus canadensis) 2 lbs. PLS/Acre (2.2 kg/ha) Switchgrass (Panicum virgatum) 1 lbs. PLS/Acre (1.1 kg/ha) Oats (Avena sativa) 32 lbs./Acre (36.0 kg/ha)</p> <p>Furnish Big bluestem, Indiangrass, Canada wildrye and Little bluestem that is debarbed or equal to facilitate the application of seed.</p> <p>Furnish seed certified as Source Identified Class (Yellow Tag) Source G0-Iowa. Oats are excluded from this requirement.</p> <p>Place seed according to the requirements of Article 4169.02 of the Standard Specifications.</p> <p>Place mulch according to the requirements of Articles 2601.03,E,2,a and 4169.07,A of the Standard Specifications.</p> <p>Preparing the seedbed, furnishing and applying seed and mulch are incidental to mobilization and will not be paid for separately.</p>

100-4A 10-29-02																																													
ESTIMATE REFERENCE INFORMATION																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Item No.</th> <th>Item Code</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2102-2713090</td> <td>EXCAVATION, CLASS 13, WASTE This item is for excavation for placement of paved shoulders. Refer to Tab. 112-9 for details.</td> </tr> <tr> <td>2</td> <td>2122-5190501</td> <td>PAVED SHOULDER, PORTLAND CEMENT CONCRETE (PAVED SHOULDER PANEL FOR BRIDGE END DRAIN) Paved shoulder thickness shall be 10 inches. Refer to Tab. 104-8A for details.</td> </tr> <tr> <td>3</td> <td>2122-5500090</td> <td>PAVED SHOULDER, HOT MIX ASPHALT MIXTURE, 9 IN. Item is for paved shoulders adjacent to existing guardrail per detail 7156 on Sheet B.1. Refer to Tab. 112-9 for details.</td> </tr> <tr> <td>4</td> <td>2123-7450000</td> <td>SHOULDER CONSTRUCTION, EARTH Item is for earth shoulder construction adjacent to paved shoulders and existing guardrail posts. Refer to Tab. 112-9 for details.</td> </tr> <tr> <td>5</td> <td>2301-0685550</td> <td>BRIDGE APPROACH PAVEMENT, AS PER PLAN For Bridge Approach Pavement, as per Plan, constructed in accordance with the contract documents, the quantities shown in the contract documents will be considered the quantity placed, in square yards, and will be paid for at the contract unit price per square yard. The contract unit price shall be compensation for furnishing all tools, equipment, labor, and materials necessary for construction of the Bridge Approach Pavement in accordance with the contract documents. Removal and reinstallation of steel beam guardrail will be allowed with no additional payment. Refer to modified standard road plan BR-202 on the U Sheets and Tab. 112-6 for details.</td> </tr> <tr> <td>6</td> <td>2401-6745065</td> <td>REMOVAL OF BRIDGE END DRAINS Item is for removal of existing bridge end drains, pipes, and outlets adjacent to each corner of the bridge. Refer to Tab. 110-2 for details.</td> </tr> <tr> <td>7</td> <td>2503-0500402</td> <td>BRIDGE END DRAIN, DR-402 Item is for placement of rock flume bridge end drains adjacent to paved shoulder panels for bridge end drains. Refer to Tab. 104-8A for details.</td> </tr> <tr> <td>8</td> <td>2510-6745850</td> <td>REMOVAL OF PAVEMENT Refer to Tab 110-1 for details.</td> </tr> <tr> <td>9</td> <td>2518-6910000</td> <td>SAFETY CLOSURE Refer to Tab. 108-13A for details.</td> </tr> <tr> <td>10</td> <td>2527-9263109</td> <td>PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT-BASED Refer to Tab. 108-22 for details.</td> </tr> <tr> <td>11</td> <td>2528-8445110</td> <td>TRAFFIC CONTROL Refer to Traffic Control Plan on Sheet J.1.</td> </tr> <tr> <td>12</td> <td>2602-0000312</td> <td>PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 12 IN. DIA.</td> </tr> <tr> <td>13</td> <td>2602-0000320</td> <td>PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 20 IN. DIA.</td> </tr> <tr> <td>14</td> <td>2602-0000350</td> <td>REMOVAL OF PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE Refer to Tab. 100-19. The tabulation includes estimated locations for placement of Perimeter and Slope Sediment Control Device, 12 in. and 20 in. dia. to address erosion to be encountered during construction. Verify the specific locations with the Engineer prior to beginning placement. Bid item includes 25% additional quantity for field adjustments and replacements. Use Perimeter and Slope Sediment Control Devices fabricated using wood excelsior.</td> </tr> </tbody> </table>	Item No.	Item Code	Description	1	2102-2713090	EXCAVATION, CLASS 13, WASTE This item is for excavation for placement of paved shoulders. Refer to Tab. 112-9 for details.	2	2122-5190501	PAVED SHOULDER, PORTLAND CEMENT CONCRETE (PAVED SHOULDER PANEL FOR BRIDGE END DRAIN) Paved shoulder thickness shall be 10 inches. Refer to Tab. 104-8A for details.	3	2122-5500090	PAVED SHOULDER, HOT MIX ASPHALT MIXTURE, 9 IN. Item is for paved shoulders adjacent to existing guardrail per detail 7156 on Sheet B.1. Refer to Tab. 112-9 for details.	4	2123-7450000	SHOULDER CONSTRUCTION, EARTH Item is for earth shoulder construction adjacent to paved shoulders and existing guardrail posts. Refer to Tab. 112-9 for details.	5	2301-0685550	BRIDGE APPROACH PAVEMENT, AS PER PLAN For Bridge Approach Pavement, as per Plan, constructed in accordance with the contract documents, the quantities shown in the contract documents will be considered the quantity placed, in square yards, and will be paid for at the contract unit price per square yard. The contract unit price shall be compensation for furnishing all tools, equipment, labor, and materials necessary for construction of the Bridge Approach Pavement in accordance with the contract documents. Removal and reinstallation of steel beam guardrail will be allowed with no additional payment. Refer to modified standard road plan BR-202 on the U Sheets and Tab. 112-6 for details.	6	2401-6745065	REMOVAL OF BRIDGE END DRAINS Item is for removal of existing bridge end drains, pipes, and outlets adjacent to each corner of the bridge. Refer to Tab. 110-2 for details.	7	2503-0500402	BRIDGE END DRAIN, DR-402 Item is for placement of rock flume bridge end drains adjacent to paved shoulder panels for bridge end drains. Refer to Tab. 104-8A for details.	8	2510-6745850	REMOVAL OF PAVEMENT Refer to Tab 110-1 for details.	9	2518-6910000	SAFETY CLOSURE Refer to Tab. 108-13A for details.	10	2527-9263109	PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT-BASED Refer to Tab. 108-22 for details.	11	2528-8445110	TRAFFIC CONTROL Refer to Traffic Control Plan on Sheet J.1.	12	2602-0000312	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 12 IN. DIA.	13	2602-0000320	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 20 IN. DIA.	14	2602-0000350	REMOVAL OF PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE Refer to Tab. 100-19. The tabulation includes estimated locations for placement of Perimeter and Slope Sediment Control Device, 12 in. and 20 in. dia. to address erosion to be encountered during construction. Verify the specific locations with the Engineer prior to beginning placement. Bid item includes 25% additional quantity for field adjustments and replacements. Use Perimeter and Slope Sediment Control Devices fabricated using wood excelsior.
Item No.	Item Code	Description																																											
1	2102-2713090	EXCAVATION, CLASS 13, WASTE This item is for excavation for placement of paved shoulders. Refer to Tab. 112-9 for details.																																											
2	2122-5190501	PAVED SHOULDER, PORTLAND CEMENT CONCRETE (PAVED SHOULDER PANEL FOR BRIDGE END DRAIN) Paved shoulder thickness shall be 10 inches. Refer to Tab. 104-8A for details.																																											
3	2122-5500090	PAVED SHOULDER, HOT MIX ASPHALT MIXTURE, 9 IN. Item is for paved shoulders adjacent to existing guardrail per detail 7156 on Sheet B.1. Refer to Tab. 112-9 for details.																																											
4	2123-7450000	SHOULDER CONSTRUCTION, EARTH Item is for earth shoulder construction adjacent to paved shoulders and existing guardrail posts. Refer to Tab. 112-9 for details.																																											
5	2301-0685550	BRIDGE APPROACH PAVEMENT, AS PER PLAN For Bridge Approach Pavement, as per Plan, constructed in accordance with the contract documents, the quantities shown in the contract documents will be considered the quantity placed, in square yards, and will be paid for at the contract unit price per square yard. The contract unit price shall be compensation for furnishing all tools, equipment, labor, and materials necessary for construction of the Bridge Approach Pavement in accordance with the contract documents. Removal and reinstallation of steel beam guardrail will be allowed with no additional payment. Refer to modified standard road plan BR-202 on the U Sheets and Tab. 112-6 for details.																																											
6	2401-6745065	REMOVAL OF BRIDGE END DRAINS Item is for removal of existing bridge end drains, pipes, and outlets adjacent to each corner of the bridge. Refer to Tab. 110-2 for details.																																											
7	2503-0500402	BRIDGE END DRAIN, DR-402 Item is for placement of rock flume bridge end drains adjacent to paved shoulder panels for bridge end drains. Refer to Tab. 104-8A for details.																																											
8	2510-6745850	REMOVAL OF PAVEMENT Refer to Tab 110-1 for details.																																											
9	2518-6910000	SAFETY CLOSURE Refer to Tab. 108-13A for details.																																											
10	2527-9263109	PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT-BASED Refer to Tab. 108-22 for details.																																											
11	2528-8445110	TRAFFIC CONTROL Refer to Traffic Control Plan on Sheet J.1.																																											
12	2602-0000312	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 12 IN. DIA.																																											
13	2602-0000320	PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE, 20 IN. DIA.																																											
14	2602-0000350	REMOVAL OF PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE Refer to Tab. 100-19. The tabulation includes estimated locations for placement of Perimeter and Slope Sediment Control Device, 12 in. and 20 in. dia. to address erosion to be encountered during construction. Verify the specific locations with the Engineer prior to beginning placement. Bid item includes 25% additional quantity for field adjustments and replacements. Use Perimeter and Slope Sediment Control Devices fabricated using wood excelsior.																																											

105-4 10-18-11																											
STANDARD ROAD PLANS																											
The following Standard Road Plans apply to construction work on this project.																											
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Number</th> <th>Date</th> <th>Title</th> </tr> </thead> <tbody> <tr> <td>BR-211</td> <td>10-17-17</td> <td>Bridge Approach (Abutting PCC or Composite Pavement)</td> </tr> <tr> <td>DR-402</td> <td>10-15-19</td> <td>Rock Flume for Bridge End Drain</td> </tr> <tr> <td>EC-204</td> <td>04-21-20</td> <td>Perimeter and Slope Sediment Control Devices</td> </tr> <tr> <td>PM-110</td> <td>04-21-20</td> <td>Line Types</td> </tr> <tr> <td>PV-101</td> <td>04-21-20</td> <td>Joints</td> </tr> <tr> <td>SI-881</td> <td>04-16-19</td> <td>Special Signs for Workzones</td> </tr> <tr> <td>TC-1</td> <td>10-15-19</td> <td>Work Not Affecting Traffic (Two-Lane or Multi-Lane)</td> </tr> <tr> <td>TC-252</td> <td>04-21-20</td> <td>Routes Closed to Traffic</td> </tr> </tbody> </table>	Number	Date	Title	BR-211	10-17-17	Bridge Approach (Abutting PCC or Composite Pavement)	DR-402	10-15-19	Rock Flume for Bridge End Drain	EC-204	04-21-20	Perimeter and Slope Sediment Control Devices	PM-110	04-21-20	Line Types	PV-101	04-21-20	Joints	SI-881	04-16-19	Special Signs for Workzones	TC-1	10-15-19	Work Not Affecting Traffic (Two-Lane or Multi-Lane)	TC-252	04-21-20	Routes Closed to Traffic
Number	Date	Title																									
BR-211	10-17-17	Bridge Approach (Abutting PCC or Composite Pavement)																									
DR-402	10-15-19	Rock Flume for Bridge End Drain																									
EC-204	04-21-20	Perimeter and Slope Sediment Control Devices																									
PM-110	04-21-20	Line Types																									
PV-101	04-21-20	Joints																									
SI-881	04-16-19	Special Signs for Workzones																									
TC-1	10-15-19	Work Not Affecting Traffic (Two-Lane or Multi-Lane)																									
TC-252	04-21-20	Routes Closed to Traffic																									

PERIMETER AND SLOPE SEDIMENT CONTROL DEVICE						100-19 04-19-16
Possible Standards: EC-204						
Location			Length of Installation			Remarks
Begin Station	End Station	Side	9 inch Dia	12 inch Dia	20 inch Dia	
			LF	LF	LF	
20072+92.00	20074+02.00	Lt.		110.0		
20072+80.00	20073+90.00	Rt.		110.0		
20077+32.00	20078+42.00	Rt.		110.0		
20077+42.00	20078+52.00	Lt.		110.0		
20073+64.00	20073+64.00	Rt.			30.0	At bottom of rock flume
20073+76.00	20073+76.00	Lt.			30.0	At bottom of rock flume
20077+82.00	20077+82.00	Lt.			30.0	At bottom of rock flume
20077+55.00	20077+55.00	Rt.			30.0	At bottom of rock flume
			Subtotals:	440.0	120.0	
			25% contingency	100.0	30.0	
			Totals:	540.0	150.0	





REMOVAL OF EXISTING STRUCTURES			110-2 04-16-13
Location	Description	Remarks	
NW Corner of Bridge	Bridge End Drain & connected pipes/outlets	To Become Property of the Contractor, remove from site.	
SW Corner of Bridge	Bridge End Drain & connected pipes/outlets	To Become Property of the Contractor, remove from site.	
SE Corner of Bridge	Bridge End Drain & connected pipes/outlets	To Become Property of the Contractor, remove from site.	
NE Corner of Bridge	Bridge End Drain & connected pipes/outlets	To Become Property of the Contractor, remove from site.	



SCOUR PROTECTION OR ROCK FLUME FOR BRIDGE END DRAIN														104-8A 10-17-17	
Refer to Standard Road Plan DR-401 and DR-402															
Location		Bid Items			PCC Paved Shoulder			Scour Protection (DR-401)			Rock Flume (DR-402)			Remarks	
Bridge Station	Bridge Corner	Distance DI-1 or DI-2	PCC Paved Shoulder	Bridge End Drain	Panels Required	Polymer Grid	Modified Subbase	Special Ditch Control, Wood Excelsior Mat	Turf Reinforced Mat (TRM), Type 2	Transition Mat	Macadam Stone Base	Engineering Fabric	Erosion Stone		
															FT
20075+66.51	SW	42.1	25.9	DR-402	C & B		25.9	16.3				1.5	72.6	58.8	
20075+66.51	NW	50.4	12.5	DR-402	A		12.5	7.9				1.5	96.0	77.8	
20075+66.51	SE	50.4	12.5	DR-402	A		12.5	7.9				1.5	100.7	81.6	
20075+66.51	NE	42.1	25.9	DR-402	C & B		25.9	16.3				1.5	101.9	82.5	
Totals:			76.8									6.0	371.2	300.7	

REMOVAL OF PAVEMENT						110-1 04-16-13
Refer to Tabulation 102-5						
Begin Station	End Station	Side	Pavement Type	Area	Saw Cut*	Remarks
				SY	LF	
20073+70.00	20074+15.83	Both	PCC	119.5	22.0	
20077+17.19	20077+63.02	Both	PCC	119.5	22.0	
Total:				239.0	44.0	

SAFETY CLOSURES			108-13A 08-01-08
Refer to Section 2518 of the Standard Specifications			
Station	Closure Type		Remarks
	Road Qty.	Hazard Qty.	
20071+85.00	1		
20079+47.00	1		

BRIDGE APPROACH SECTION																		112-6 04-18-17				
Refer to the BR Series.																						
Location		Approach Pavement						Standard Road Plans BR Series			Subdrain				Remarks							
Bridge Station	End	Skew Ahead		Thickness	Pay Length	Non-Reinf. Pavement Area	Single-Reinf. Pavement Area	Double-Reinf. Pavement Area	Approach	Fixed or Movable Abutment	Abutting Pavement	Perforated Subdrain 4"	Subdrain Outlet		Porous Backfill	Class 'A' Crushed Stone Backfill	Modified Subbase	Polymer Grid	Special Backfill			
		Degrees											CY	CY						TON	SY	TON
		LEFT	RIGHT																			
20075+66.51	West	21.233		10.0	40.0	0.0	46.9	71.7	BR-202	Fixed	BR-211						118.8	133.1	0.000			
20075+66.51	East	21.233		10.0	40.0	0.0	46.9	71.7	BR-202	Fixed	BR-211						118.8	133.1	0.000			
Totals:							93.8	143.4	237.2													

-  PCC Bridge Approach
-  PCC Paved Shoulder for Bridge End Drain
-  HMA Shoulder Paving
-  Pavement Removal




108-23A 08-01-08	TRAFFIC CONTROL PLAN
<p>A. Co. Rd. S13 / C55 will be closed to traffic at the bridge utilizing standard road plan TC-252.</p> <p>B. The Contractor shall implement the detour of traffic in accordance with the route shown on sheet J.2.</p>	

111-01 04-17-12	COORDINATED OPERATIONS
<p>Other work in progress during the same period of time will include the construction of the projects listed. Coordinate operations with those of other contractors working within the same area.</p>	
Project	Type of Work
None Provided	

108-25 10-21-14	511 TRAVEL RESTRICTIONS
--------------------	--------------------------------

Route	Direction	County	Location Description	Feature Crossed	Object Type	Maint. Bridge No., Structure ID, or FHWA No.	Type of Restriction	Existing Measurement	Construction Measurement	Construction Measurement as Signed	Projected As Built Measurement	Remarks
Co. Rd. S13 / C55	Both	Franklin	Bridge over I-35	For Bridge Construction - Traffic Detoured	Barrier	602425	Horizontal	N/A	N/A	N/A	N/A	




Google Earth




DETOUR MAP

FILE NO.	ENGLISH	DESIGN TEAM	WHKS & CO.	FRANKLIN COUNTY	PROJECT NUMBER	MBIN-035-1(514)157--0M-35	SHEET NUMBER	J.2
12:07:08 PM 4/14/2020	bb1rkland	K:\8500.19\Franklin\13over1-35\Plans\35035514.dsn						



DETAIL 'A'
Fixed Abutment




DETAIL 'B'
FIXED ABUTMENT

- ① 2" to 2½" clear to bent bar.
- ② Minimum lap length: #5 bars - 18 inches
#6 bars - 27 inches
#8 bars - 48 inches
- ③ Place additional #5 bar parallel to skewed face.

MODIFIED	REVISION	
	1	10-17-17
STANDARD ROAD PLAN		BR-202
		SHEET 1 of 3
MODIFICATIONS: Removed Non-reinforced Section Removed Movable Abutment Detail Updated Notes		

**DOUBLE REINFORCED 10" APPROACH
WITH VARIABLE DEPTH PAVING NOTCH**







SECTION THRU CENTERLINE

MODIFIED	REVISION	
	1	10-17-17
STANDARD ROAD PLAN	BR-202	
SHEET 2 of 3		
MODIFICATIONS: Adjusted Pay Length Removed Section Adjacent to HMA Pavement Updated Notes		
DOUBLE REINFORCED 10" APPROACH WITH VARIABLE DEPTH PAVING NOTCH		







SECTION A-A



SECTION B-B




APPROACH PAVEMENT LAYOUT AT A SKEW




DETAIL 'D'
(Joint Placement)

- ⑤ Longitudinal Joint (PV-101):
Single pour - Saw cut joint per Detail B.
Two pours - Use 'KS-2' Joint.
- ⑥ Refer to BR-211.
- ⑦ Design shoulder width.
- ⑧ Reinforced bridge approach section.
- ⑨ Expansion joint at end of Bridge Rail End Section: Place joint filler the full depth of the bridge approach pavement. In areas with curb, place full depth of pavement plus curb and shape material to fit the shape of the curb per Section B-B of PV-101. Seal joint per Detail F of PV-101.


- Fixed Abutment Bridges: Type 'E' Joint.



BENT BAR SHAPES



DETAIL 'G'



DETAIL 'E'
(Back of Curb Placement)

MODIFIED STANDARD ROAD PLAN	REVISION	
	3	10-17-17
BR-202		Sheet 3 of 3

MODIFICATIONS: Updated Notes
Updated Detail 'E' for Existing Retrofit End

**DOUBLE REINFORCED 10" APPROACH
WITH VARIABLE DEPTH PAVING NOTCH**

